



**Maintenance item #150
Analysis and Response**

Craig Gunther (craig.gunther@harman.com)
January 2015, Atlanta

This presentation addresses Maintenance Request #150:

- http://www.ieee802.org/1/private/email_mq/msg00149.html
- <http://www.ieee802.org/1/files/public/docs2015/maint-messenger-session1-0115-v1.pdf>

The issues are with SRP-11 and SRP-12 of the SRP End station PICS (IEEE 802.1Q-2011, Annex B.10, page 1193):

- Cut-and-paste error from similar items in Bridge PICS (Annex A.31, page 1182),
- What is Talker behavior with regard to handling of Talker Advertise if sufficient resources are no longer available? Withdraw Talker Advertise or change to Talker Failed?
- If Transition to Talker Failed what goes in the Talker Failed FailureInformation (35.2.2.8.7)?

Bridges: *Talker Advertise* transition to *Talker Failed*

Bridge behavior is correctly defined and should not change. If a Bridge had been sending a Talker Advertise and resources on the corresponding egress port are no longer available the Talker Advertise shall transition to a Talker Failed with appropriate FailureInformation.

Bridges do not have the option to stop sending the Talker attributes when stream related resources are no longer available, they must transition from an Advertise to a Failed.

Talker: *Talker Advertise* transition to *Talker Failed*

The original intent of SRP with regards to handling a Talker Advertise when resources are no longer available was:

1. Withdraw the Talker Advertise, or
2. Withdraw the Talker Advertise and register a new Talker Failed, or
3. Transition from a Talker Advertise directly to a Talker Failed (see 35.2.6).

Agreed?

Assuming “yes”, let’s fix the problem...

Fix 1: Clause 35.1.2.1 Talkers

Add the following paragraph after the end station description of “a) Talker Advertise” and “b) Talker Failed”:

If a Talker is declaring a Talker Advertise for a stream and it has determined there is no longer enough bandwidth or resources available to support that stream it shall withdraw the Talker Advertise. The Talker may then declare a Talker Failed to keep Listeners informed of the status of the stream. A Talker is allowed to transition directly from a Talker Advertise to a Talker Failed without deregistering the Talker Advertise from the network (see 35.2.6).

Clause 35.1.2.1 is the only clause that reference end stations as Talkers. The remainder of Clause 35 describes bridge behavior, protocol definition and operation, and bridge attribute propagation (MAP).

Fix 2: Clause 35.2.2.8.7 FailureInformation

From IEEE Std 802-2014 Clause 3.1 Definitions:

station: An end station or bridge. See also: *bridge; end station.*

Modify 35.2.2.8.7 to refer to bridges and end stations:

At the point when a Talker Advertise Declaration is transformed into a Talker Failed Declaration, the ~~Bridge~~ station making the transformation adds information that indicates, to the Listeners registering the Talker Failed Declaration, the cause of the failure, and the identity of the ~~Bridge and Bridge Port~~ station at which the failure occurred. The subcomponents of the FailureInformation include:

a) The Bridge ID (13.24.1) of the Bridge, or MAC Address of the end station¹, that changed the Declaration Type from Advertise to Failed.

b) The Reservation Failure Code which is represented by a single octet containing the value shown in Table 35-6.

1. The most significant 16 bits are zero filled, the remaining 48 bits contain the MAC Address.

The “bits” wording of note 1 is similar to that found in Q-2014 Clause 14.2.5.

Fix 2 (continued): Related FailureInformation changes

There are several other locations that need to be modified. Those fixes could replace “Bridge ID” by “Bridge ID or end station MAC Address”, or replace “Bridge ID” by “station”.

- Table 12-14 references “Failed Bridge ID” and “Bridgeld”,
- Table 12-20 references “ieee8021SrpReservationFailureBridgeld” and “Bridge ID of Bridge”. I would suggest “Station” may be preferable here,
- Figure 35-2 references “Bridge ID”,
- Table 35-6 uses “Bridge” in descriptions and notes.

Fix 3: Annex B.10 SRP End stations PICS

SRP-11

Does the implementation update the Failure Information Bridge ID end station MAC Address and Code when a Talker Failed is declared? ~~in the event of insufficient bandwidth or resources through a Bridge?~~

Fix 4: Annex B.10 SRP End stations PICS

SRP-12

Does the implementation ~~it~~ create a Talker Failed in the event of insufficient bandwidth or resources ~~through a Bridge?~~

In addition:

- Change References from “35.2.4.3, 35-10” to “35.1.2.1”.
- Change from Mandatory to Optional, allowing “Yes[] No[]”.

This is a bit bigger of a change since an erroneously written Mandatory requirement is now being changed to a correctly written Optional requirement. If we decide to stay with Mandatory then my first suggested fix must be reworded.

My recommendation throughout this presentation is to make it Optional.




Harman International

Premium Solutions for Audio and Infotainment