

5.9 GHz DSRC Band Utilization Conceptual Proposals

Prepared for IEEE
802.11 Standard
Extension Study
Group and ASTM 5.9
GHz DSRC User's
Group and Writing
Group

5-9GHz_Public_Brf.PPT/9-7-99/bcash

5.9 GHz DSRC APPLICATION FUNCTIONAL CATEGORIES

- | | |
|--|---|
| <ul style="list-style-type: none"> • ACCESS POINT OPERATIONS <ul style="list-style-type: none"> - ACCESS CONTROL (+ IN/OUT TRACKING) • TRAFFIC MANAGEMENT <ul style="list-style-type: none"> - PROBE DATA COLLECTION - TRAFFIC INFORMATION - IN-VEHICLE SIGNING - WORK ZONE WARNING - HIGHWAY/RAIL INTERSECTION WARNING - ROAD CONDITION WARNING • TRAFFIC SIGNAL INTERFACE <ul style="list-style-type: none"> - INTERSECTION COLLISION AVOIDANCE - EMERGENCY VEHICLE SIGNAL PREEMPTION - TRANSIT VEHICLE SIGNAL PRIORITY • ELECTRONIC PAYMENT (In-motion) <ul style="list-style-type: none"> - TOLL COLLECTION - PARKING PAYMENT - RENTAL CAR PROCESSING • ELECTRONIC PAYMENT (Stationary) <ul style="list-style-type: none"> - GAS (FUEL) PAYMENT - FAST FOOD PAYMENT - PHARMACY DRIVE-THRU PAYMENT • MAINTENANCE <ul style="list-style-type: none"> - DIAGNOSTIC DATA - REPAIR-SERVICE RECORD - VEHICLE COMPUTER PROGRAM UPDATES - MAP and MUSIC DATA UPDATES | <ul style="list-style-type: none"> • COMMERCIAL VEHICLE OPERATIONS (In-motion) <ul style="list-style-type: none"> - ROLLOVER WARNING - MAINLINE SCREENING (WEIGH-STATION CLEARANCE) - BORDER CLEARANCE - ON-BOARD SAFETY DATA TRANSFER - UNIQUE CVO FLEET MANAGEMENT • COMMERCIAL VEHICLE OPERATIONS (Stationary) <ul style="list-style-type: none"> - DRIVER'S DAILY LOG - VEHICLE SAFETY INSPECTION - TRUCK TRACTOR-TRAILER INTERFACE • TRANSIT DATA TRANSFER <ul style="list-style-type: none"> - TRANSIT VEHICLE DATA TRANSFER - TRANSIT VEHICLE REFUELING • RAIL DATA TRANSFER <ul style="list-style-type: none"> - LOCOMOTIVE FUEL MONITORING - LOCOMOTIVE DATA TRANSFER • OTHER DATA TRANSFER <ul style="list-style-type: none"> - VEHICLE REGISTRATION TAG (formerly ELECTRONIC LICENSE PLATE) |
|--|---|

A

5-9GHz_Public_Brf.PPT/9-7-99/bcash

5.9 GHz DSRC APPLICATION RANGE and VEHICLE CATEGORIES

SHORT RANGE CORE APPLICATIONS (FOR ALL VEHICLES)

- ACCESS CONTROL
- PROBE DATA COLLECTION
- TRAFFIC INFORMATION
- TOLL COLLECTION
- GAS PAYMENT
- DRIVE-THRU PAYMENT*
- **VEHICLE REGISTRATION TAG (ELP)****
- IDB DATA TRANSFER*
 - DIAGNOSTIC DATA
 - REPAIR-SERVICE RECORD
 - VEHICLE COMPUTER PROGRAM UPDATES*
 - MAP and MUSIC DATA UPDATES*
- RENTAL CAR PROCESSING

APPLICATIONS FOR HEAVY TRUCKS, BUSES, TRAINS, EV (SHORT- EXT RANGE)

- **ROLLOVER WARNING**
- MAINLINE SCREENING
- BORDER CLEARANCE
- ON-BOARD SAFETY DATA TRANSFER
- UNIQUE CVO FLEET MANAGEMENT
- **TRACTOR TO TRAILER DATA TRANSFER***
- DRIVER'S DAILY LOG
- VEHICLE SAFETY INSPECTION
- TRANSIT VEHICLE DATA TRANSFER (gate)
- TRANSIT VEHICLE DATA TRANSFER (yard)
- TRANSIT VEHICLE REFUELING
- LOCOMOTIVE FUEL MONITORING
- TRANSIT VEHICLE SIGNAL PRIORITY

EXTENDED RANGE CORE APPLICATIONS (FOR ALL VEHICLES)

- **IN-VEHICLE SIGNING**
 - **WORK ZONE WARNING**
 - **HIGHWAY/RAIL INTERSECTION WARNING**
- **ROAD CONDITION WARNING***
- **INTERSECTION COLLISION AVOIDANCE**

APPLICATIONS FOR HEAVY TRUCKS, BUSES, TRAINS, EV (EXT & LONG RANGE)

- EMERGENCY VEHICLE SIGNAL PREEMPTION
- LOCOMOTIVE DATA TRANSFER

SHORT RANGE - < 50 ft
MEDIUM RANGE - 50 to 300 ft
EXTENDED RANGE - 300 to 1100 ft
LONG RANGE - 1100 to 3000 ft
CVO - Commercial Vehicle Operations

EV - Emergency Vehicles
THRU - Through
EXT - Extended
ELP - Electronic license Plate
* - New Item Since Last Revision

RED* - Vehicle to Vehicle
RED** - Vehicle to Vehicle
and Roadside to Vehicle
GREEN - One-Way
Communication from the
RSE to the OBE

A

5-9GHz Public Brf.PPT/9-7-99/bcash

SUMMARY OF 5.9 GHz DSRC APPLICATION REQUIREMENTS

- Nationally Compatible
- All Weather Operation
- Two-way (point to point) Communication
- One-way (roadside to vehicle) Communication
- Extremely low latency
- Secure (only authorized users can read transmitted data)
- Reliable (High MTBF and communications performance as indicated in the specific requirements)
- Maintainable (Low MTTR)
- Easy to use
- Scalable (grow from one to multiple lanes of service)
- Widely Installable (few incompatible sites)
- Multimodal (road, rail, aircraft [on the ground] and sea [canal, river, or port])
- Non-Interference with 915 MHz systems
- Non-Interference to incumbent (primary allocation) 5.9 GHz systems
- Minimize interference with secondary allocation 5.9 GHz systems
- Tolerant of inadvertent interference from incumbent 5.9 GHz systems
- Market acceptable cost (< \$100 for basic On-Board Equip.) A

5-9GHz Public Brf.PPT/9-7-99/bcash


SUMMARY OF 5.9 GHz DSRC APPLICATION REQUIREMENTS

Vehicle Location -- Yes.
Lane Discrimination -- Yes.
Traffic Speed -- 0 to 120 mph
Traffic Density -- 3000 v/h/l - (1 to 8 lanes).
Min. OBE longitudinal separation -- 6 ft (motorcycles) / 16 ft (other).
Min. OBE lateral separation -- 3 ft (motorcycles) / 10 ft (other).
RSE Density -- 1 /lane
Communication Modes - one-way and two-way
Transaction Size -- 500 Bits to 10 Mbits.
Max. No. of Messages -- limited by transaction size
Nominal RSE Transmission Range -- 5 to 1100 ft
Nominal OBE Reception Range -- 5 to 1100 ft
Special RSE Transmission Range -- 20 to 3000 ft (Emergency Vehicles and Rail)
Special OBE Reception Range -- 20 to 3000 ft (Emergency Vehicles and Rail)
Communication Zone Size -- 7 to 2980 ft
Nominal Beacon Separation Distance -- 50 to 5500 ft.
Special Beacon Separation Distance -- 50 to 15000 ft.

A

5-9GHz Public Brf.PPT/9-7-99/bcash

NARROWBAND OPTION 5.850 to 5.925 GHz DSRC BAND



* DL - Downlink UL - Uplink

A

5-9GHz Public Brf.PPT/9-7-99/bcash

NARROWBAND SPECIFICATIONS

NARROWBAND CANDIDATE A - ACTIVE (AM)

- RSE Maximum EIRP 44.77 dBm (30 W)
- OBE EIRP 3 dBm (10 mW) cars / 20 dBm (100 mw) Transit Vehicles / 44.77 (30W) EV
- Active
- Nominal Modulation - Dual Binary Signaling (OOK with alternating phase shift) downlink (DL) and uplink (UL)
- Optional Modulation - None
- OBE Sensitivity - -60 dBm (EV -75 dBm) with 15 dB front to back ratio in the antenna
- Active RSE Sensitivity - -75 dBm with 20 dB front to back ratio in the antenna
- S/I - 14 dB
- Vehicle Powered
- BW 75 MHz (5.850 - 5.925 GHz)
- 3 - 4 MHz DL channels and 1 - 12 MHz UL channel or 3 DL/UL channel pairs of 4 MHz w/37 MHz separation
- DL Data Rate - 1000 kbps nominal
- UL Data Rate - 1000 kbps nominal
- Two-way Range - 3 to 305 m (10 to 1000 ft); One-way Range - 3 to 325 m (10 to 1100 ft)
- EV Two-way Range - 3 to 2134 m (10 to 7000 ft)
- Band Sharing Strategy - Selection of alternate channels for adjacent zones . On-site Frequency Coordination. Isolation of Installations where possible. Use TDMA or CSMA to prevent interference between users in the zone.
- 3 Channel OBE Estimated Cost - \$50 to \$100

ABBREVIATIONS

RSE - Roadside Unit
 OBE - Onboard Unit
 EIRP - Effective Isotropic Radiated Power
 Dist. - Distance
 mod - modulated
 EV - Emergency Vehicle

A

5-9GHz Public Brf.PPT/9-7-99/bcash

NARROWBAND SPECIFICATIONS

NARROWBAND CANDIDATE B - ACTIVE (PSK)

- RSE Maximum EIRP 44.77 dBm (30 W)
- OBE EIRP 3 dBm (10 mW) cars / 20 dBm (100 mw) Transit Vehicles / 44.77 (30W) EV
- Active
- Nominal Modulation - DBPSK downlink (DL) and uplink (UL)
- Optional Modulation - DQPSK, D8PSK, D16PSK or D16QAM downlink (DL) and uplink (UL) (after initialization)
- OBE Sensitivity - -60 dBm (EV -75 dBm) with 15 dB front to back ratio in the antenna
- Active RSE Sensitivity - -75 dBm with 20 dB front to back ratio in the antenna
- S/I - 12 dB (for DBPSK)
- Vehicle Powered
- BW 75 MHz (5.850 - 5.925 GHz)
- 3 to 9 channel pairs: of 4 MHz UL and 4 MHz DL w/37 MHz
- DL Data Rate - 1000 kbps nominal (2000, and 4000 kbps optional)
- UL Data Rate - 1000 kbps nominal (2000, and 4000 kbps optional)
- Two-way Range - 3 to 305 m (10 to 1000 ft); One-way Range - 3 to 325 m (10 to 1100 ft)
- EV Two-way Range - 3 to 2134 m (10 to 7000 ft)
- Band Sharing Strategy - Selection of alternate channels for adjacent zones . On-site Frequency Coordination. Isolation of Installations where possible. Use TDMA or CSMA to prevent interference between users in the zone.
- 3 Channel OBE Estimated Cost - \$50 to \$100
- 9 Channel OBE Estimated Cost - \$150 to \$200 (\$300 to \$500 with optional capabilities)

ABBREVIATIONS

RSE - Roadside Unit
 OBE - Onboard Unit
 EIRP - Effective Isotropic Radiated Power
 Dist. - Distance
 mod - modulated
 EV - Emergency Vehicle

A

5-9GHz Public Brf.PPT/9-7-99/bcash

NARROWBAND SPECIFICATIONS

NARROWBAND CANDIDATE C - BACKSCATTER

- RSE Maximum EIRP 44.77 dBm (30 W)
- OBE EIRP -65 to -15 dBm
- Backscatter (1.5 MHz subcarrier used in backscatter)
- Nominal Modulation (DL)- Dual Binary Signaling (OOK with alternating phase shift) downlink
- Nominal Modulation (UL)- QPSK modulated subcarrier that AM modulates the reflected signal
- Optional Modulation - 8PSK or 16PSK uplink (UL) subcarrier (after initialization)
- OBE Sensitivity - -60 dBm with 15 dB front to back ratio in the antenna
- RSE Sensitivity - -90 dBm with 20 dB front to back ratio in the antenna
- S/I - Active Downlink: 14 dB
- S/I - Backscatter Uplink: 6 dB
- Vehicle Powered
- BW 75 MHz (5.850 - 5.925 GHz)
- 3 channel pairs: of 4 MHz UL and 4 MHz DL w/37 MHz
- DL Data Rate - 1000 kbps
- UL Data Rate - 500 kbps core nominal (1000 and 2000 kbps optional)
- Two-way Range - 3 to 90 m (10 to 300 ft); One-way Range - 3 to 325 m (10 to 1100 ft)
- Band Sharing Strategy - Selection of alternate channels for adjacent zones . On-site Frequency Coordination. Isolation of Installations where possible. Use TDMA or CSMA to prevent interference between users in the zone.
- 3 Channel OBE Estimated Cost - \$30 to < \$80

ABBREVIATIONS


RSE - Roadside Unit
 OBE - Onboard Unit
 EIRP - Effective Isotropic Radiated Power
 Dist. - Distance
 mod - modulated
 EV - Emergency Vehicle

5-9GHz Public Brf.PPT/9-7-99/bcash

A



NARROWBAND ACTIVE LINK BUDGET



**90 m (300 ft) Two-way Nominal Range
 (Uplink Power Limited)**






5-9GHz Public Brf.PPT/9-7-99/bcash

A












- ### ULTRAWIDEBAND SPECIFICATIONS
-
- #### ULTRAWIDEBAND
- RSE Maximum EIRP 4.5 dBm
 - OBE Maximum EIRP 4.5 dBm

 - Nominal Modulation - OOK Nano pulse


 - OBE Sensitivity - -53 dBm
 - RSE Sensitivity - -53 dBm
 - S/I - Active: 11 dB - 20 dB processing gain
 - Vehicle Powered
 - BW 75 MHz (5.850 - 5.925 GHz) or 200 MHz (5.725 to 5.925)
 - 1 downlink/uplink channel of 75 MHz or 200 MHz
 - Data Rate - 1000 kbps (2000 kbps optional)
 - Two-way Range - 3 m (10 ft)
 - Lateral Reuse Dist. - 3 m (10 ft) Inline tractor and trailer
 - Band Sharing Strategy - Operation over an extended band width and in a partially covered mobile environment with very low power levels and directional antennas prevents interfering with other RF links.
 - Estimated Cost - \$100 to \$200
-
- ABBREVIATIONS
- RSE - Roadside Unit
 OBE - Onboard Unit
 EIRP - Effective Isotropic Radiated Power
 Dist. - Distance
 mod - modulated
- A**
- 5-9GHz Public Brf.PPT/9-7-99/bcash



TRANSIT On-Board Equipment



RAIL ENGINE On-Board Equipment



On-Board Equipment (OBE) STRATEGY

Common Equipment Configuration

The type of application requirements range from simple transmit only and receive only to high data rate with overlapping communication zones. It may not be wise to design all devices for the most strenuous requirement if most will not be used that way and the price is more than the average user is willing to pay. The DSRC technique used should be matched to the difficulty of the application implementation as long as a basic national compatibility mode (precursor to interoperability) is included in each device.

Therefore, users should be able to acquire equipment which connects them to the applications they want at an attractive price and have national interoperability. They could then pay more for OBE that implement applications with more demanding requirements. So, if we can require that each application be implemented with one mode nationwide, the following configurations of equipment scale up the capability of a DSRC device from the least demanding to the most while maintaining interoperability with all simpler versions:

OBE TYPES	SHORT RANGE	MED RANGE	EXT RANGE	LONG RANGE	BASIC DATA RATE	HIGHER DATA RATES	DATA TO SPEECH	DISPLAY	VEHICLE BUS CONNECTION
A	X		X*		X		X		
B	X		X*		X		X	X	
C	X		X*		X		X	X	X
D	X	X	X		X		X		
E	X	X	X		X		X	X	
F	X	X	X		X	N	X	X	X
G	X	X	X		W	H	X	X	X
H	X	X	X		X	H	X	X	X

X* - DOWNLINK ONLY EXT - EXTENDED MED - MEDIUM N - Narrowband limit is 4 Mbps
 H - Wideband operation enables 5.5 and 11 Mbps W - No narrowband basic data rate - Wideband only

5-9GHz Public Brf.PPT/9-7-99/bcash

A

On-Board Equipment (OBE) STRATEGY

Special Equipment Configurations

Some devices have special requirements which are not shared by other applications and must be treated separately. Each of these special OBE types need to be interoperable only within its supported applications and may have a different physical layer interface and protocol from the common devices and other special types.

The following list identifies the devices with unique requirements and capabilities:

OBE TYPES	SHORT RANGE	MED RANGE	EXT RANGE	LONG RANGE	BASIC DATA RATE	LOWER DATA RATES	UNIQUE L1	UNIQUE L2 & L7	VEHICLE BUS CONNECTION
L	O	O	O	X	X		?	?	X
R*	X					X	X ¹	X ¹	
T*	X				X		X ²	X ²	X

X¹ - Maybe Backscatter
 X² - Ultrawideband
 T* - Tractor to Trailer ONLY
 R* - RFID Tag ONLY
 O - OPTIONAL
 ? - Some applications may use a unique layer / others may not
 EXT - EXTENDED
 MED - MEDIUM

5-9GHz Public Brf.PPT/9-7-99/bcash

A

On-Board Equipment (OBE) ASSIGNMENTS

SHORT RANGE CORE APPLICATIONS (FOR ALL VEHICLES)

OBE - TYPES A,B,C or as indicated

- ACCESS CONTROL
- PROBE DATA COLLECTION
- TRAFFIC INFORMATION
- TOLL COLLECTION
- GAS PAYMENT (R*)
- DRIVE-THRU PAYMENT
- VEHICLE REGISTRATION TAG (ELP)** (R*)
- IDB DATA TRANSFER
 - DIAGNOSTIC DATA
 - REPAIR-SERVICE RECORD
 - VEHICLE COMPUTER PROGRAM UPDATES
 - MAP and MUSIC DATA UPDATES (G/H)
- RENTAL CAR PROCESSING

EXTENDED RANGE CORE APPLICATIONS (FOR ALL VEHICLES) OBE - TYPES A,B,C

- IN-VEHICLE SIGNING
 - WORK ZONE WARNING
 - HIGHWAY/RAIL INTERSECTION WARNING
- ROAD CONDITION WARNING
- INTERSECTION COLLISION AVOIDANCE

APPLICATIONS FOR HEAVY TRUCKS, BUSES, TRAINS, EV (SHORT-EXT RANGE)

OBE - TYPES D,E,F or as indicated

- ROLLOVER WARNING
- MAINLINE SCREENING
- BORDER CLEARANCE
- ON-BOARD SAFETY DATA TRANSFER
- UNIQUE CVO FLEET MANAGEMENT (opt G/H)
- **TRACTOR TO TRAILER DATA TRANSFER* (T*)**
- DRIVER'S DAILY LOG
- VEHICLE SAFETY INSPECTION
- TRANSIT VEHICLE DATA TRANSFER (gate) (G/H)
- TRANSIT VEHICLE DATA TRANSFER (yard) (G/H)
- TRANSIT VEHICLE REFUELING
- LOCOMOTIVE FUEL MONITORING
- TRANSIT VEHICLE SIGNAL PRIORITY (F/G/H/L)

APPLICATIONS FOR HEAVY TRUCKS, BUSES, TRAINS, EV (LONG RANGE)

OBE - TYPE G,H,L

- EMERGENCY VEHICLE SIGNAL PREEMPTION (L)
- LOCOMOTIVE DATA TRANSFER (G/H/L)

SHORT RANGE - < 50 ft

MEDIUM RANGE - 50 to 300 ft

EXTENDED RANGE - 300 to 1100 ft

LONG RANGE - 1100 to 3000 ft

CVO - Commercial Vehicle Operations

5-9GHz Public Brf.PPT/9-7-99/bcash

EV - Emergency Vehicles

THRU - Through

EXT - Extended

ELP - Electronic license Plate

T* - Tractor to Trailer ONLY

R* - RFID Tag ONLY

RED* - Vehicle to Vehicle

RED** - Vehicle to Vehicle

and Roadside to Vehicle

GREEN - One-Way

Communication from the

RSE to the OBE

A

PROPOSED NARROWBAND DSRC FREQUENCY ASSIGNMENT STRATEGY

Narrowband Frequency Assignment

Each operating frequency and accompanying bandwidth should be designated as a channel and these channels generally assigned to groups of applications.

OBE with several different capability levels will share the spectrum. The capability of the OBE will identify where it can operate.

The basic level OBE (Types A, B, and C) will be able to operate over only the first three narrowband channels to support the core applications. The OBE will rapidly sample each channel (I propose every 3 msec) and start initialization when a valid signal is detected. This will provide a fast initialization time for those applications that require low latency response. These OBE will use the three separate channels to prevent interference between applications (Frequency Division Multiple Access [FDMA]). This channel isolation will allow applications to operate within the co-channel interference range of other applications.

The second level OBE (Types D, E, and F) will be able to operate in all the narrowband channels. These OBE will be capable of sending and receiving over short, medium, or extended ranges and monitoring all the narrowband channels in a way that will enable them to start initialization in any channel within a specified time (I suggest 1 msec) after being exposed to the required communication zone signal level. These OBE will support the applications that use the initial three channels as well as applications that use the other six channels to prevent overcrowding and interference.

The third level includes OBE Types G and H. These OBE are specially designed to communicate with high data rates (5.5 and 11 Mbps) by using the wideband allocation. Type G only implements the wideband high data rate capability. Type H will be able to operate in all the narrowband channels and the wideband channels. These type H OBE will be capable of sending and receiving over short, medium, extended and long ranges in the narrow band and the wideband and monitor all the channels in a way that enables them to initialize in any channel in the required time.

A

5-9GHz Public Brf.PPT/9-7-99/bcash

PROPOSED NARROWBAND DSRC FREQUENCY ASSIGNMENT STRATEGY

Narrowband Frequency Assignment (continued)

The rest of the discussions on this page cover OBE that are configured to meet unique requirements.

The fourth level OBE(Type L) will also be able to operate in all the channels. These OBE will be capable of sending and receiving over short, medium, extended and long ranges and monitor all the channels in a way that enable them to initialize in any channel in the required time. These OBE are specially designed to communicate with high power levels in channels restricted to transit signal priority and emergency vehicle signal preemption because of their extended and long range requirements and overlapping communication zones. The RSE (beacons) implementing these applications will operate in a synchronized mode and the protocol will provide for a specified number of time slots in each second in which the OBE and RSE in the area can communicate.

The next OBE(Type T) will implement the tractor to trailer interface and be able to operate across several channels in a way that does not interfere with OBE implementing other applications. These OBE will operate using a spread spectrum or ultrawideband method.

Finally, the Type R OBE will implement the applications that require an auxiliary transponder on the vehicle. This transponder must operate at short ranges, over several channels, and at the lowest cost possible. The short range and low power requirements of the applications these OBE implement, along with the assignment to the sparsely used channels, will prevent them from interfering with other applications. In addition, the vehicle registration tag is assigned a channel by itself, because it is a roaming application and can be implemented anywhere on the road. With a separate channel it can operate and not cause interference even if it is initiated in the communication zone of another application.

See the following charts which present a proposed channel assignment for discussion.

A

5-9GHz Public Brf.PPT/9-7-99/bcash

PROPOSED NARROWBAND CHANNEL ASSIGNMENTS

CHANNELS	APPLICATIONS
• One - Three	• ACCESS CONTROL
• One - Three	• PROBE DATA COLLECTION
• One - Three	• TRAFFIC INFORMATION
• One - Three	• TOLL COLLECTION
• Six - Eight	• GAS (FUEL) PAYMENT
• Five	• VEHICLE REGISTRATION TAG (formerly ELP)
• One - Three	• DRIVETHRU PAYMENT
• One - Three (WB Opt)	• IDB DATA TRANSFER
• One - Three	• RENTAL CAR PROCESSING
• One - Three	• IN-VEHICLE SIGNING
• One - Three	• WORK ZONE WARNING
• One - Three	• HIGHWAY/RAIL INTERSECTION WARNING
• One - Three	• ROAD CONDITION WARNING
• Nine	• INTERSECTION COLLISION AVOIDANCE
• Four	• EMERGENCY VEHICLE SIGNAL PREEMPTION
• Four	• TRANSIT VEHICLE SIGNAL PRIORITY
• Six - Eight (WB Opt)	• TRANSIT VEHICLE DATA TRANSFER
• Six - Eight	• TRANSIT VEHICLE REFUELING
• One - Three	• ROLLOVER WARNING
• One - Three	• MAINLINE SCREENING
• One - Three	• BORDER CLEARANCE
• One - Three	• ON-BOARD SAFETY DATA
• Six - Eight (WB Opt)	• UNIQUE CVO FLEET MANAGEMENT
• Six - Eight	• DRIVER'S DAILY LOG
• Six - Eight	• VEHICLE SAFETY INSPECTION
• ALL*	• TRACTOR TO TRAILER DATA TRANSFER
• Six - Eight (WB Opt)	• LOCOMOTIVE DATA TRANSFER
• Six - Eight	• LOCOMOTIVE FUEL MONITORING

ELP -Electronic license Plate
WB Opt - These applications may use the wideband technique for faster data throughput
* Ultrawideband

A

5-9GHz Public Brf.PPT/9-7-99/bcash

PROPOSED WIDEBAND DSRC FREQUENCY ASSIGNMENT STRATEGY

Wideband Frequency Assignment

The wideband frequencies are used for those applications that need high rates of data transfer in isolated communication areas (Bus Parking Lots, Maintenance Areas, and Service Stations are examples of where this technique can be used).

IT IS NOT BELIEVED THAT THIS APPROACH CAN RESOLVE ALL POSSIBLE INTERFERENCE CONFLICTS BETWEEN APPLICATIONS BECAUSE OF THE LIMITED NUMBER OF CHANNELS. SO IT IS APPLICABLE TO ONLY A FEW APPLICATIONS THAT CAN SHARE SPECTRUM WITH THE NARROWBAND TECHNIQUE THROUGH ISOLATION OF THE COMMUNICATION ZONES.

This equipment is not expected to be adopted in general use for core applications because of its higher price.

These communications links must not interfere with narrowband communication operations located in the surrounding area. If located close to a major emergency route it must accept occasional and brief interference from emergency vehicle operations.

Each operating frequency and accompanying bandwidth should be designated as a channel and these channels generally assigned to groups of applications.

See the following charts which present a proposed channel assignment for discussion.

A

5-9GHz Public Brf.PPT/9-7-99/bcash



PROPOSED WIDEBAND CHANNEL ASSIGNMENTS



CHANNELS	APPLICATIONS
• N/A	• ACCESS CONTROL
• N/A	• PROBE DATA COLLECTION
• N/A	• TRAFFIC INFORMATION
• N/A	• TOLL COLLECTION
• N/A	• GAS (FUEL) PAYMENT
• N/A	• VEHICLE REGISTRATION TAG (formerly ELP)
• N/A	• DRIVETHRU PAYMENT
• One - Four	• IDB DATA TRANSFER
• N/A	• RENTAL CAR PROCESSING
• N/A	• IN-VEHICLE SIGNING
• N/A	• WORK ZONE WARNING
• N/A	• HIGHWAY/RAIL INTERSECTION WARNING
• N/A	• ROAD CONDITION WARNING
• N/A	• INTERSECTION COLLISION AVOIDANCE
• N/A	• EMERGENCY VEHICLE SIGNAL PREEMPTION
• N/A	• TRANSIT VEHICLE SIGNAL PRIORITY
• One - Four	• TRANSIT VEHICLE DATA TRANSFER
• N/A	• TRANSIT VEHICLE REFUELING
• N/A	• ROLLOVER WARNING
• N/A	• MAINLINE SCREENING
• N/A	• BORDER CLEARANCE
• N/A	• ON-BOARD SAFETY DATA
• One - Four	• UNIQUE CVO FLEET MANAGEMENT
• N/A	• DRIVER'S DAILY LOG
• N/A	• VEHICLE SAFETY INSPECTION
• All*	• TRACTOR TO TRAILER DATA TRANSFER
• One - Four	• LOCOMOTIVE DATA TRANSFER
• N/A	• LOCOMOTIVE FUEL MONITORING



* Ultrawideband



A



5-9GHz Public Brf.PPT/9-7-99/bcash



























SUMMARY OF 5.9 GHz DSRC PHYSICAL LAYER OPTIONS

- AM / OOK ACTIVE w/3 Channels and separate frequency DL/UL
 - Possible low cost solution for core applications
 - Low channel isolation (could allow interference between applications)
- DBPSK ACTIVE w/3 Channels and separate frequency DL/UL
 - Viable solution for core applications
- DBPSK ACTIVE w/9 Channels and separate frequency DL/UL
 - Viable solution for all* applications
- BACKSCATTER w/3 Channels and separate frequency DL/UL (AM / OOK)
 - Possible low cost solution for core applications
 - Low channel isolation (could allow interference between applications)
- DSSS ACTIVE w/4 Channels and same frequency DL/UL (High Data Rate Opt)
 - Possible limited application solution (not enough channels for all).
 - Most nearly off-the-shelf solution
- ULTRAWIDEBAND w/1 Channel and same frequency DL/UL (Tractor-Trailer Opt)
 - Totally viable for tractor to trailer application

A

* - Excluding the tractor to trailer application

5-9GHz Public Brf.PPT/9-7-99/bcash

SUMMARY OF 5.9 GHz DSRC DATALINK LAYER CANDIDATES

- ASTM V7
 - Acceptable to all parties
 - Significant development costs (design chips from scratch)
- ARIB STD-T55
 - Not acceptable to all parties
 - Less implementation cost (existing chip designs)
- CEN 12795
 - Not acceptable to all parties
 - Less implementation cost (existing chip designs)
- IEEE 802.11
 - Suitability not fully explored
 - Low implementation cost (available off-the-shelf chips)
 - Cost to interface to IEEE 1455
- IEEE 802.15
 - Suitability not yet explored
 - Low implementation cost (potential off-the-shelf chips)
 - Cost to interface to IEEE 1455

A

5-9GHz Public Brf.PPT/9-7-99/bcash