

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	Local Forwarding over IEEE 802.16.1a	
Date Submitted	2011-10-31	
Source(s)	Eunkyung Kim, Sungcheol Chang, Won-Ik Kim, Seokki Kim, Sungkyung Kim, Miyong Yun, Hyun Lee, Chulsik Yoon, Kwangjae Lim ETRI	Voice: +82-42-860-5415 E-mail: ekkim@etri.re.kr scchang@etri.re.kr
Re:	“IEEE 802.16n-11/0020,” in response to Call for Comments on GRIDMAN AWD	
Abstract	Local forwarding on IEEE 802.16 GRIDMAN Amendment Draft Standard	
Purpose	To discuss and adopt the proposed text in the draft amendment document on 802.16 GRIDMAN	
Notice	<i>This document does not represent the agreed views of the IEEE 802.16 Working Group or any of its subgroups.</i> It represents only the views of the participants listed in the “Source(s)” field above. It is offered as a basis for discussion. It is not binding on the contributor(s), who reserve(s) the right to add, amend or withdraw material contained herein.	
Copyright Policy	The contributor is familiar with the IEEE-SA Copyright Policy < http://standards.ieee.org/IPR/copyrightpolicy.html >.	
Patent Policy and Procedures	The contributor is familiar with the IEEE-SA Patent Policy and Procedures: < http://standards.ieee.org/guides/bylaws/sect6-7.html#6 > and < http://standards.ieee.org/guides/opman/sect6.html#6.3 >. Further information is located at < http://standards.ieee.org/board/pat/pat-material.html > and < http://standards.ieee.org/board/pat >.	

Local Forwarding over IEEE 802.16.1a

Eunkyung Kim, Sungcheol Chang, Won-Ik Kim, Seokki Kim, Sungkyung Kim, Miyoung Yun, Hyun Lee, Chulsik Yoon, Kwangjae Lim
ETRI

1. Introduction

This document provides a proposed local forwarding operation on IEEE 802.16 GRIDMAN. Local forwarding allows an HR-MS to communicate with one or more HR-MSs via an HR-infrastructure station without going through the backhaul[1]. In addition, localized routing in WiMAX[7] allows communication between MSs whose data paths are anchored on the same ASN-GW.

Thus, the first scenario, which routes data between MSs inside an ASN, of the localized routing covers the requirement on the local forwarding in IEEE 802.16n[6][7].

2. References

- [1] IEEE 802.16n-10/0048r2, 802.16n System Requirement Document including SAMR annex, July 2011.
- [2] IEEE 802.16n-11/0024, P802.16n Draft AWD, October 2011.
- [3] IEEE 802.16n-11/0025, P802.16.1a Draft AWD, October 2011.
- [4] IEEE P802.16Rev3/D2, IEEE Draft Standard for Local and metropolitan area networks; Part 16: Air Interface for Fixed and Mobile Broadband Wireless Access Systems, October 2011.
- [5] IEEE P802.16.1TM/D2, [Draft] WirelessMAN-Advanced Air Interface for Broadband Wireless Access Systems, October 2011.
- [6] IEEE C802.16n-11/0174, Local Forwarding in IEEE 802.16n, September 2011.
- [7] WiMAX Forum, WiMAX ASN Localized Routing (unapproved), February 2011.

3. Proposed Text on the IEEE 802.16 GRIDMAN Amendment Draft Standard

[-----Start of Text Proposal-----]

[Remedy: Replace the whole text in 6.12.6 by the following text in the 802.16.1a AWD.]

When local forwarding opportunity is determined, an HR-MS may communicate with one or more HR-MSs via an HR-infrastructure station without going through the backhaul. However, how to determine the local forwarding opportunity is outside scope of this specification.

An infrastructure station capable of providing local forwarding shall (re)assign and manage the FID for the HR-MS during DSA procedure. Any available FID may be used for the local

forwarding (i.e., there are no dedicated FIDs for local forwarding connections). An HR-MS may not be aware of local forwarding but shall follow the same procedure defined in 6.2.

Data traffic for HR-MSs sent on the connection with the FID shall be forwarded to other one or more HR-MSs without going through the backhaul. Each MAC PDU shall begin with a MAC Header and its format is the same as that define in 6.2.2.1. The header may be followed by one or more extended headers. The MAC PDU shall also contain a payload. The payload consists of one or more HR-MSs' data traffic. MAC PDUs sent on the connection used by local forwarding shall follow the same format as shown in Figure 2.

[-----End of Text Proposal-----]