

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	Comments and further considerations for Uncoordinated Coexistence Protocol	
Date Submitted	2006-11-10	
Source(s)	Jiezhen Lin Siemens Network Ltd., Beijing R&D 1# Building of SOFPA, No.8 of Dong Bei Wang Xi Lu, Haidian District, Beijing, P.R.China, 100094	Voice: +86 10 6476 6914 Fax: +86 10 6473 3786 Jiezhen.lin@siemens.com
Re:	The first Letter Ballot to IEEE P80216h_D1	
Abstract	Comments and further considerations reflects ongoing Work Group discussion on the Enhancement for uncoordinated coexistence	
Purpose	Revised comments	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < http://ieee802.org/16/ipr/patents/policy.html >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < mailto:chair@wirelessman.org > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < http://ieee802.org/16/ipr/patents/notices >.	

Comments and Further Considerations for Uncoordinated Coexistence Protocol

Jiezhen Lin

Siemens Network Ltd., Beijing R&D

Introduction

The UCP (Uncoordinated Coexistence Protocol) supports 16 system coexistence operation on Non-exclusively assigned and non-exclusively licensed band which contains SSUs (Specific Spectrum Users) and Non-SSUs. Especially, with UCP, the problem of coexistence with 11y (OFDM PHY for the 3650 MHz Band) should be well resolved achieving the CBP requirements of FCC.

Together with the CBP requirements, considering the business use, the UCP should be

- ✓ A simple mechanism to reduce the design/deployment cost
- ✓ An applicable mechanism with more consideration on full scenarios.
- ✓ A compatible mechanism, with the best effort on reducing the necessary to change the coexisted system.
- ✓ An efficiency mechanism to make the best usage of the non-exclusively licensed band, and especially preserve the 16 system advantages of supporting real-time services.

The drafted UCP in 16h Draft1 give us a good guide to a simple uncoordinated scheme, providing DFS/DCS for coexistence with SSU and non-SSU; EQP for providing other user access opportunities; and adaptive EQP for better resource usage. Whereas there are still some problems exist in the current scheme. I'd here to point them out for discussion and improvement.

Existing Problems

1. Different Reactions with SSU (Specific Spectrum Users, Incumbent user) and non-SSU

The uncoordinated coexistence mechanism may conduct the following different reactions of channel allocation for SSU and non-SSU:

	Initialization Stage	Operation Stage
SSU presents/occurs	Find the best frequency without a SSU. Will conduct DFS/DCS.	If SSU occurs, should vacate the physical frequency and select and change to new available frequency. Will conduct DFS/DCS.
Non-SSU presents/occurs	Can coexistence with Non-SSU system, Wait and find a less interfered area of the frame (frequency and time component or a portion thereof), Will conduct DCS.	Coexistence with Non-SSU system, May maintain the allocation usage, or find a less interfered area of the frame (frequency and time component or a portion thereof), or provide opportunity for other to access. Will conduct DCS.

In initialization stage, when detect the SSU or non-SSU presents, UCP will have different reactions. For SSU, UCP will update the available channel list, and try another channel. As for non-SSU, UCP may expect to co-existence with it, and find an available opportunity.

The similar situation is in operation stage, if SSU occurs in the operation channel, UCP have no choice but to vacant the channel; while if non-SSU occurs, UCP will consider about whether or not to release some channel resource. When to release and which to release, the decisions may be variable basing the UCP, the current transmission/receive status and other factors.

So the UCP description section should fully consider the full scenarios, and give a complete introduction in section 6.4.2.4.

2. EQP usage

The duty cycle and EQP's relation should be clarified in the draft. The duty cycle present may be calculated basing EQP. If EQP is a long period and occurs frequently, then in the duty cycle, UCP's usage proportion are small, other wise, UCP will get a large present of duty cycle usage.

As for non-SSU in the channel, UCP will set the duty cycle occupation present of no more than max_duty_cycle, EQP may be very short and seldom occurs. Unless there have non-SSU in the channel, UCP will considerate about set a lower duty cycle occupation present to share the channel with others.

But it is difficult to determine when to begin EQP, and the duration of EQP. It is an issue of the time domain channel resource allocation between non-SSUs. And is there any consideration about that to give a more efficient solution?

3. Support the difference Service Classes of 16 and 11 systems

Can 16's real time services be supported by UCP?

Since the UCP should perform EQP to provide access opportunity for other coexistence system, and need to listen before talk after the EQP to get access opportunity again, so there exists the possibility that UCP fail to support real time service transmission/reception in the right time.

It seems that 16 and 11 system should have coordination in some extents. May there any "slight" communication between coexistence system can be introduced in to the UCP to resolve this problem?

4. Retransmission/Resume Scheme for collision

A contention based protocol should consider about the retransmission scheme for collision. Though the draft assume each of the coexistence systems should perform listen before talk, while collision is still possible for beginning to transmit at the same time after monitoring on a vacant channel. The Retransmission/Resume Scheme should be added in the draft.

Suggested Revisions for section 6.4.2.4

To be added in later version.

Open issues

The following issues are suggested to discuss as open issues in meeting or ad-hoc after meeting:

1. Time domain channel resource allocation between non-SSUs.
2. Support the difference Service Classes of 16 and 11 systems.
3. Retransmission/Resume Scheme for collision

Reference

- [1] IEEE P80216h_D1 Part 16: Air Interface for Fixed and Mobile Broadband Wireless Access Systems: Improved Coexistence Mechanisms for License-Exempt Operation; Working Document
- [2] C80216h-06_074r2: Uncoordinated Coexistence Protocol (UCP), Paul Piggin, NextWave Broadband