

Project	<b>IEEE 802.16 Broadband Wireless Access Working Group</b> < <a href="http://ieee802.org/16">http://ieee802.org/16</a> >	
Title	<b>IPv4 connection management</b>	
Date Submitted	<b>2005-07-12</b>	
Source(s)	Mi Young Yun	<a href="mailto:myyun@etri.re.kr">myyun@etri.re.kr</a>
	Jung Mo Moon, PhD	<a href="mailto:jmmoon@etri.re.kr">jmmoon@etri.re.kr</a>
	Sang Ho Lee, PhD	<a href="mailto:leesh@etri.re.kr">leesh@etri.re.kr</a>
	ETRI 161, Gajeong-dong, Yuseong-Gu, Daejeon, 305-350, Korea	Voice: 82-42-860-4821 Fax: 82-42-861-1966
Re:	Contribution on comments to IEEE 802.16g-04/03r3	
Abstract	In this contribution, we describe IPv4 connection procedure and primitives that could be exchanged between the BS and the NCMS entities.	
Purpose	Adoption	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate text contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures (Version 1.0) < <a href="http://ieee802.org/16/ipr/patents/policy.html">http://ieee802.org/16/ipr/patents/policy.html</a> >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, if there is technical justification in the opinion of the standards-developing committee and provided the IEEE receives assurance from the patent holder that it will license applicants under reasonable terms and conditions for the purpose of implementing the standard."	
	<p>Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair &lt;<a href="mailto:r.b.marks@ieee.org">mailto:r.b.marks@ieee.org</a>&gt; as early as possible, in written or electronic form, of any patents (granted or under application) that may cover technology that is under consideration by or has been approved by IEEE 802.16. The Chair will disclose this notification via the IEEE 802.16 web site &lt;<a href="http://ieee802.org/16/ipr/patents/notices">http://ieee802.org/16/ipr/patents/notices</a>&gt;.</p>	

# IPv4 connection Management

Mi Young Yun, Jung Mo Moon and Sang Ho Lee

**ETRI**

## 1. Problem Statement

The purpose is to describe IPv4 connection procedure and primitives that could be exchanged between the BS and the NCMS entities. This proposal makes it possible to establish IP connectivity for SS and MS as specified in the remainder of this document.

## 2. Summary of the Proposed Remedy

In this contribution, we define 3 primitives to support service flow management between BS and access network (NCMS) which are described briefly in the following table.

Primitive	Direction	Primitive Contents
MIP Transfer	BS <-> NCMS	MS ID, MIP Payload
DHCP Transfer	BS <-> NCMS	MS ID, DHCP Payload
IP_Allocation_Notification.indication	BS <- NCMS	MS ID, Allocated IP Address

### 3. Proposed Text Changes

[Insert section 14.5.6.3 as follow]

#### 14.5.6.3 SS/MS Connection Management

##### 14.5.6.3.1 IPv4 Connection Management

There are two kinds of IP allocation method in the secondary management connection, DHCP (Dynamic Host Control Protocol) and MIP (Mobile IP).

First, for the IP allocation using DHCP, the DHCP protocol is employed in SS/MS and NCMS (a DHCP relay agent and a server). DHCP payloads are transported between SS/MS and BS, but BS forward them encapsulated. SS/MS sends a DHCPDISCOVER message in order to initiate IP allocation procedure. A SS/MS receives a DHCPOFFER message which has the information of DHCP server. The SS/MS requests an IP address allocation by sending a DHCPREQUEST message. Then a newly allocated IP address is provided by the DHCP server in a DHCPACK message. A Gateway address, DNS (Domain Name Server) addresses, and an IP address lease time are also represented.

Second, for the IP allocation using MIP, the MIP protocol is employed in MS and NCMS or a mobility agent (a Foreign Agent and/or a Home Agent). MIP payloads encapsulated also are forwarded between MS and BS. MIP procedure is started when a MS receives an Agent Advertisement message with information of a mobility agent. After that, the SS sends a MIP Registration Request message which includes a Home Agent address, a user NAI (Network Access Identifier) and so on. Then, the MS receives a MIP Registration Response message with successful Result-Code. If the MS forwards the MIP Registration Request message with no IP address, an allocated IP address is represented in the MIP Registration Response.

##### 14.5.6.3.2 Service Primitives

###### 14.5.6.3.2.1 DHCP\_Transfer

###### 14.5.6.3.2.1.1 Function

DHCP payloads are exchanged between an SS/MS and an DHCP Client entity. The DHCP payloads are encapsulated in the DHCP Transfer primitive because it is not interpreted in the BS.

###### 14.5.6.3.2.1.2 Semantics of the Service Primitives

The parameters of the primitives are as follows:

```
DHCP_Transfer
{
  MS/SS ID
  DHCP Payload
}
```

###### MS/SS ID

48-bit unique identifier used for user identification between BS and NCMS

**DHCP Payload**

Contains the DHCP payload

**14.5.6.3.2.2 MIP\_Transfer****14.5.6.3.2.2.1 Function**

MIP payloads are exchanged between an MS and an entity with functionalities of mobility agent in NCMS. The MIP payloads are encapsulated in the MIP Transfer primitive because it is not interpreted in the BS.

**14.5.6.3.2.2.2 Semantics of the Service Primitives**

The parameters of the primitives are as follows:

```
MIP_Transfer
{
MS ID
MIP Payload
}
```

**MS ID**

48-bit unique identifier used for user identification between BS and NCMS

**MIP Payload**

Contains the MIP payload

**14.5.6.3.2.3 IP\_Allocation\_Notification.indication****14.5.6.3.2.3.1 Function**

After MIP or DHCP exchanges are completed, the SS/MS gets a new allocated IP address. For the BS, NCMS sends a new allocated IP address for the SS/MS in IP\_Allocation.indication primitive.

**14.5.6.3.2.3.2 Semantics of the Service Primitives**

The parameters of the primitives are as follows:

```
IP_Allocation_Notification.indication
{
MS ID
IP Address
}
```

**MS ID**

48-bit unique identifier used for user identification between BS and NCMS

**IP Address**

A new address allocated to the SS/MS using DHCP or MIP.

**14.5.6.3.2.3.3 When generated**

This primitive is issued by a NCMS (a DHCP client or a Mobility Agent) when the IP allocation procedure are successfully completed.

#### **14.5.6.3.2.3.4 Effect of receipt**

A newly allocated IP address is known to the BS.

#### References

- [1] R. Droms, "Dynamic Host Configuration Protocol," RFC2131, March 1997
- [2] C. Perkins, "IP Mobility Support for IPv4," RFC3344, August 2002
- [3] IEEE-Std 802.16-2004
- [4] IEEE P802.16e/D9