

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title		
Date Submitted	2007-02-15	
Source(s)	Peretz Feder – Alcatel-Lucent Phillip Barber - Huawei Honghai Zhang – Alcatel-Lucent	pfeder@alcatel-lucent.com pbarber@broadbandmobiletech.com hozhang@alcatel-lucent.com
Re:	IEEE 802.16 Session #47 plus over the phone	
Abstract	This contribution proposes the updates of IEEE 802.16g D7 document in order to obtain loading information from the Base Station	
Purpose	Update 802.16g draft to include BS redirection option for a ranging MS	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < http://ieee802.org/16/ipr/patents/policy.html >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < mailto:chair@wirelessman.org > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < http://ieee802.org/16/ipr/patents/notices >.	

Option to Redirect ranging MS to another Carrier or channel

Peretz Feder -Alcatel-Lucent
Honghai Zhang – Alcatel-Lucent
Phillip Barber - Huawei

1. Introduction

In some cases during the initial ranging and network entry the BS may want to handover an MS to another channel or a carrier. If not done initially, the MS needs to enter the network and follow with a quick BS initiated handover procedure. A more expedited process is a channel redirection when multiple carriers are available in the vicinity of the BS/sector. Since the Offset Frequency Adjustment TLV is a 32 bits value the redirection value in the RNG-RSP message can provide +/- 2GHz adjustment value. When the offset frequency adjustment value is small the BS attempts to better tune the MS to the center frequency of the channel. However when the adjustment value is larger than half of the channel BW, the BS is attempting to redirect the MS to another carrier or channel.

2. Proposed Text Change

Remedy 1:

Use the Offset Frequency Adjustment to redirect MS

[In 6.3.9.5.1 insert the following text before the third paragraph below Table 115 as indicated:]

A BS may decide to re-direct the ranging SS to another channel by sending the RNG-RSP with an Offset Frequency Adjustment pointing to the other channel. If the Offset Frequency Adjustment value is less than half of the channel bandwidth, this is fine-frequency adjustment within the ranged channel, otherwise, the value is a reassignment to a different channel.

...

On receiving a RNG-RSP instruction to move to a new downlink frequency, the SS shall consider any previously assigned Basic, Primary Management, and Secondary Management CIDs to be deassigned, and shall obtain new Basic, Primary Management, and Secondary Management CIDs via initial ranging and registration.

the UCD. Then, the SS shall wait for a bandwidth allocation map for the selected channel. It may begin transmitting uplink in accordance with the MAC operation and the bandwidth allocation mechanism.

The SS shall perform initial ranging at least once, per Figure 60 and Figure 61. If initial ranging is not successful, the procedure is restarted from scanning to find another downlink channel.

The SS MAC is considered to have valid uplink parameters as long as it continues to successfully receive the UL-MAP and UCD message is not received within the time intervals specified in Table 342, the SS shall not use the uplink. This is illustrated in Figure 59.

Remdy 2:

Use the Offset Frequency Adjustment in the RNG-RSP to redirect the MS

6.3.10.3.1 Contention based initial ranging and automatic adjustments

- The SS, after acquiring downlink synchronization and uplink transmission parameters, shall choose randomly a Ranging Slot (with the use of a binary truncated exponent algorithm to avoid possible re-collisions) at the time to perform the ranging, then it chooses randomly a Ranging Code (from the Initial Ranging domain) and sends it to the BS (as a CDMA code).

- The BS cannot tell which SS sent the CDMA ranging request; therefore, upon successfully receiving a CDMA Ranging Code, the BS broadcasts a Ranging Response message that advertises the received Ranging Code as well as the ranging slot (OFDMA symbol number, subchannel, etc.) where the CDMA Ranging code has been identified. This information is used by the SS that sent the CDMA ranging code to identify the Ranging Response message that corresponds to its ranging request. The Ranging Response message contains all the needed adjustment (e.g., time, power, and possibly frequency corrections) and a status notification.
- Upon receiving a Ranging Response message with continue status, the SS shall continue the ranging process as done on the first entry with ranging codes randomly chosen from the Initial Ranging domain sent on the Periodic Ranging region.
- When the BS receives an initial-ranging CDMA code that results in sending an RNG-RSP message with success status, the BS shall provide BW allocation for the SS using the CDMA_Allocation_IE to send an RNG-REQ message.
- Initial ranging process is over after receiving RNG-RSP message, which includes a valid basic CID (following a RNG-REQ transmission on a CDMA_Allocation_IE). If this RNG-RSP message includes ‘continue’ indication, the ranging process should be continued using the periodic ranging mechanisms.
- **If the RNG-RSP include an Offset Frequency Adjustment pointing to another channel and it is larger than the value required for a channel bandwidth offset the MS SHALL synchronize with the new channel indicated in the RNG-RSP.**
- The timeout required for SS to wait for RNG-RSP, following or not following CDMA Allocation IE, is defined by T3.
- Using the OFDMA ranging mechanism, the periodic ranging timer is controlled by the SS, not the BS.

The message sequence chart (Table 121) and flow charts (Figure 85, Figure 86, Figure 86a, and Figure 87) on the following pages define the CDMA initial ranging and adjustment process that shall be followed by compliant SSs and BSs.