

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	MMR Protocol Stack and Definition of RS Types	
Date Submitted	2007-04-19	
Source(s)	<p>Hang Zhang, Mo-Han Fong, G.Q. Wang, Peiyong Zhu, Wen Tong, David Steer, Gamini Senarath, Derek Yu, Mark Naden</p> <p>Nortel 3500 Carling Avenue Ottawa, Ontario K2H 8E9</p> <p>Kanchei (Ken) Loa, Yung-Ting Lee, Youn-Tai Lee, Heng-lang Hsu</p> <p>Institute for Information Industry 8F, No. 218, Sec. 2, Dunhua S. Rd., Taipei City 106, Taiwan, ROC.</p> <p>Jeffrey Z. Tao, Koon Hoo Teo, Jinyun Zhang</p> <p>Mitsubishi Electric Research Lab 201 Broadway Cambridge, MA 02139 USA</p> <p>Toshiyuki Kuze</p> <p>Mitsubishi Electric Corp 5-1-1 Ofuna Kamakura, Kanagawa 2478501, Japan</p> <p>Mary Chion, Jerry Chow, Hongyun Qu ZTE Corporation</p>	<p>Voice: +1 613 7631315 [mailto:WenTong@nortel.com]</p> <p>[mailto:pyzhu@nortel.com]</p> <p>loa@nmi.iii.org.tw</p> <p>Voice: 617-621-{7557,7527} Fax: 617-621-7550</p> <p>{tao, teo, jzhang}@merl.com</p> <p>Voice: +81-467-41-2885 Fax: +81-467-41-2486 kuze.toshiyuki@ah.MitsubishiElectric.co.jp</p> <p>mchion@zteusa.com</p>
Re:	A response to a Call for Technical Proposal, http://www.ieee802.org/16/relay/docs/80216j-07_007r2.pdf	
Abstract	In order to support 802.16e MAC PDU forwarding by RSs on the relay link, MMR protocol stack is proposed to enable different types of relay forwarding operation.	

Purpose	To incorporate the proposed text into the P802.16j Baseline Document (IEEE 802.16j-06/026r2)
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < http://ieee802.org/16/ipr/patents/policy.html >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < mailto:chair@wirelessman.org > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < http://ieee802.org/16/ipr/patents/notices >.

MMR Protocol Stack and Types of Relay Stations

Hang Zhang, Mo-Han Fong, G.Q. Wang, Peiyong Zhu, Wen Tong, David Steer, Gamini Senarath, Derek Yu, Mark Naden

Nortel

*Kanchei (Ken) Loa, Yung-Ting Lee, Youn-Tai Lee, Heng-lang Hsu
Institute for Information Industry*

Jeffrey Z. Tao, Koon Hoo Teo, Jinyun Zhang
Mitsubishi Electric Research Lab

Toshiyuki Kuze
Mitsubishi Electric Corp.

Mary Chion, Jerry Chow, Hongyun Qu
ZTE Corporation

Introduction

To efficiently support 802.16e MAC PDU forwarding by RSs and end-to-end operation between MR-BS and MS, an MMR data protocol stacks are proposed as shown in Figure 1 and Figure 2. Figure 1 shows the protocol for MS traffic relaying where the MS connection and privacy managements are on end-to-end basis (between MMRBS and MS). Figure 2 shows the other protocol for MS traffic relaying where the MS connection and privacy management are managed by the RS and the RS connection and privacy management are controlled by MR-BS. The R-MAC layer provides an extendable framework for various relay related functions, such as QoS control, routing control and etc.

For purely physical layer relaying, the protocol is the same as current 802.16d/e protocol stack.




Figure 1 MMR data protocol stack for simple RS (MS traffic relaying)




Figure 2 MMR data protocol for micro-BS RS (MS traffic relaying)

The design principles of the R-MAC layer proposal should:

- Enable extensibility of functionality
- Minimize overhead

Protocol stack shown in Figure 2 can be used for mobile RS usage scenario, see contribution C80216j-06_235 [1].

Based on the functions a relay station implements, relay stations can be categorized into 4 types. The following table shows the functions of each type of relay station implements and corresponding operations.

		Type 1 R-link: R-PHY Access link: PHY	Type 2 R-link: R-PHY, R-MAC Access link: PHY, MAC-CPS	Type 3 R-link: R-PHY, R-MAC, MAC-CPS Access link: PHY, MAC-CPS	Type 4 R-link: R-PHY, R-MAC, MAC-SS, MAC-CPS, MAC-CS Access link: PHY, MAC-SS, MAC-CPS, MAC-CS
RS properties	RS naming (RSID)	Yes	Yes	Yes	Yes
	Basic CID/Primary CID	Yes	Yes	Yes	Yes
	Secondary CID	No	No	No	Yes
	Transport CID	No	Yes (for connection originated relaying) No (for packet originated relaying)	Yes (for connection originated relaying) No (for packet originated relaying)No	Yes
	RS <-> MMRBS security	No	Yes	Yes	Yes
	Trans/non-trans	Transparent	Transparent/non-transparent	Transparent/non-transparent	Non-transparent
MS connection and security and	MS connection management	No (MS end-to-	No (MS end-to-end	No (MS end-to-end	Yes (MS

service flow management		end connection with MMRBS)	connection with MMRBS)	connection with MMRBS)	connection with serving RS)
	MS security management	No (MS end-to-end security established with BS)	No (MS end-to-end security established with BS)	No (MS end-to-end security established with BS)	Yes (MS security established with serving RS)
	MS service flow management	No	No	No	Yes
R-link functions (MS data/message and other RS control message forwarding)	Route control	No	Yes (e.g., destination RS based, T-CID based based, etc) No (e.g., source routing)	Yes (MS CID based)	Yes (any routing methods)
	QoS control-forwarding scheduling	No	Yes if supported	Yes if supported	Yes if supported
Access-link functions	Preamble/MAP transmission (IDCell)	No Or optionally it may transmit the same preamble as the MR-BS.	Yes	Yes	Yes
	MS control message/control header process	No (i.e., transparent)	Yes (for non-authenticated MS control management message, RS	Yes (for non-authenticated MS control management message, RS may	Yes (for all MS control messages and control

			may process) No (for authenticated MS control message, RS only forwards)	process) No (for authenticated MS control message, RS only forwards)	header, RS can process)
	MS traffic scheduling (DL/UL)	No (centralized scheduling)	Optional (centralized or distributed scheduling)	Optional (centralized/distribute d scheduling)	Yes (distributed scheduling)
	UL traffic forwarding QoS control	No	Yes if supported	Yes if supported	Yes if supported
	MS MAC state management	No	No	No	Yes

Proposed text change

[Insert new subclause 6.1.1.1 MMR Protocol]

1.4.1 MMR Protocol

The R-MAC sub-layer provides efficient 802.16e MAC PDU relaying/forwarding and control functions. This sub-layer is applicable to the links between MR-BS and RSs and between RSs. The resulting data protocol stacks are shown in Figure XX and Figure XXX. Figure XX shows the protocol for MS traffic relaying where the MS connection and privacy managements are on end-to-end basis (between MR-BS and MS). Figure XXX shows the other protocol for MS traffic relaying where the MS connection and privacy management are managed by the RS and the RS connection and privacy management are controlled by MR-BS.




Figure XX. MMR Data Protocol for simple RS (MS traffic relaying).




Figure XXX. MMR Data Protocol for micro-BS RS (MS traffic relaying)

The R-MAC provides the concatenation and fragmentation of forwarded 802.16d/e MAC PDU and control functions, such as scheduling, routing, flow control and etc.

The R-PHY layer provides definition of physical layer design, such as, sub-channelization, modulation and code set and etc, for links between MMR-BS and RS and between RSs.

The CPS-lite block includes functions such as process (sharing) of MAC management messages between MR-BS and MS, scheduling on access link and etc.

A relay station can optionally implement R-MAC sub-layer, or 802.16e MAC CPS function and MAC CS function.

If a relay station only implements R-PHY layer on R-link and 16e PHY on access link, this relay station is defined as a type 1 relay station; If a relay station implements R-PHY and R-MAC layers on R-link, this relay station is defined as type 2 relay station; If a relay station implements R-PHY, R-MAC and MAC-CPS layers on R-link, this relay station is defined as type 3 relay station; If a relay station implements R-PHY, R-MAC, MAC-SS, MAC-CPS and MAC-CS layers on R-link, this relay station is defined as type 4 relay station.

The transport connection(s) of a MS can be established between MMR-BS and MS (end-to-end connection) or established between its serving station (MMR-BS or relay station) and the MS.

[1] "Moving RS operation", Hang Zhang, G.Q. Wang, Peiying Zhu, Wen Tong, David Steer, Gamini Senarath, Derek Yu, Mark Naden, C80216j-06_235.