
IEEE 802.16 Broadband Wireless Access Working Group <<http://ieee802.org/16>>

Title **MS scanning in MR network**

Date Submitted **2007-03-11**

Hyunjeong Kang, Sungjin Lee,
Hyoung Kyu Lim, Jungje Son
Samsung Electronics

[mail to: hyunjeong.kang@samsung.com]

Source(s) Rakesh Taori
Samsung Advanced Institute of Technology

[mail to: rakesh.taori@samsung.com]

[Hyunjeong Lee](#)
[Intel Corporation](#)

[mail to: Hyunjeong.hannah.lee@intel.com]

Re: Call for technical proposals regarding IEEE project P802.16j

Abstract This contribution proposes the scheme with which RS supports MS scanning operation.

Purpose Discussion and Adoption in IEEE 802.16j

Notice This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.

Release The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.

Patent Policy and Procedures The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures <<http://ieee802.org/16/ipr/patents/policy.html>>, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair <<mailto:chair@wirelessman.org>> as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site <<http://ieee802.org/16/ipr/patents/notices>>.

MS scanning in MR network

Hyunjeong Kang, Sungjin Lee, Hyoung Kyu Lim and Jungje Son
Samsung Electronics

Rakesh Taori
Samsung Advanced Institute of Technology

Hyunjeong Lee
Intel Corporation

Introduction

In MR network it is needed to define an operation with which a relay station supports MS scanning.

As described in section 6.3.22.1.2 of 802.16e-2005, a serving MR-BS allocates scanning intervals to an MS and scanning negotiation messages are transmitted between the MR-BS and the MS. An access RS relays the scanning negotiation signals of the MS and the serving MR-BS.

Assuming that RS has a capability to schedule MS data transmission, the RS needs to be informed of MS scanning and take MS scanning intervals into account scheduling of MS data transmission. In this case, a serving MR-BS may inform an access RS of MS scanning intervals so that the access RS schedules MS data transmission. In addition, when MS repeats its scanning process with the number of scanning interval and interleaving interval as in figure 1 and the access RS knows the information of each intervals, the RS schedules to transmit MS data during interleaving intervals using the information.

If the access RS does not receive the indication of MS scanning mode, the access RS may transmit MS data to an MS in scanning mode. To keep consistency in MS status among MR-BS, RS and MS, upon receiving indication of MS scanning intervals from the serving MR-BS, the access RS sends its response to the indication.

When an MS terminates any of scanning interval by sending a MAC PDU, the access RS assumes that the MS is no longer in scanning mode based on MAC PDU from the MS. But if the MS sends MOB_SCN-REQ or the serving MR-BS sends MOB_SCN-RSP to terminate the group of scanning intervals, the access RS does not know the termination of group of intervals. So the serving MR-BS shall notify the access RS of the termination of group of intervals using MS_SCN-CLT message.




Figure 1 Example of periodic scanning by MS request in distributed scheduling case

Proposed Text Change

[Insert the followings at the end of section 6.3.22.1.2:]

In MR network MR-BS shall control MS scanning. An RS relays MOB_SCN-REQ, MOB_SCN-RSP and MOB_SCN-REP messages between an MS and the MR-BS in centralized scheduling or distributed scheduling. In the case of distributed scheduling, the MR-BS sends MS_SCN-INF message to inform the access RS of MS scanning related information after the MR-BS determines the scanning intervals of MS. The access RS transmits MS_SCN-ACK message as an acknowledgement of MS_SCN-INF. Based on MS_SCN-INF

message, the access RS schedules MS data transmission.

The MR-BS shall transmit MS_SCN-CLT message to inform an access RS that the group of intervals of MS is terminated. The access RS shall assume that the MS is no longer in scanning mode when the access RS receives MS_SCN-CLT message or a MAC PDU of MS.

[Insert new subclause 6.3.2.3.xx after section 6.3.2.3.64:]

6.3.2.3.xx MS Scanning Inform (MS_SCN-INF) message

A MS_SCN-INF message may be transmitted by an MR-BS to inform an access RS of MS scanning operation.

An MR-BS includes the information of scanning intervals of MS(s) in a MS_SCN-INF message.

An MR-BS shall generate MS_SCN-INF message in the format shown in Table x. The MS_SCN-INF message shall be transmitted on the RS's basic CID.

Table x – MS_SCN-INF message format

Syntax	Size	Notes
MS_SCN-INF Message format() {	=	
Management Message Type=TBD	8 bits	=
Transaction ID	8 bits	=
N MS	8 bits	Number of MSs
For(i=0; i<N MS; i++) {		
MS CID	16 bits	Basic CID of MS
Start frame	4 bits	Start frame number from which the MS start the first scanning interval. Measured from the frame in which this message was received. A value of zero means that first scanning interval starts in the next frame.
Scan duration	8 bits	Duration (in units of frames) where the MS may perform scanning.
Interleaving interval	8 bits	Duration in frames. The period interleaved between scanning intervals when MS shall perform normal operation.
Scan iteration	8 bits	The number of iterating scanning interval.
Padding	4 bits	Shall be set to zero
}		
}		

[Insert new subclause 6.3.2.3.yy after section 6.3.2.3.64:]

6.3.2.3.yy MS Scanning Acknowledgement (MS_SCN-ACK) message

An RS sends MS_SCN-ACK message as a response of MS_SCN-INF message to an MR-BS.

An RS shall generate MS_SCN-ACK messages in the format shown in Table y. MS_SCN-ACK message shall be transmitted on the RS's basic CID.

Table y – MS_SCN-ACK message format

<u>Syntax</u>	<u>Size</u>	<u>Notes</u>
<u>MS_SCN-ACK Message format() {</u>	<u>=</u>	
<u>Management Message Type=TBD</u>	<u>8 bits</u>	<u>=</u>
<u>Transaction ID</u>	<u>8 bits</u>	<u>Transaction ID in corresponding</u>
		<u>MS_SCN-INF message</u>
<u>}</u>		

[Insert new subclause 6.3.2.3.zz after section 6.3.2.3.64:]

6.3.2.3.zz MS Scanning Completion (MS_SCN-CLT) message

A MS_SCN-CLT message may be transmitted by an MR-BS to inform an access RS that the group of intervals of MS is terminated.

An MR-BS shall generate MS_SCN-CLT messages in the format shown in Table z. MS_SCN-CLT message shall be transmitted on the RS's basic CID.

Table z – MS_SCN-CLT message format

<u>Syntax</u>	<u>Size</u>	<u>Notes</u>
<u>MS_SCN-CLT Message format() {</u>	<u>=</u>	
<u>Management Message Type=TBD</u>	<u>8 bits</u>	<u>=</u>
<u>N_MS</u>	<u>8 bits</u>	<u>Number of MSs</u>
<u>For(i=0; i<N_MS; i++) {</u>		
<u>MS CID</u>	<u>16 bits</u>	<u>Basic CID of MS</u>
<u>}</u>		
<u>}</u>		