

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	RS Configuration Description- Broadcast Message	
Date Submitted	2007-04-25	
Source(s)	<p>Hang Zhang, Peiyong Zhu, Mo-Han Fong, Wen Tong, David Steer, Gamini Senarath, Derek Yu, Mark Naden, G.Q. Wang</p> <p>Nortel 3500 Carling Avenue Ottawa, Ontario K2H 8E9</p> <p>I-Kang Fu NCTU/ITRI ED922, 1001 Ta Hsueh Rd., Hsinchu City, Taiwan 300, ROC</p> <p>Matty Levanda</p>	<p>Voice: +1 613 7631315 [mailto:WenTong@nortel.com]</p> <p>[mailto:pyzhu@nortel.com]</p> <p>IKFu@itri.org.tw</p> <p>MattyL@winetworks.com</p>
Re:	A response to a Call for Technical Proposal, http://www.ieee802.org/16/relay/docs/80216j-07_007r2.pdf	
Abstract	With relay station introduced, some configuration parameters specific for normal operation of RS may be required. This contribution introduces a new broadcast message used to broadcast configuration parameters specific for RS operation.	
Purpose	To incorporate the proposed text into the P802.16j Baseline Document (IEEE 802.16j-06/026r2)	

Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < http://ieee802.org/16/ipr/patents/policy.html >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < mailto:chair@wirelessman.org > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < http://ieee802.org/16/ipr/patents/notices >.

RS Configuration Description Message

Hang Zhang, Peiying Zhu, Mo-Han Fong, Wen Tong, David Steer, Gamini Senarath, Derek Yu, Mark Naden, G.Q. Wang

Nortel

1. Introduction

With relay station introduced, some configuration parameters specific for normal operation of RSs ~~may be~~ are required. There are some examples, such as, ranging back-off, radio environment report threshold, HARQ related parameters, frame structure configuration, and so on. In current baseline documents, the configuration for frame structure is sent through Relay frame configuration message (6.3.2.3.77) and the RS-able transmission/monitoring configuration is sent in RS_Config-REQ message (6.3.2.3.66). The contents included in Relay frame configuration message and contents of RS-able transmission/monitoring parameters shall be considered as RS system operation parameter configuration.

This contribution suggests to introduce a message called "RS Configuration Description message" dedicated to ~~broadcast declare~~ configuration parameters specific for RS operation thus reducing the types of the 802.16j MAC management messages.

2. Introduction of RS configuration description management messages

In fact, 802.16e DCD and UCD messages can be modified to include those new configurations. However, there are following disadvantages using DCD/UCD for this purpose:

- The DCD/UCD would include new TLVs which are not related to the operation of 802.16e MSs. It is not efficient for a MS to decode a lengthy DCD/UCD message

- In addition, the change/update of MS related configuration and that of RS related configuration are not

synchronized. Even though a DCD/UCD may only contain updated RS related configuration parameters, an MS has to decode this message.

In current baseline documents, the configuration for frame structure is sent through Relay frame configuration message (6.3.2.3.77) and the RS-able transmission/monitoring configuration is sent in RS Config-REQ message (6.3.2.3.66). The contents included in Relay frame configuration message and contents of RS-able transmission/monitoring parameters shall be considered as RS system operation parameter configuration. We propose to use RS Configuration Description (RS-CD) message to send those configurations to reduce the types of the 802.16j MAC management messages.

The RS-CD message includes configuration parameters for both DL and UL.

3. Proposed text change

[Modify the last row in Table 14 in page 4 as follows]

Type	Message name	Message description	Connection
68-255-68	RS-CD- Configuration Description (RS_CD)	RS specific configuration description sent by MMR-BS and forwarded by intermediate RSs	Broadcast to all associated RS of a MMR-BS
69-255		Reserved	

[Replace 6.3.2.3.77 by the following]

6.3.2.3.77 RS configuration description message

This message is used by MR-BS to broadcast RS operation configurations to all associated RSs or used by MR-BS or RS to a broadcast-multicast configuration to message among its associated child RSs of a MMRBS. This message is transmitted by a MMRBS and forwarded by intermediate RSs. This message is used by a MMRBS to broadcast description of configuration specific to all of its associated RSs to enable RSs' operations, such as network entry, initialization, and 802.16c traffic forwarding. This message can also be unicast to a RS during

initial network entry to inform the configuration parameter to this RS.

Table XXX. RS configuration description (RS-CD) message format.

Syntax	Size	Notes
<u>RS_CD format {</u>		
<u>Management message type = 67</u>	<u>8 bits</u>	
<u>Configuration_para_type</u>	<u>8 bits</u>	<u>b0 = 1, Frame Structure-Configuration is included.</u> <u>b1 = 1, R-amble transmission/monitoring parameters are included.</u> <u>b2 - b7: reserved</u>
<u>If (b0 of Configuration_para_type == 1) {</u> <u> TLVs</u>	<u>Variable</u>	<u>Configuration TLV</u>
<u>Type of frame‡</u>	<u>1 bits</u>	<u>0: single frame approach</u> <u>1: multi frame approach</u>
<u>Frame Number</u>	<u>4 bits</u>	<u>Frame number to take effect</u>
<u>DL indicator</u>	<u>1 bit</u>	<u>1: indicates DL subframe configuration are included</u>
<u>UL indicator</u>	<u>1 bit</u>	<u>1: indicates UL subframe configuration is included</u>
<u>Reserved</u>	<u>1 bit</u>	
<u>If (Type of frame == 0) {</u>		
<u> If (DL indicator == 1) {</u>		
<u> Number of relay zones</u>	<u>8 bits</u>	
<u> for (i=0; i< Number of Relay zones; i++)</u> <u> {</u>		
<u> Transceiver mode</u>	<u>2 bits</u>	<u>00: Tx mode.</u> <u>01: Rx mode.</u> <u>11: Idle mode</u>
<u> OFDMA Symbol Offset</u>	<u>8 bits</u>	
<u> Frame Config Duration</u>	<u>6 bits</u>	
<u> }</u>		
<u> }</u>		
<u>If (UL indicator == 1) {</u>		

<u>Number of relay zones</u>	8 bits	
<u>for (i=0; i< Number of Relay zones; i++)</u>		
<u>{</u>		
<u>Transceiver mode</u>	2 bits	
<u>OFDMA Symbol Offset</u>	8 bits	
<u>Frame Config Duration</u>	6 bits	
<u>}</u>		
<u>}</u>		
<u>{</u>		
<u>If (Type of frame ==1){</u>		
<u>If (DL indicator ==1){</u>		
<u>Number of frame</u>	8 bits	
<u>for (i=0; i< Number of frame; i++) {</u>		
<u>Transceiver mode</u>	2 bits	<u>00: Tx mode,</u> <u>01:Rx mode,</u> <u>11:Idle mode</u>
<u>OFDMA Symbol Offset</u>	8 bits	
<u>Reserved</u>	6 bits	
<u>}</u>		
<u>}</u>		
<u>If (UL indicator ==1){</u>		
<u>Number of frame</u>	8 bits	
<u>for (i=0; i< Number of frame; i++) {</u>		
<u>Transceiver mode</u>	2 bits	<u>00: Tx mode,</u> <u>01:Rx mode,</u> <u>11:Idle mode</u>
<u>OFDMA Symbol Offset</u>	8 bits	
<u>Reserved</u>	6 bits	-
<u>}</u>		
<u>}</u>		
<u>}</u>		
<u>{</u>		
<u>If (b1 of Configuration para type == 1) {</u>		
<u>Start Frame Number</u>	8 bits	<u>8 LSB bits of the frame number</u>
<u>Monitoring Duration</u>	8 bits	<u>Units are frames</u>
<u>Prefix</u>	2 bits	<u>00: The R-amble transmission and reception is instructed by MR-BS.</u>

		<u>01: The R-amble transmission and measurement shall be performed autonomously.</u> <u>10: The RSs shall report its neighbor measurement results.</u> <u>11: reserved</u>
<u>If (Prefix == 00){</u>		
<u> Interleaving Interval</u>	<u>8 bits</u>	<u>Units are frames</u>
<u> Iteration Number</u>	<u>8 bits</u>	<u>Units are frames</u>
<u> N_stations</u>	<u>8 bits</u>	<u>Number of stations received this message</u>
<u> For (i=0, i< Iteration, i++){</u>		
<u> N_Transmitter</u>	<u>8 bits</u>	<u>Number of stations to transmit the R-amble</u>
<u> For (j=0, j< N_Transmitter, j++){</u>		
<u> Amble Index</u>	<u>8 bits</u>	<u>The RS with the amble index in this list shall transmit the R-amble</u>
<u> }</u>		
<u> For (j=0, j< N_stations - N_Transmitter, j++){</u>		
<u> Amble Index</u>	<u>8 bits</u>	<u>The RS with the amble index in this list shall receive the R-amble</u>
<u> }</u>		
<u> }</u>		
<u> }</u>		
<u>If (Prefix == 01){</u>		
<u> Config_type</u>	<u>3 bits</u>	<u>Bit [0] = 1: R-amble for synchronization is present.</u> <u>Bit [0] = 0: R-amble for synchronization is not transmitted.</u> <u>Bit [1] = 1: R-amble for random monitoring is present;</u> <u>Bit [1] = 0: any current monitoring operation is to be stopped by all RSs.</u> <u>Bit [2] = 1: any RS which does not support subordinate RSs should transmit the R-amble for advertisement purpose</u> <u>Bit [2] = 0: any RS which does not support subordinate RSs should not transmit the R-amble.</u>
<u> If (Config_type[0] == 1){</u>		
<u> Synchronization cycle</u>	<u>8 bits</u>	<u>N. Units are frame (see subsection</u>

		8.4.6.1.1.3.1
Synchronization frame offset	4 bits	Ks, Units are frame (see subsection 8.4.6.1.1.3.1)
}		
If (Config_type[1] == 1){		
Neighbor monitoring cycle	4 bits	M, Units are frame (see subsection 8.4.6.1.1.3.2)
Neighbor monitoring frame offset	4 bits	Km, Units are frame (see subsection 8.4.6.1.1.3.1)
Neighbor monitoring frame repetition	8 bits	L, Units are frame (see subsection 8.4.6.1.1.3.1)
}		
}		
Report Request	1 bit	0: RSSI 1: CINR
}		
}		
Encoded TLV	Variable	
}		

Type of frame:

[This field indicates whether a single frame approach or multi frame approach is being used.](#)

Frame number:

[This is the frame number for the frame configuration to take effect. The system applies the frame configuration in the message starting from the frame number.](#)

DL indicator:

[1 indicates that the message include DL subframe configuration.](#)

UL indicator:

1 indicates that the message include UL subframe configuration.

Transceiver mode:

Transceiver mode in the relay zone is one of either Tx mode, Rx mode, or Idle mode. When the transceiver mode is idle mode, it does not transmit nor receive.

OFDMA symbol Offset :

The relay zone starts at the OFDMA symbol Offset.

Duration:

The relay zone ends after the duration starting from the OFDMA symbol offset. The unit of duration is OFDMA symbol.

Number of frame :

This field indicates the number of frames in a multi-frame.

Start Frame Number

The RS shall start transmitting/receiving the R-amble from this designated frame number

Monitoring_Duration

Duration (in units of frames) of the measurement/monitoring/transmission process. If the Monitoring_Duration value is set to 0x00 and prefix is 0b01 monitoring is to be continued until further notice

Interleaving Interval

The period (in units of frames) which is interleaved between the consecutive R-amble transmission/reception opportunity

Iteration

The requested number of iterating intervals

N_Transmitter

Number of stations instructed to transmit R-amble, the station may be RS or MR-BS.

N_Receiver_RS

Number of RSs instructed to receive R-amble

Amble index

R-amble means preamble, midamble or postamble transmitted in relay zone. It will be determined by R-amble location in downlink relay zone.

Synchronization Cycle Length, N

This field is used to indicate the synchronization R-amble period if present

Synchronization Frame Offset, Ks

The offset of the second R-amble in the synchronization cycle

Neighbor Monitoring Frame Repetition Rate, L

This field is used to indicate the neighbor monitoring R-amble period if present

Neighbor Monitoring Frame Offset, Km

The offset of the R-amble in the neighbor monitoring cycle

Neighbor Monitoring Cycle Length, M

This defines the number of neighbor monitoring R-amble frames in an R-amble monitoring cycle

[Insert the text from Page 26, Line 37 until Page 27, line28, and modify as indicated below and insert at the end of Section 6.3.2.3.77. Changes to the existing text is marked using track changes]

The MR-BS can send a RS_Config-REQ message to instruct the RSs to transmit or receive the R-amble in relay zone. This message can be sent by either unicast, multicast or broadcast CID of the RSs. ~~An 8 LSB bits of the frame number index will indicate the starting point of the subsequent R-amble transmission/reception opportunities. In order to instruct the stations in different MR-cell to transmit/receive the R-ambles at the same time, a coordinator in backhaul network is needed to ensure the Start Frame Number in the message sent by different MR-BSs will align to the same time.~~

When the Prefix is set as "00", the configuration message as per above (b) is sent, i.e. ~~t~~the RS shall follow the pattern instructed by MR-BS to transmit/receive the R-amble in relay zone. The pattern is composed by the amble index, and the RS shall transmit/receive the R-amble according to the field where its amble index is. Start Frame Number is the 8 LSB bits of frame number index used to indicate the starting point of subsequent R-amble transmission/reception opportunities. In order to coordinate the R-amble transmission/reception in different MR-cell, a coordinator in backhaul network is needed to ensure the Start Frame Number parameters sent in different MR-cell will align to the same time. The transmission opportunities are identified by Monitoring Duration and Interleaving Interval for each iteration. An example is given in Figure x, where the Duration = 2, Interleaving Interval = 3 and the Iteration = 2. When the Iteration is more than one, the pattern for each iteration will be carried in this message. After the last iteration, the RSs shall report the measurement results by RS_NBR-MEAS-REP message defined in 6.3.2.3.63.

[Move Lines 24-28 on Page 27 to the following paragraph as indicated below and insert at the end of Section 6.3.2.3.77. Changes to the existing text is marked using track changes]

If the Prefix is set "01", the configuration message as per above (c) is sent, i.e., the RS will autonomously transmit/receive the R-~~amble in relay zone~~ without periodic instruction from MR-BS by defining R-~~amble repetition patterns and monitoring patterns~~. The deactivation or activation of the functionalities of individual RSs can be done by sending (unicast) this message during initial entry of an RS. In the case of conflict, broadcast message parameters shall supersede the unicast message parameters except for the case of the parameter M which shall be set only by the unicast message. ~~–The detail design of the associated parameters is stated in 8.4.6.1.1.46.2.x.x. The RS is instructed to report its measurement results if the Prefix is set as "10" - When the RS is instructed to transmit/receive the R-~~amble transmission autonomously~~, the MR-BS shall send the measurements using standard measurement reporting mechanisms already defined in this document. Alternatively, MR-BS can instruct the RS to report its measurement results by this message with the prefix set as "10".~~

~~This message is transmitted (unicast or broadcast) by a MMR-BS for the purpose of RS configuration. A MMR-BS can use this message to set operation parameters for a RS. This also can be used to choose the R-~~amble repetition pattern and to activate or deactivate these monitoring/synchronization processes for a specified period.~~~~

~~The deactivation or activation of the functionalities of individual RSs can be done by sending (unicast) this message during initial entry of an RS. In the case of conflict, broadcast message parameters shall supersede the unicast message parameters except for the case of the parameter M which shall be set only by the unicast message.~~

[Delete the text of Section 6.6.2.3.66 from Page 26, Line 37 until the end of the Section]