

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >
Title	Receiver Sensitivity contribution to IEEE P802.16a/D2-2001
Date Submitted	2002-02-25
Source(s)	<p>Voice: (403) 207-6477 Fax: (403) 273-5100 gantonello@wi-lan.com srogers@wi-lan.com staylor@wi-lan.com slightfoot@wi-lan.com</p> <p>Gordon Antonello Shane Rogers Shawn Taylor Shawn Lightfoot</p> <p>Wi-LAN Inc. 2891 Sunridge Way NE Calgary, AB T1Y 7K7</p>
Re:	This is a contribution to the IEEE 802.16 TG3/TG4 document IEEE P802.16a/D2-2001.
Abstract	The contribution provides suggested text and Table 194 data for P802.16a/D2-2001 section 8.3.5.2.7.1 Receiver Sensitivity.
Purpose	To provide section 8.3.5.2.7.1 input, Table 203 data, and change the text for this section to match completed Table 203.
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.
Patent Policy and Procedures	<p>The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures (Version 1.0) <http://ieee802.org/16/ipr/patents/policy.html>, including the statement "IEEE standards may include the known use of patent(s), including patent applications, if there is technical justification in the opinion of the standards-developing committee and provided the IEEE receives assurance from the patent holder that it will license applicants under reasonable terms and conditions for the purpose of implementing the standard."</p> <p>Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair <mailto:r.b.marks@ieee.org> as early as possible, in written or electronic form, of any patents (granted or under application) that may cover technology that is under consideration by or has been approved by IEEE 802.16. The Chair will disclose this notification via the IEEE 802.16 web site <http://ieee802.org/16/ipr/patents/notices>.</p>

Suggested Text for Document IEEE P802.16a/D2-2001, section 8.3.5.2.7.1 Receiver Sensitivity

The following individuals have provided input to this contribution

Gordon Antonello

Shane Rogers

Shawn Taylor

Shawn Lightfoot

1 Introduction

This document Provides information towards completion of Table 203 in section 8.3.5.2.7.1 and makes changes to the text to reflect the updated table. The table is expanded to include most other channel bandwidths known by the authors to be relevant to the IEEE 802.16a standard.

2 Reference

[TG1/D5] IEEE P802.16/D5 - 2001.

[TG3&4/D2] IEEE 802.16a/D2 - 2001.

3 Suggested Text for Section 8.3.5.2.7.1

8.3.5.2.7.1 Receiver Sensitivity

The packet error rate (PER) shall be less than 10% at the power levels shown in Table 203 for standard message and test conditions. The measurement shall be taken at the antenna port or through a calibrated radiated test environment using standardized packet formats.

Table 203 – Receiver Sensitivity (dBm)

Channel Bandwidth h (MHz)	QPSK		16QAM		64QAM	
	—	—	—	—	—	—
1.5						
1.75						
3.0						
3.5						
5.0						
6.0						
7.0						
10.0						
12.0						
14.0						
15.0						
20.0						

Standard test messages:

Test messages for measuring Receiver Sensitivity shall be based on a MAC PDU with defined payloads.

Short test message payload:

Short test message payload packets are 288 Bytes in length

QPSK: continuous stream of packets each containing the sequence REPEAT (n, [0xE4, 0xB1, 0xE1, 0xB4]) where n = 72

16QAM: continuous stream of packets each containing the sequence REPEAT (n, [0xA8, 0x20, 0xB9, 0x31, 0xEC, 0x64, 0xFD, 0x75]) where n = 36

64QAM: continuous stream of packets each containing sequence REPEAT (n, [0xB6, 0x93, 0x49, 0xB2, 0x83, 0x08, 0x96, 0x11, 0x41, 0x92, 0x01, 0x00, 0xBA, 0xA3, 0x8A, 0x9A, 0x21, 0x82, 0xD7, 0x15, 0x51, 0xD3, 0x05, 0x10, 0xDB, 0x25, 0x92, 0xF7, 0x97, 0x59, 0xF3, 0x87, 0x18, 0xBE, 0xB3, 0xCB, 0x9E, 0x31, 0xC3, 0xDF, 0x35, 0xD3, 0xFB, 0xA7, 0x9A, 0xFF, 0xB7, 0xDB]) where n = 6

Long test message payload:

Long test message payload packets are 1536 Bytes in length

QPSK: continuous stream of packets each containing the sequence REPEAT (n, [0xE4, 0xB1, 0xE1, 0xB4]) where n = 384

16QAM: continuous stream of packets each containing the sequence REPEAT (n, [0xA8, 0x20, 0xB9, 0x31, 0xEC, 0x64, 0xFD, 0x75]) where n = 192

64QAM: continuous stream of packets each containing sequence REPEAT (n, [0xB6, 0x93, 0x49, 0xB2, 0x83, 0x08, 0x96, 0x11, 0x41, 0x92, 0x01, 0x00, 0xBA, 0xA3, 0x8A, 0x9A, 0x21, 0x82, 0xD7, 0x15, 0x51, 0xD3, 0x05, 0x10, 0xDB, 0x25, 0x92, 0xF7, 0x97, 0x59, 0xF3, 0x87, 0x18, 0xBE, 0xB3, 0xCB, 0x9E, 0x31, 0xC3, 0xDF, 0x35, 0xD3, 0xFB, 0xA7, 0x9A, 0xFF, 0xB7, 0xDB]) where n = 32

Test Conditions:

Ambient room temperature, shielded room, conducted measurement at the RF port if available, radiated measurement in a calibrated test environment if the antenna is integrated, and FEC is enabled.