

Handover in 802.16e MAC

IEEE 802.16 Presentation Submission Template (Rev. 8.3)

Document Number:

IEEE S802.16e-03/01

Date Submitted:

2003-01-12

Source:

Vladimir Yanover

Alvarion Ltd.

11/5 Shtern Str.

Herzlya Israel

Voice: +972-36457834

Fax: +972-36456262

E-mail: vladimir.yanover@alvarion.com

Venue:

Meeting #23

Base Document:

IEEE C802.16e-03/01 http://ieee802.org/16/tge/contrib/C80216e-03_01.pdf

Purpose:

The document is intended to be presented to 802.16E TG

Notice:

This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.

Release:

The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.

IEEE 802.16 Patent Policy:

The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures <<http://ieee802.org/16/ipr/patents/policy.html>>, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair <<mailto:chair@wirelessman.org>> as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site <<http://ieee802.org/16/ipr/patents/notices>>.

Handover in 802.16e MAC

Vladimir Yanover

Alvarion Ltd.

Service Definition

- Home IP network identification
 - specifies IP network to which the SS belong. It means that when the SS roams from one BS to another, an IP stack located on the top of Packet Convergence Sublayer (see [1] , “5.2 Packet Convergence Sublayer”) stays unaware on the roaming
- QoS Parameters for wireless communications

Service Definition

- Service is kept when changing the location:
 - Home IP network identification
 - specifies IP network to which the SS belong. It means that when the SS roams from one BS to another, an IP stack located on the top of Packet Convergence Sublayer stays unaware on the roaming
 - QoS Parameters for wireless communications

Main Features

- Terminal Assisted HO (MAHO)
- Intra- and Inter-BS HO
- HO Initiated by either terminal or BS, authorized by the network


Measurements

- Vacation Periods
 - SS periodically leaves the cell for an integer number of frame durations
 - at the Vacation Period SS tries to receive DL transmissions from neighbor base stations and in some cases communicates to them on Association (“visits” the neighbor BSs)
 - Serving BS is responsible to arrange for the SS vacation periods with no data transfer scheduled between the SS and BS

Measurements

- Visiting neighbor base stations
 - Initial list of HO candidate BSs broadcasted by each BS
 - Visited BSs allocates MAINT transmission opportunities (TOs) for Association of visitors
- Measurements Results
 - The list of parameters measured while a SS visits a BS, is TBD. It will include certain PHY parameters (like RSSI, SNR) and system parameters like service availability at the visited BS.
- Results of measurements are transferred to the serving BS. Serving BS may share this information with other BSs (MC)

Sets of Neighbor BSs



Sets of Neighbor BSs

- Detected BSs
- Monitored BSs i.e. those that are visited for passive measurements
- A subset of Monitored BSs is defined as Selected (for Association attempts)
- After Association, the BS becomes an Associated. Association is performed with limited number of neighbor AUs (see 5.5)

Sets of Neighbor BSs

- After completion of HO (Network Entry) the BS becomes Serving
- Upper layers at BS should include functions for authentication of SU and authorization of services through external server (functional equivalent of HLR at GSM/3G)
- Network should support mobility by changing the routing path for the IP datagrams

Association Procedure

- Visiting each Selected BS, the SS performs Association procedure similar to 802.16 Network Entry procedure:
 - Scan for downlink channel and establish synchronization with the BS
 - Obtain transmit parameters
 - Initial ranging
 - Negotiate basic capabilities
 - Authorize SS and perform key exchange
 - Negotiate availability of services allocated to the SS
 - Perform pre-registration
 - Transfer operational parameters
 - Information on Association is reported to the Serving BS

Neighbor BS Operations

- Respond to Ranging: with transmit power correction, time and frequency offsets
- Authentication of the terminal
- Check whether the terminal is authorized for certain services; setup of security association
- Pre-registration (as guest) including authorization of services [service meanwhile are not enabled]
- Optionally triggering TBD procedure for micro-mobility support (network level)

Serving BS Operations

- Serving BS
 - Collects measurements information and Association information received from SS
 - Performs measurement of signal received from SS
 - Makes decision on HO of the SS to another BS and executes the decision

Handover Decision

- **[Hard] Handover decision** is made by the SS after loosing effectively connection to serving BS
- **[Soft] Handover decision** is made by the network (BS/MC) according to link quality at the given cell and estimated link quality at neighbor cells.


HO Execution

- SS decides on HO to one of the Associated BSs, alone or together with the network
- The SS performs the rest of Network Entry procedure:
 - Informs the old BS and leaves
 - Jumps to the new BS's frequency and timing
 - Adjusts synchronization to DL

HO Execution – Cont.

- SS Informs the new BS on arrival using one of the following
 - Periodic ranging TOs
 - RR contention slots
- The new BS informs old BS (handshake) and the rest of Associated BSs on the HO. Also the network is informed for updating the IP routing paths [depends on the type of mobility support in the IP network]
- BS sets up connections to the SS
- After all that BS and SS continue regular operations.

Handover Solution



Handover Solution – Cont.

