

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	Proposed text for P802.16m Requirements Document -- Section 7	
Date Submitted	2007-02-25	
Source(s)	Jean-Pierre Balech Alcatel-Lucent, France	jean-pierre.balech@alcatel-lucent.fr +33 (1) 3077 4459
	Peretz Feder Alcatel-Lucent, New Jersey	pfeder@alcatel-lucent.com +1 973 386 6976
	Dan Gal Alcatel-Lucent, New Jersey	dgal@alcatel-lucent.com +1 973 428 7734
	Hardy Halbauer Alcatel-Lucent, Germany	hardy.halbauer@alcatel-lucent.de +49 (711821) 34182
	Ashok Rudrapatna Alcatel-Lucent, New Jersey	anr1@alcatel-lucent.com +1 973 386 7730
	Joerg Schaepperle Alcatel-Lucent, Germany	Joerg.Schaepperle@alcatel-lucent.de +49.711.821-32266
	Antoine Soulie Alcatel-Lucent, France	antoine.soulie@alcatel-lucent.com +33 (1) 40 76 1652
	Philippe Sehier Alcatel-Lucent, France	philippe.sehier@alcatel.fr
	Reinaldo Valenzuela (& team) Alcatel-Lucent, New Jersey	rav@alcatel-lucent.com +1 732 888 7031
Re:	IEEE 802.16m-07/004r1 – Call for Contributions for P802.16m Requirements	
Abstract	Proposed draft text for 802.16m Requirements Document -- Section 7	
Purpose	Incorporate into the draft-802.16m Requirements Document	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < http://ieee802.org/16/ipr/patents/policy.html >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < mailto:chair@wirelessman.org > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < http://ieee802.org/16/ipr/patents/notices >.	

Proposed Text for P802.16m Requirements Document – Section 7

Alcatel-Lucent 16m team

7.1 User throughput

Average rates

In a 20 MHz channel, the achievable average throughput, per terminal, in practical operational conditions (cellular environment, mobility effects, etc.) at typically required cell coverage, shall be at least 10 Mbps. The definition of average throughput per user terminal should be consistent with the definition and measurement specifics specified in the TGM Evaluation Criteria document (TBD).

PHY Improvements

Some improvements over the current 16e standard are required to increase performance in variable mobile user environments, mobility speeds and spectrum/bandwidth allocations. In particular, the service availability at the cell edge should be doubled (relative to “16e”) for the 10-percentile of the cell-edge users. Such improvements should be accompanied by increased spectral efficiency. Example solutions include:

- Extended MCS range to support large channel loss
- Waveform adaptation depending on channel multi-path spread and Doppler
- Increase spectrum efficiency by:
 - Enhanced multiple antenna schemes including BF and MIMO.
 - Frequency and time optimised scheduling (water-filling)
 - Interference avoidance, or coordination methods, to achieve higher cell edge throughput, and more uniform service availability

Adaptability to a wide range of user speeds

- High speed need large overhead for reference symbols and signalling
- In low speed environments, higher spectrum efficiency can be achieved
 - By lowering signalling and reference symbols overhead, or increase channel estimate (including channel sounding needed in CL MIMO)
- Cognitive methods should be used to get knowledge of users characteristics, and adapt the transmission format, receiver algorithms and sounding periodicity accordingly

MAC Optimization

Further optimization of the MAC should be considered for “16m”. Overhead for critical real-time, latency-sensitive applications, should be reduced as far as feasible without compromising other performance criteria. More specifically, 802.16m should support various FEC-block, MAC-PDU and other protocol layer block sizes, optimized for typical applications by minimizing padding bits, i.e., matching payload to block sizes for the key application that need to be supported (VoIP, Gaming, Video, etc).

Although backward compatible 802.16m should be able to receive the legacy DCD/UCD messages, as well as the DL and UL MAPs, other non compatible operating modes shall be supported where the overhead of the layer 2 maps is significantly reduced.

7.2 Spectrum efficiency

7.3 Mobility

For seamless mobility interoperation with other mobile wireless standards, Event, Command and Information services specified in IEEE 802.21 should be adopted by 802.16m as media-specific support. Event services in the 802.16m PHY and MAC should be supported by triggering link events when configurable thresholds are crossed, enabling the MIH (Media Independent Handover) function to react expeditiously to the changing channel conditions. Similarly, the MAC and PHY layers should be able to accept local and remote commands as specified in IEEE 802.21.

Mobility procedures should be fully compatible with the Network Control and Management Services (NCMS) procedures described in the IEEE 802.16g amendment. At a minimum, 802.16m shall support all the NCMS functional entities, described in IEEE 802.16g, which may be centrally located or distributed across the network.

7.4 Coverage

7.5 Enhanced Multicast-Broadcast