

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	Header-based ARQ Acknowledgement Scheme	
Date Submitted	2008-09-18	
Source(s)	Whai-En Chen National Ilan University Shiann-Tsong Sheu, Chih-Cheng Yang National Central University Kanchei (Ken) Loa, Yung-Ting Lee, Chiu-Wen Chen, Chun-Yen Hsu, Youn-Tai Lee, Yi-Hsueh Tsai, Tsung-Yu Tsai Institute for Information Industry Yang-Han Lee, Yih Guang Jan Tamkang University	Voice: +886-3-9357400#340 Fax: +886-3-9353804 wechen@niu.edu.tw Voice: +886-2-66000100 Fax: +886-2-66061007 loa@iii.org.tw
Re:	Re: MAC: Data Plane; in response to the TGm Call for Contributions and Comments 802.16m-08/033 for Session 57	
Abstract	This contribution proposes the text for ARQ scheme in 802.16m SDD	
Purpose	For discussion and approval by IEEE 802.16 TGm	
Notice	<i>This document does not represent the agreed views of the IEEE 802.16 Working Group or any of its subgroups. It represents only the views of the participants listed in the "Source(s)" field above. It is offered as a basis for discussion. It is not binding on the contributor(s), who reserve(s) the right to add, amend or withdraw material contained herein.</i>	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy	The contributor is familiar with the IEEE-SA Patent Policy and Procedures: < http://standards.ieee.org/guides/bylaws/sect6-7.html#6 > and < http://standards.ieee.org/guides/opman/sect6.html#6.3 >. Further information is located at < http://standards.ieee.org/board/pat/pat-material.html > and < http://standards.ieee.org/board/pat >.	

Header-based ARQ Acknowledgement Scheme

Whai-En Chen
National Ilan University

Shiann-Tsong Sheu, Chih-Cheng Yang
National Central University

Kanchei (Ken) Loa, Yung-Ting Lee, Chiu-Wen Chen, Chun-Yen Hsu, Youn-Tai Lee, Yi-Hsueh Tsai,
Tsun-Yu Tsai
Institute for Information Industry (III)

Yang-Han Lee, Yih Guang Jan
Tamkang University

Introduction

The IEEE 802.16e system supports ARQ scheme to accomplish the reliable transmissions for ARQ-enabled non-real-time services. The ARQ feedback information can be sent as a standalone MAC management message (ARQ_feedback message) or piggybacked on an existing connection. For an MS having the ARQ-enabled connection in downlink direction, it needs the uplink bandwidth for issuing the ARQ_feedback message to BS regularly; and the period of bandwidth request process requires at least three frames. To shorten the ARQ report latency and save bandwidth for reporting short ARQ_feedback message, we propose a header-based ARQ acknowledgement scheme for IEEE 802.16m system.

Message-based ARQ Acknowledgement Scheme

In order to efficiently use the channel resource, the legacy 16e system has defined four ARQ report types:

- Selective ACK (SA)
- Cumulative ACK (CA)
- Cumulative with Selective ACK (CSA)
- Cumulative ACK with Block Sequence ACK (CABSA)

The Cumulative ACK (CA) message only carries the information of block sequence number (BSN), which indicates the corresponding block and all blocks with lesser values within the transmission window have been successfully received. The selective ACK (SA) message carries the information of ARQ ACK MAP, which indicates the successfully received ARQ blocks and unsuccessfully received ARQ blocks. The CSA message combines both information of BSN and ACK MAP. The CABSA message is the most complicated one among four report types. According to the status of data reception, using different ARQ report type to carry ARQ feedback information will cause different overheads.

When an MS desires to send an ARQ_feedback message to BS but has no available uplink bandwidth, it shall follow the contention-based bandwidth request procedure, as illustrated in Fig 1. In legacy 16e system, the process of an MS reporting short ARQ_feedback message also follows the entire bandwidth request procedure, which spends six or more time frames, under the UL-MAP indicates the uplink allocations in the next frame.




Figure 1 The message-based UL ARQ acknowledgement mechanism, wherein the UL-MAP indicates UL resource allocations in the next frame.

Header-based ARQ Acknowledgement Scheme

As the channel quality is stable and the link adaptation functions well, the MS may always report the short CA-type ARQ_feedback message to BS. To efficiently report such short message, we propose a header-based ARQ acknowledgement process by using the ARQ_feedback header. As the BS allocates bandwidth to MS in response to the ranging code, MS may send the ARQ_feedback header to BS, instead of the legacy BR header. As illustrated in Figure 2, the header-based ARQ acknowledgment scheme is able to reduce the latency of ARQ feedback report.




Figure 2 The header-based UL ARQ acknowledgement scheme.

Proposed Text Changes:

[Add the following subclause 10.x “ARQ Functions”]

10.x ARQ Functions

In the UL ARQ acknowledgement scheme, the ARQ feedback information should be sent in message or

header format. When BS first allocates bandwidth to MS in response to the received BR ranging code, the MS may send the ARQ feedback header to BS, instead of the legacy BR header.