

BS Coordinated Data Forwarding (BSCDF)

IEEE 802.16 Presentation Submission Template (Rev. 9)

Document Number:

[IEEE S802.16m-08/1355r2]

Date Submitted:

[2008-11-10]

Source:

Ki-Dong Lee and Li-Hsiang Sun
LG Electronics

Voice: +1-858-635-5300
E-mail: kidonglee@lge.com

*<<http://standards.ieee.org/faqs/affiliationFAQ.html>>

Venue:

IEEE 802.16m-08/040“Call for Contributions on Project 802.16m System Description Document (SDD)”, in response to the following topics: “Relaying Model”, MAC related]

Base Contribution:

N/A

Purpose:

to be discussed and adopted by TGm for the 802.16m SDD

Notice:

This document does not represent the agreed views of the IEEE 802.16 Working Group or any of its subgroups. It represents only the views of the participants listed in the “Source(s)” field above. It is offered as a basis for discussion. It is not binding on the contributor(s), who reserve(s) the right to add, amend or withdraw material contained herein.

Release:

The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE’s name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE’s sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.

Patent Policy:

The contributor is familiar with the IEEE-SA Patent Policy and Procedures:

<<http://standards.ieee.org/guides/bylaws/sect6-7.html#6>> and <<http://standards.ieee.org/guides/opman/sect6.html#6.3>>.

Further information is located at <<http://standards.ieee.org/board/pat/pat-material.html>> and <<http://standards.ieee.org/board/pat>>.


BS Coordinated Data Forwarding (BSCDF)

Ki-Dong Lee and Li-Hsiang Sun
LG Electronics

Update in Oct. 2008

Introduction (1/2)

- Tree v.s. Mesh




- Relay/node selection
- Handover
- Topology change from Mesh to PMP;
- Billing/charging
- Security

*: in .16e stage, “mesh mode” was referred to as “relay mode”

** : traffic may not go through BS nor RS

Introduction (2/2)


- Tree topology
 - Example: cellular network w/ single path relays
 - Pros: simple to handle (but not always)
 - Cons: not throughput-optimal; not always shortest path
- Mesh topology
 - Example: *ad hoc* network
 - Pros: throughput-efficient (but not always)
 - Cons: hard to handle/control; hard to achieve or approach the know performance bound



Now, what is proposed...


BS Coordinated Data Forwarding (1)

- Partitioning information
 - BS controlled (PMP networking)
 - Primary control information
 - Connection setup: AAA
 - Connection maintenance
 - BS non-controlled (Mesh networking)
 - Secondary control information
 - Link control
 - Traffic





Functional Division and Collaboration

- Computing/Making Decision/Signaling for




Flow Division

- Flow of Control Traffic
 - Primary (MS-RS, RS-RS, RS-BS) via PMP
 - Secondary (MS-RS, RS-RS)
- Flow of Data Traffic via Mesh
 - “Mesh” link formed
 - E2E Delay-wise shortest
 - Throughput-wise shortest
 - Forward path != backward path, wherever available



BS Coordinated Data Forwarding (2/5)

- Proposed Scope of CMN
 - Connection coverage
 - Within a cell (MS A and MS B)
 - Between adjacent cells (MS A and MS C; MS B and MS C)
 - One BS or multiple BS's make decision whether to open HMN connection or not
 - Routing map (or table) is handled by BS
 - BS handled routing map/table: a lookup table for the destination BS to check if the source RS and the destination RS are within CMN scope




Procedure of BSCDF (1/3)

- (paging successfully done)
- Source MS → home RS → home BS → (backhaul) → destination MS
- Destination BS checks if the pair of MS's are eligible for CMN
 - And gives the result back to the home BS
- If CMN eligible,
 - Home BS ordered the home RS to do CMN
 - Destination BS ordered the destination RS to get ready for CMN

Procedure of BSCDF (2/3)

- If CMN eligible (cont.),
 - Home RS sends (using routing table/map)
 - BS-controlled information to BS (as PMP mode)
 - BS non-controlled information (incl. traffic) to the next RS or next node (as Mesh mode)
 - Destination RS can either copy the forward route from home RS or set up a different backward route using its own routing table/map
 - Depending on the traffic congestion on a certain node in the path(s)




Procedure of BSCDF (3/3)

- If CMN eligible (cont.),
 - Radio Link Control: Each RS in the Mesh path can do its own link control
 - If MS location changes or if handover is needed,
 - The associated RS
 - (1) Reports to the BS and BS allocates a new RS to the MS
 - (2) Requests handover to the new RS


Handover in BSCDF with a Single RS

- Handover can be handled by RS with result report to RS (if no approval is needed in advance)
- Handover can be handled by BS with report from RS
- Within the same cell:
 - If MS A, which wants to talk to MS B, is connected to RS 2 and if RS moves to MS C point, then MS B (in a new location of MS C's) and MS A can be switched to RS 3, if needed and feasible
- Between two or more neighboring cells
 - If MS A, which wants to talk to MS B, is connected to RS 3, then RS 3 can be connected to RS 2, if feasible



Performance Review

- In multihop environments, the **probability** that an MS can use BSCDF is **large**; this prob increases as # hops increases
 - Since the area ratio of 0th tier relative to the whole cell is very small, it is very likely that a large number of MS's can experience the BSCMN
- E2E throughput increase: Since the throughput bottleneck usually happens in the 1st link from BS, if 10% of MS's uses BSCMN, it results in 10% potential increase in E2E throughput
 - In 16m FS, the 1st link can hardly be assigned more than two subframe
- E2E delay is reduced: by number of hops or by throughput increase in turn



Possible Improvements

- Reduction in control traffic due to reduction of avg # links/hops
- Alleviate the heavy load in the center tier(s)
- E2E throughput (resource utilization): possible reduction in number of hops
- E2E delay: result from reduced number of hops and from improved utilization and the alleviated burden on the 1st hop link (from BS)
- Handover dropping (connection level)
 - The same (under normal traffic load conditions)
 - Can be improved (under heavy traffic load conditions)
- Easy to control the mesh network in comparison to (full) mesh networking
- Easy to handle the UL/DL traffic asymmetry

$$\eta = \lim_{V_{relay} \rightarrow \infty} \frac{V_{receiveDown} + V_{relay}}{V_{receiveUp} + V_{relay}} = 1$$

$$\eta = \lim_{V_{relay} \rightarrow \infty} \frac{V_{receiveDown} + V_{relay} \cdot f_{selfish}}{V_{sendUp} + V_{relay} \cdot f_{selfish}} = \begin{cases} \frac{V_{receiveDown}}{V_{sendUp}} (> 1), & f_{selfish} = 0 \\ 1, & f_{selfish} \neq 0 \end{cases}$$

Proposed Text

- Data traffic going up to BS and coming back through the same path in part should have a reduced path.
- [Note]
 - This data forwarding architecture does not violate the current scope of 16jm so far.