

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	DL MU-MIMO codebook	
Date Submitted	2008-09-05	
Source(s)	Wookbong Lee, Bin-chul Ihm LG Electronics	E-mail: wbong@lge.com , bcihm@lge.com * http://standards.ieee.org/faqs/affiliationFAQ.html >
Re:	PHY: MIMO; in response to the TGM Call for Contributions and Comments 802.16m-08/033 for Session 57	
Abstract	In this contribution, we discuss downlink multi-user MIMO codebook	
Purpose	Discuss and adopt in TGM	
Notice	<i>This document does not represent the agreed views of the IEEE 802.16 Working Group or any of its subgroups. It represents only the views of the participants listed in the "Source(s)" field above. It is offered as a basis for discussion. It is not binding on the contributor(s), who reserve(s) the right to add, amend or withdraw material contained herein.</i>	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy	The contributor is familiar with the IEEE-SA Patent Policy and Procedures: < http://standards.ieee.org/guides/bylaws/sect6-7.html#6 > and < http://standards.ieee.org/guides/opman/sect6.html#6.3 >. Further information is located at < http://standards.ieee.org/board/pat/pat-material.html > and < http://standards.ieee.org/board/pat >.	

DL MU-MIMO codebook

Wookbong Lee and Bin-Chul Ihm

LG Electronics

1. Codebook reconfiguration

There are two kinds of major MU-MIMO candidates in IEEE 802.16m. First one is based on non-unitary transmission and second one is based on unitary transmission. Depending on MU-MIMO scheme and feedback mechanism, the preferred sizes of codebook are different.

There are two kinds of method which can handle this issue.

First one is codebook subset selection. Predefine multiple (≥ 2) subsets (one for large and one for small) and indicate which one will be used for MU-MIMO.

Second method is codebook reconfiguration so called “codebook subset restriction.”

Basic idea of this concept is indicating which codebook elements are used or restricted.

Second method requires more bits to indicate but more flexible than first method.

But both schemes commonly require which codebook subset will be used.

2. Proposed Remedy

Remedy

line 29, page 73, add the following sentence:

The codebook is a subset (including full set) of SU-MIMO codebook. BS indicates which codebook subset will be used.