

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	Proposed text related to Interference Mitigation in Femto ABS for the IEEE802.16m/D2 (15.4.11)	
Date Submitted	2009-11-04	
Source(s)	Linghang Fan, Andreas Maeder, Nader Zein, Hassan Al-kanani, Tetsu Ikeda NEC	[Linghang.fan, nader.zein, hassan.alkanani] @eu.nec.com andreas.maeder@nw.neclab.eu, t-ikeda@ap.jp.nec.com
Re:	LB comment to 802.16m Amendment Working Document D2	
Abstract	This contribution is to propose detail description on IM	
Purpose	Update P802.16m/D2 by discussion and adoption	
Notice	<i>This document does not represent the agreed views of the IEEE 802.16 Working Group or any of its subgroups. It represents only the views of the participants listed in the "Source(s)" field above. It is offered as a basis for discussion. It is not binding on the contributor(s), who reserve(s) the right to add, amend or withdraw material contained herein.</i>	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy	The contributor is familiar with the IEEE-SA Patent Policy and Procedures: < http://standards.ieee.org/guides/bylaws/sect6-7.html#6 > and < http://standards.ieee.org/guides/opman/sect6.html#6.3 >. Further information is located at < http://standards.ieee.org/board/pat/pat-material.html > and < http://standards.ieee.org/board/pat >.	

Proposed text related to Interference Mitigation in Femto ABS for the IEEE802.16m/D2 (15.4.11)

Linghang Fan, Andreas Maeder, Nader Zein, Hassan Al-kanani, Tetsu Ikeda

NEC

1. Introduction

Section 15.4.11 in D2 has defined the procedures for interference avoidance and interference mitigation. The received signaling power from the adjacent cells has been classified as interference, and it is not need to distinguish the interference sources. However, in the hierarchical and dense deployed femtocell environment, the femtocell BSs must identify each major interference source, and then apply interference mitigation schemes targeting the identified interference sources. This is missed in the current draft.

In addition, since the measurement metrics CINR and RSSI cannot be easily used to distinguish the signal from each macro/femtocell base station, we propose to use CNR as the measurement metric in the scanning messages.

2. Proposed Texts

-----Text Start -----

Remedy 1 :

[Insert texts as suggested below: Page 551, Line 14]

15.4.11 Interference Avoidance and Interference Mitigation

The serving Femto ABS can request its AMS(s) to report the signal strength measurement of neighbor ABSs, including macro and/or Femto ABSs, via AAI_SCN-RSP. The serving femto ABS should identify the interfering Femto ABS(s) and/or macro ABS(s) by the CNR in the report metric. The serving femto ABS can mitigate interference, based on AMSs' scanning report, by reducing its transmission power, and/or blocking the interference related resource region. Cooperation between multiple ABSs may be applied.

Remedy 2 :

[Modify texts as suggested below: Page 51, Table 682]

15.2.6.12 AAI_SCN-RSP

Table 682—Parameters for AAI_SCN-RSP message

Report metric	Bitmap indicator of trigger metrics that the serving ABS requests the AMS to report. The serving ABS shall indicate only the trigger metrics agreed during AAI_SBC-	
---------------	---	--

	REQ/RSP negotiation. Each bit indicates whether reports will be initiated by trigger based on the corresponding metric:	
Bit 0: BS CINR mean		
Bit 1: BS RSSI mean		
Bit 2: Relative delay		
Bit 3: BS RTD		
Bits 4: BS CNR mean	The BS CNR Mean parameter indicates the CNR measured by the AMS from the serving ABS. The value shall be interpreted as a signed byte with units of 0.5 dB. The measurement shall be performed on the subcarriers of the frame preamble that are active in the serving ABS's segment and averaged over the measurement period.	
Bit 4-5: Reserved; shall be set to zero		

Remedy 3 :

[Modify texts as suggested below: Page 54, Table 683]

15.2.6.13 AAI_SCN-REP**Table 683—Parameters for AAI_SCN-REP message**

Report metric	Bitmap indicator of trigger metrics that the serving ABS requests the AMS to report. The serving ABS shall indicate only the trigger metrics agreed during AAI_SBC-REQ/RSP negotiation. Each bit indicates whether reports will be initiated by trigger based on the corresponding metric:	
Bit 0: BS CINR mean		
Bit 1: BS RSSI mean		
Bit 2: Relative delay		
Bit 3: BS RTD		

Bits 4: BS CNR mean	The BS CNR Mean parameter indicates the CNR measured by the AMS from the serving ABS. The value shall be interpreted as a signed byte with units of 0.5 dB. The measurement shall be performed on the subcarriers of the frame preamble that are active in the serving ABS's segment and averaged over the measurement period.	
Bit 4-5: Reserved; shall be set to zero		

-----Text End-----