

# A Reference Model for 802.17

Anoop Ghanwani

[anoop@lanterncom.com](mailto:anoop@lanterncom.com)

IEEE 802.17 Plenary Meeting

St. Louis, MO

March 2002

# Motivation

- We need a reference model for standardization
- The model should not simply be a block diagram of an implementation
- It should be possible for multiple implementations to conform to the model


# Purpose of a Reference Model

- Provides a reference for developing state machines
- All features that are part of the standard must be explicable using the block diagram
- Provides a clear, consistent picture to guide us through the development of the standard
  - What we have now is inadequate, and often inconsistent
- Provides a “big picture” view of the standard
- Not necessarily representative of how things are implemented

# Reference Model Requirements

- The RPR MAC is a fairly complex MAC (fairness, protection, topology, etc.)
- The reference model must capture all of the features and their interworking
  - 2 PHYs
  - Dual ringlets
  - Protection using steering and wrapping
  - Topology
  - Ringlet selection for data sourced at the node
  - Bandwidth management and media access control

# Reference Model for the RPR MAC



# Reference Model Description (1) – Transmit Data Path

- Ringlet Selection: Either uses data from the client and/or information from topology and protection components
- Policing: Simple or VDQ policing
- Control Mux: Multiplexes control and data packets
- Transmit Mux: Multiplexes/schedules packets from the node and transit packets
- Bandwidth Monitor: Monitors activity on the output link

# Reference Model Description (2) – Receive/Transit Data Path

- Receive Logic: Decides whether to receive, receive and transit, strip the frame, etc.
- Ctrl Mux: Sends control packets to appropriate module
- Frame collector: Gathers frames from both ringlets and passes them up to the client
- Transit buffer: Holds transit frames as they wait to be scheduled for transmission by the Transmit Mux.

# Reference Model Description (3) – Control Entities

- Fairness Control Unit: Performs the computations, consumes received messages and schedules fairness messages
- Protection Control Unit: Consumes/transmits protection messages and communicates with entities within the MAC to implement protection
- Topology Control Unit: Participates in the topology discovery and provides the necessary information to other components
- MAC Control



# State Machines

- Need to have state machines describing each block in the reference model
- The state machine:
  - Shows the states that each block can be in
  - Describes the transitions between the states
- Also need to have a diagram that shows the relationship between related state machines

# State Machine for the Fairness Control Unit

- TBD

# Conclusions

- Need a reference model for 802.17
- The model should be able to cover all features that the standard discusses
- We should use the model to develop state machines for the standard