MMF Ad Hoc meeting minutes

29th November 2012
Unapproved minutes
recorded by Jonathan King

MMF ad hoc meeting minutes, 29th Nov 2012 ... 1

- Meeting started at 8:30 am Pacific, chaired by Jonathan King.
- Attendee list was taken from the Webex attendee list, ~60 attendees were noted.
- **Presentations** shared in the MMF ad hoc can be found at the MMF ad hoc web page.
 - http://www.ieee802.org/3/bm/public/mmfadhoc/meetings/index.html
- **IEEE patent policy:** Attendees were reminded of the IEEE patent policy
 - http://www.ieee802.org/3/patent.html
- Agenda slides agreed.
- Meeting minutes for 25th Oct: Jonathan asked if anyone had amendments to the unapproved minutes for the 25th October meeting. One name/affiliation error was noted and corrected before the meeting. No further comments were made, so the minutes are approved by the MMF Ad Hoc.
- Presentations and discussion:
- Pete Anslow: BER and FER for 100GBASE-SR4
- Pete described different methods for calculating the relationship between uncorrected BER, corrected BER and FER (Frame Error Ratio) for optical links using the RS(528,514) FEC scheme defined in Clause 91 of IEEE P802.3bj D 1.2. Pete's analysis leads to a proposal that:
 - BER at the PMA service interface should be less than 5×10^{-5} to meet the required FER
 - For a complete Physical Layer, this specification is considered to be satisfied by a FER less than 5.12×10^{-10} for 64 octet frames with minimum inter-packet gap
- During discussion, Pete recommended a statement should be added to clarify that this BER requirement assumes uncorrelated errors, several others agreed. Pete asked if anyone *disagreed* with the proposed requirement of FER less than 5.12×10^{-10} (calculation method C, Q at PMA interface >3.89); Piers said he preferred the requirement of FER less than 6.62×10^{-10} (calculation method B, Q at PMA interface >3.88).
- Also shown was the how FEC changes the effect of optical margin on a system: For a receiver limited by Gaussian receiver noise, a margin of ~0.5 dB is required to give a BER of 10^{-15} rather than the spec limit of 10^{-12} . With the addition of RS(528,514) FEC, the same 0.5 dB margin takes the BER from 10^{-12} to $\approx 10^{-19}$.

MMF ad hoc telecon minutes, 29th Nov 2012 ... 2

• Presentations and discussion continued:

- John Petrilla: 100G 100m (& 20m) MMF Transceivers
- John presented further work jitter budgets for retimed and un-retimed links addressing the 100m and 20m reach on MMF objectives, which use the FEC scheme defined in Cl. 91 of IEEE P802.3bj D1.2.
 - John presented sensitivity analyses of MMF links to margin vs BER and bit rate, reach vs BER, and reach and margin vs jitter at TP4.
 - John's work shows that the maximum reach for the retimed PMD will be 110m on OM4, and that an un-retimed 20m reach PMD could be supported, provided strong DFE is not needed in the host to recover the signal.
 - John said he will update his modeling using a Q consistent with a BER of $5x10^{-5}$ at the PMA service interface (this presentation used $6.9x10^{-5}$). This may reduce the retimed PMD's reach by up to 5m.

Actions and issues requiring resolution

- A description is needed for the error statistics required at the PMA service interface in order to meet the required FER. Pete Anslow, Adam Healey, Mike Dudek, Matt Brown were particularly active during discussion of this topic.
- A PIC statement will be required to describe the PMA service interface BER requirement and the error statistics.
- 802.3bm will also need to define a normative test to guarantee system operation

MMF ad hoc telecon minutes, 29th Nov 2012 ... 3

- Other items needing resolution/further work:
 - If defined, should the 20m reach PMD be compatible with the 100m PMD?
 - Further contributions addressing the 100m MMF reach objective
 - Further contributions addressing options for 20m MMF reach objective, showing significant cost density or power improvements

• Next meetings: TBC: Thursday 13th December, 2012, 8am Pacific

TBC: Thursday 20th December, 2012, 8am Pacific

Webex meeting details are shown on the last slide

Attendees

John Abbott, Corning
John D'Ambrosia, Force10Networks
Adrian Amezcua, Draka

Pete Anslow, Ciena

Murat Arabaci,

Luis Armenta, ANSYS

Chris Bergey, Wyle Labs

Brad Booth, Dell

Matt Brown, Applied Micro

Phil McClay, TE Connectivity

Adam Courchesne,

Piers Dawe, IPtronics

Stephen Docking, PMC-Sierra

Dan Dove, Applied Micro

Mike Dudek, QLogic

Ilango Ganga, Intel

Moa Garcia,

Ali Ghiasi, Broadcom

Hioroshi Hamano, Fujitsu

Adam Healey, LSI

Scott Irwin,

Jack Jewell, independant

Inho Kim, Intel

Miles Kimmitt,

Jonathan King, Finisar

Beth Kochuparambi, Cisco

Paul Kolesar, Commscope

Kumar,

Gerard Kuyt,

Ryan Latchman, Mindspeed

Kevin Lefebvre, Eigenlight

Sharon Lutz, US Conec

Arthur Marris, Cadence

Marco Mazzini, Cisco

David Ofelt, Juniper

Tom Palkert, Luxtera

Peter Pepeljugoski, IBM

John Petrilla, Avago Technologies

Liang Qiu, Source Photonics

Rick Rabinovich, Alcatel-Lucent

Adee Ran, Intel

Song Shang, Semtech Kapil Shrikhande, Dell

Jeff Slavik,

Greg McSorley, Amphenol

Ted Sprague,

Peter Stasser,

Andre Szczepanek, Inphi

Tawa,

Brian Teipen,

Nathan Tracy, TE

Ed Ulrichs,

Raman Venkataraman,

Zhongfeng Wang, Broadcom

CK Wong, FCI

Hiroki Yanagisawa,

Zengli,

Webex details

- Start: 8am Pacific, 4pm GMT, 1.5 hours duration
- Webex meeting number: 598 394 654
- Meeting password: IEEE
- ------
- To join the meeting go to
 - https://finisar.webex.com/finisar/j.php?J=592272448&PW=NYWY4OTVhYTAy
 - 2. If requested, enter your name and email address.
 - 3. Enter the meeting password: IEEE
 - 4. Click "Join".
 - 5. Follow the instructions that appear on your screen.
- Teleconference information
 - Call-in toll-free number: 1-8666545792 (US)
 - Show global numbers:
 https://www.tcconline.com/offSite/OffSiteController.jpf?cc=9805136069
 - Conference Code: 980 513 6069