

- Option C can be deleted, it does not address the issue (PClass Tables must be modified).

- Option B can be deleted, nobody likes this, it can only cause confusion.

## Comment (Clause 145.2.7, #45, Page 151, L15)

Table 145-11 and the following text in page 150 lines 9-11:

" PSE implementations may use  $VPSE = VPort\_PSE - 2P \text{ min}$  and  $RChan = RCh$  when powering using a single pairset, or  $RChan = RCh/2$  when powering using two pairsets to arrive at over-margined values as shown in Table 145-11"

There are few problems:

- a) If we plug the worst-case values of  $Vpse$  and  $Rch$  in Equations 145-2 and 145-3, we will not get the over margined fixed values in Table 145-11. There are significant unexplained differences in the specification.
- b) Class 1-3 value differences could be justified when Type 1 and Type PSEs was part of the 802.3bt spec. Now they are in separate clause 33.
- c) The value  $RCh=20 \Omega$  for Type 1 is not realistic and should not imposed on Type 3 and 4 PSE systems and even if we impose it, the Pclass values will be lower than Table 145-11.
- d) Table 145-11 numbers for Pclass define for class 1-6 with Type 4 PSEs are much lower due to lower  $Rch$  and/or higher  $Vpse_{\text{min}}$ .
- e) The PSE can set the true minimum PClass and PClass-2P by using Equation 145-2 and 145-3 as the intent of this spec but currently this objective is not met.
- f) In addition,  $Vpd$  per the assigned class need to be verified per the above arguments.

The solution for the problems above consist of 3 elements:

1. To disconnect between Table 145-11 and how we get the over-margined value, for example:  
" PSE implementations may use  $VPSE = VPort\_PSE - 2P \text{ min}$  and  $RChan = RCh$  when powering using a single pairset, or  $RChan = RCh/2$  when powering using two pairsets to arrive at over-margined values.~~as shown in Table 145-11~~"
2. Clarify that the values in Table 145-11 are based on the lower PSE type used per the assigned class which will generate the maximum Pclass or Pclass-2P.
3. To update Table 145-11 numbers per the overmargined values obtained from Equation 145-2 AND 145-3 when the worst case relevant Type parameters are used. See Annex A for details.



1 Discussion:

2 **In some rows in the table below, the actual calculated worst case values per Equations**  
 3 **145-2 and 145-3 are significantly lower than the values in Table 145-11.**

4

Table 145-11—Physical Layer power classifications

PD Requested Class	Number of PSE class events	Assigned Class	P <sub>Class</sub>	P <sub>Class-2P</sub>
PSEs connected to a single-signature PD				
1	1	1	4 W	—
2	1	2	7 W	—
0, 3 to 8	1	3	15.4 W	—
4 to 8	2 or 3	4	30 W	—
5	4	5	45 W	—
6 to 8	4	6	60 W	—
7	5	7	75 W	—
8	5	8	90 W	—
PSEs connected to a dual-signature PD (classification per pairset)				
1	1, 2, or 3	1	—	4 W
2	1, 2, or 3	2	—	7 W
3	1, 2, or 3	3	—	15.4 W
4 or 5	1	3	—	15.4 W
4 or 5	2 or 3	4	—	30 W
5	4	5	—	45 W

Fixed values based on Type 1 systems V<sub>pse</sub>=44V and R<sub>ch</sub>=20Ω

Fixed values based on Type 2 systems V<sub>pse</sub>=50V and R<sub>ch</sub>=12.5Ω

Fixed values based on Type 3 systems V<sub>pse</sub>=50V and R<sub>ch</sub>=12.5Ω

Fixed values based on Type 4 systems V<sub>pse</sub>=52V and R<sub>ch</sub>=12.5Ω

Fixed values based on Type 4 assigned class 1-6 doesn't match Table 145-11 due to the fact that in Type 4 V<sub>pse</sub> is higher than in Type 3.

12

13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23

NOTE 1—P<sub>Class</sub> is the minimum required power at the PSE PI calculated using minimum V<sub>Port PSE-2P</sub> and maximum R<sub>Chan</sub>. Use Equation (145-2) for other values of V<sub>Port PSE-2P</sub> and R<sub>Chan</sub>. For maximum power available to PDs, see Table 145-24.  
 NOTE 2—P<sub>Class-2P</sub> is the minimum required power for a pairset calculated using minimum V<sub>Port PSE-2P</sub> and maximum R<sub>Chan-2P</sub>. Use Equation (145-3) for other values of V<sub>Port PSE-2P</sub> and R<sub>Chan-2P</sub>. For maximum power available to PDs, see Table 145-25.  
 NOTE 3—The number of PSE class events refers to the number of class events since the most recent PD reset.

The minimum power output a PSE supports for the PD's assigned Class, when powering a single-signature PD, or supplying power in 2-pair mode, is defined by Equation (145-2). PSE implementations may use V<sub>PSE</sub> = V<sub>Port PSE-2P</sub> min and R<sub>Chan</sub> = R<sub>Ch</sub> when powering using a single pairset, or R<sub>Chan</sub> = R<sub>Ch</sub>/2 when powering using two pairsets to arrive at over-margined values as shown in Table 145-11. P<sub>Class</sub> may subsequently be adjusted using Data Link Layer classification.

$$P_{Class} = \left\{ V_{PSE} \times \left( \frac{V_{PSE} - \sqrt{V_{PSE}^2 - 4 \times R_{Chan} \times P_{Class, PD}}}{2 \times R_{Chan}} \right) \right\}_W \quad (145-2)$$

28

The minimum output power a PSE supports on a pairset for PSEs connected to a dual-signature PD is defined by Equation (145-3). PSE implementations may use V<sub>PSE</sub> = V<sub>Port PSE-2P</sub> min and R<sub>Chan</sub> = R<sub>Ch</sub> to arrive at over-margined values as shown in Table 145-11. P<sub>Class-2P</sub> may subsequently be adjusted using Data Link Layer classification.

29  
30  
31

$$P_{Class-2P} = \left\{ V_{PSE} \times \left( \frac{V_{PSE} - \sqrt{V_{PSE}^2 - 4 \times R_{Chan} \times P_{Class, PD-2P}}}{2 \times R_{Chan}} \right) \right\}_W \quad (145-3)$$

32



1 The differences between calculations per Equations 145-2 and 145-3 and Table 145-11.

2 Values that are  $>|0.1W|$  from the spec are marked with RED color.

This column information is no longer part of clause 145						
Requested Class	Spec. Table 145-11	Type 1/2 over 2-pairs	Type 3 Over 2-pairs	Type 4 Over 2-pairs	Type 3 Over 4-pairs	Type 4 Over 4-pairs
1	4W	4.006	3.92	3.91	3.88	3.88
2	7W	6.996	6.716	6.7	6.6	6.59
3	15.4W	15.4	14	13.89	13.45	13.42
4	30W	30	30	29.53	27.37	27.21
5	45W			45.02	45.08	44.6
6	60W				60	59.06
7	75W					75
8	90W					90.04
<b>Max Diff[W]</b>		<b>0.006</b>	<b>1.4</b>	<b>1.51</b>	<b>2.63</b>	<b>2.79</b>

3  
4

5 Notes:

6 Type 1,2 class 1-4 calculations per Equation 145-3 meets Table 145-11. They were calculated with  $V_{pse}=44V$  and  $R_{ch}=20 \Omega$ .

7

8 Type 3 class 1-3 calculated values per Equation 145-3 are lower than Table 145-11 values. They were calculated with  $V_{pse}=50V$   
9 and  $R_{ch}=12.5 \Omega$ .

10

11 Type 4 class 1-4 calculated values per Equation 145-3 are different than Table 145-11 values. They were calculated with  
12  $V_{pse}=52V$  and  $R_{ch}=12.5 \Omega$ .

13

14 Type 3 class 1-4 calculated values per Equation 145-2 are different than Table 145-11 values. They were calculated with  
15  $V_{pse}=50V$  and  $R_{chan}=6.25 \Omega$ .

16

17 Type 4 class 1-5 calculated values per Equation 145-2 are different than Table 145-11 values. They were calculated with  
18  $V_{pse}=52V$  with and  $R_{chan}=6.25 \Omega$ .

19

20

21

22

23

24

**BASELINE STARTS HERE**



## Suggested Remedy

There are 3 options. Options B and C are shown in the annexes for reference.

### Option A (Based on the calculations in Annex A)

#### 1. Modify Pclass and Pclass -2P in Table 145-11 per the following:

Pclass	Pclass-2P
4 3.92	-
7 6.72	-
<del>15.4</del> 14	-
30	-
<del>45</del> 45.1	-
60	-
75	-
90	-
-	4 3.92
-	7 6.72
-	<del>15.4</del> 14
-	<del>15.4</del> 14
-	30
-	45

Having these numbers down to 10mW resolution is a bit much. Round to 100mW resolution. Specifically, Class 5 should be 45W not 45.1W.

Does not match D2.4 text, nor does it produce a valid sentence. Please check.

#### 2. Modify the following text:

The minimum power output a PSE supports for the PD's assigned Class, when powering a single-signature PD, or supplying power in 2-pair mode, is defined by Equation (145-2). PSE implementations may use  $VPSE = VPort\_PSE-2P$  min when powering using a single pairset, or  $RChan = RCh/2$  when powering using two pairsets to arrive at over-margined values, as shown in Table 145-11 shows over-margined values for worst case PSE Type parameters. PClass may subsequently be adjusted using Data Link Layer classification.

$$P_{Class} = \left( V_{PSE} \cdot \left( \frac{V_{PSE} - \sqrt{V_{PSE}^2 - 4 \cdot R_{Chan} \cdot P_{Class, 2P}}}{2 \cdot R_{Chan}} \right) \right)_{W} \quad (145-2)$$

The minimum output power a PSE supports on a pairset for PSEs connected to a dual-signature PD is defined by Equation (145-3). PSE implementations may use  $VPSE = VPort\_PSE-2P$  min and  $RChan = RCh$  to arrive at over-margined values, as shown in Table 145-11 shows over-margined values for worst case PSE Type parameters. PClass-2P may subsequently be adjusted using Data Link Layer classification.

$$P_{Class, 2P} = \left( V_{PSE} \cdot \left( \frac{V_{PSE} - \sqrt{V_{PSE}^2 - 4 \cdot R_{Chan} \cdot P_{Class, 2P}}}{2 \cdot R_{Chan}} \right) \right)_{W} \quad (145-3)$$

Same here.



1  
2  
3  
4  
5  
6

3. *Modify Table 145-28 for Vport\_PD-2P as follows (See Annex C for details):*

	<i>From</i>	<i>To</i>
<i>Class 1</i>	42.1	48
<i>Class 2</i>	40.8	47
<i>Class 0,3</i>	37	44
<i>Class 4</i>	42.5	42.5
<i>Class 5, single-signature PD</i>	44.3	44.3
<i>Class 5, dual-signature PD</i>	41.2	41.2
<i>Class 6</i>	42.5	42.5
<i>Class 7</i>	42.9	42.9
<i>Class 8</i>	41.2	41.2



**End OF Baseline**



# 1 Annex A: Option A calculations for D2.5

2

3 Notes:

- 4 1. Type 1 and Type 2 PSEs are not part of clause 145.
- 5 2. Type 1 and Type 1 PDs need to be supported by Type 3 and Type 4 PSEs according to Table 145-1 RCh=12.5Ω
- 6 and not RCh=20Ω. Therefore, the case of RCh=20Ω is not part of the calculations to derive the spec for
- 7 clause 145.
- 8 3. The numbers for option A were rounded to the next 2 decimal point accuracy. In addition, the numbers for
- 9 option A for class 1-4 were calculated to be the maximum of 2-pairs and 4-pairs values regardless if it is
- 10 Type 3 or Type 4 (since there is only one value column for both PSE types and PSE may work on 2-pairs or 4-
- 11 pairs).

				(Rounded numbers to 2 decimal point, to be used for Option 2)				Option A			
	Not part of clause 145 spec			Part of clause 145 SPEC				Part of clause 145 SPEC			
Vpse	44	50	52	50	52	50	52	Pclass [W]		Pclass-2P[W]	
Rch	20	20	20	12.5	12.5	6.25	6.25				
	Type 1,2	Type 3	Type 4	Type 3	Type 4	Type 3	Type 4				
	Pclass 2-pais[W]			Pclass 2-pais[W]		Pclass 4-pais[W]					
Class 1	4.006	3.966	3.956	3.917	3.911	3.878	3.875	3.92	max(2-pairs, 4-pairs)	3.92	max(2-pairs)
Class 2	6.996	6.867	6.836	6.715	6.697	6.599	6.590	6.72	max(2-pairs, 4-pairs)	6.72	max(2-pairs)
Class 3	15.400	14.672	14.506	13.977	13.892	13.452	13.416	13.98	max(2-pairs, 4-pairs)	13.98	max(2-pairs)
Class 4	30.000	30.000	29.532	30.000	29.532	27.373	27.212	30	max(2-pairs, 4-pairs)	30.00	max(2-pairs)
Class 5	-	-		-	45.019	45.081	44.597	45.08	max(4-pairs)	45.02	max(2-pairs)
Class 6	-	-		-	-	60	59.063	60	max(4-pairs)		-
Class 7	-	-		-	-	-	75.002	75	max(4-pairs)		-
Class 8	-	-		-	-	-	90.038	90.04	max(4-pairs)		-

12

13



# Annex B: Option B calculations for D2.5

2

3 Notes:

- 4 1. Type 1 and Type 2 PSEs are not part of clause 145.
- 5 2. Type 1 and Type 1 PDs need to be supported by Type 3 and Type 4 PSEs according to Table 145-1 RCh=12.5Ω
- 6 and not RCh=20Ω. Therefore, the case of RCh=20Ω is not part of the calculations to derive the spec for
- 7 clause 145.
- 8 3. The numbers for option B were rounded to the next 2 decimal point accuracy.
- 9 4. The numbers for option B for class 1-4 were calculated per each Type separately and the maximum of 2-
- 10 pairs and 4-pairs values for each Type was taken. This is different than Option A where we had one column
- 11 for the values. As we can see, option B is more accurate and there are significant differences between D2.4
- 12 spec and Option B.

13

	Not part of clause 145 spec			Part of clause 145 SPEC				Option B spec			
Vpse	44	50	52	50	50	52	52	Pclass		Pclass-2P	
Rch	20	20	20	12.5	6.25	12.5	6.25				
	Type 1,2	Type 3	Type 4	Type 3	Type 3	Type 4	Type 4	Type 3	Type 4		
	Pclass 2-pais			Pclass-2P	Pclass	Pclass-2P	Pclass	Pclass		Pclass-2P	
Class 1	4.006	3.966	3.956	3.917	3.878	3.911	3.875	3.92	3.92	3.92	3.92
Class 2	6.996	6.867	6.836	6.715	6.599	6.697	6.590	6.72	6.72	6.72	6.7
Class 3	15.400	14.672	14.506	13.977	13.452	13.892	13.416	13.98	13.98	13.98	13.9
Class 4	30.000	30.000	29.532	30.000	27.373	29.532	27.212	30.00	30.00	30.00	29.53
Class 5	-	-		-	45.081	45.019	44.597	45.08	44.597	-	45.02
Class 6	-	-		-	60.000	-	59.063	60.00	59.063	-	-
Class 7	-	-		-	-	-	75.002	-	75.002	-	-
Class 8	-	-		-	-	-	90.038	-	90.038	-	-

14

15



1 Option B (Based on the calculations in Annex B)

2 **1. Modify Pclass and Pclass -2P in Table 145-11 as follows:**

3

Pclass		Pclass-2P	
Type 3	Type 4	Type 3	Type 4
4-3.92	4-3.92	-	-
7-6.72	7-6.72	-	-
15.4-14	15.4-14	-	-
30	30	-	-
45-45.1	45-44.6	-	-
60	60-59.1	-	-
	75	-	-
	90	-	-
-	-	4-3.92	4-3.92
-	-	7-6.72	7-6.7
-	-	15.4-14	15.4-13.9
-	-	15.4-14	15.4-13.9
-	-	30	30-29.53
-	-	-	45

4

5 **2. Modify the following text:**

6 The minimum power output a PSE supports for the PD's assigned Class, when powering a single-signature  
 7 PD, or supplying power in 2-pair mode, is defined by Equation (145-2). PSE implementations may use  
 8  $VPSE = VPort\_PSE-2P$  min when powering using a single pairset, or  $RChan = RCh/2$  when powering using  
 9 two pairsets to arrive at over-margined values. ~~as shown in~~ Table 145-11 shows over-margined values for  
 10 worst case PSE Type parameters. PClass may subsequently be adjusted using Data Link Layer  
 11 classification.

12 
$$P_{Class} = \left( V_{PSE} - \sqrt{\frac{V_{PSE}^2 - 4 \cdot R_{Chan} \cdot P_{Class-2P}}{2 \cdot R_{Chan}}} \right)_{W} \quad (145-2)$$

13 The minimum output power a PSE supports on a pairset for PSEs connected to a dual-signature PD is  
 14 defined by Equation (145-3). PSE implementations may use  $VPSE = VPort\_PSE-2P$  min and  $RChan = RCh$   
 15 to arrive at over-margined values. ~~as shown in~~ Table 145-11 shows over-margined values for worst case  
 16 PSE Type parameters. PClass-2P may subsequently be adjusted using Data Link Layer classification.

17 
$$P_{Class-2P} = \left( V_{PSE} - \sqrt{\frac{V_{PSE}^2 - 4 \cdot R_{Chan} \cdot P_{Class-2P}}{2 \cdot R_{Chan}}} \right)_{W} \quad (145-3)$$





1 **Option C (significant differences between the actual worst case numbers and Table 145-11 values)**

2  
3 **Modify the following text:**

4 The minimum power output a PSE supports for the PD's assigned Class, when powering a single-signature  
5 PD, or supplying power in 2-pair mode, is defined by Equation (145-2). PSE implementations may use  
6  $VPSE = VPort\_PSE-2P$  min when powering using a single pairset, or  $RChan = RCh/2$  when powering using  
7 two pairsets to arrive at over-margined values. ~~as shown in~~ Table 145-11 [shows over-margined values for](#)  
8 [worst case PSE Type parameters](#). PClass may subsequently be adjusted using Data Link Layer  
9 classification.

10 
$$P_{Class} = \left\{ V_{PSE} \times \left( \frac{V_{PSE} - \sqrt{V_{PSE}^2 - 4 \times R_{Chan} \times P_{Class\_PD}}}{2 \times R_{Chan}} \right) \right\}_W \quad (145-2)$$

11 The minimum output power a PSE supports on a pairset for PSEs connected to a dual-signature PD is  
12 defined by Equation (145-3). PSE implementations may use  $VPSE = VPort\_PSE-2P$  min and  $RChan = RCh$   
13 to arrive at over-margined values. ~~as shown in~~ Table 145-11 [shows over-margined values for worst case](#)  
14 [PSE Type parameters](#). PClass-2P may subsequently be adjusted using Data Link Layer classification.

15 
$$P_{Class-2P} = \left\{ V_{PSE} \times \left( \frac{V_{PSE} - \sqrt{V_{PSE}^2 - 4 \times R_{Chan} \times P_{Class\_PD-2P}}}{2 \times R_{Chan}} \right) \right\}_W \quad (145-3)$$



1 Annex C – PD input voltage calculations

2

	Type 1,2	Type 3	Type 4	Type 3	Type 4	Type 3	Type 4
	2P	2P	2P	2P	2P	4P	4P
Rch	20 for class 1-3 12.5 for class 4	20	20	12.5	12.5	12.5	12.5
<i>Class 1</i>	42.18	48.41	50.48	49.02	51.06	49.52	51.53
<i>Class 2</i>	40.82	47.25	49.37	48.32	50.39	49.18	51.21
<i>Class 3</i>	37.00	44.13	46.42	46.51	48.66	48.32	50.39
<i>Class 4</i>	42.50	42.50	44.90	42.50	44.90	46.58	48.73
<i>Class 5</i>					41.18	44.36	46.64
<i>Class 6</i>						42.50	44.90
<i>Class 7</i>							42.99
<i>Class 8</i>							41.18

3

