XGP

MSA (Multi-Source Agreement) Group

Overview and Status Report

Chris Simoneaux / Jack Jewell Picolight, Inc - Boulder, CO 303-530-3189 csimoneaux@picolight.com

IEEE 802.3ae Interim Meeting - New Orleans September 12 - 14, 2000

XGP MSA

Who is the XGP MSA Group?

• Group of 14 participating transceiver companies in the process of establishing a charter with a goal to develop an MSA document for 10Gbps optical transceivers


- Many of our participants from the SFP (Small Form-factor Pluggable) MSA group
- Develop a common transceiver package footprint to support the 10Gbps communications market
- Deliver footprint and functional specs to the industry in a timely manner
- Utilize ongoing industry feedback and liaison mechanisms through strong links to marketing and standards bodies






- Target P802.3ae requirements as well as other 10Gbps standards, such as 10Gig Fibre Channel
- Support 4-Lane electrical interface
- Pluggable electrical interface based on SFP connector design (hot pluggable desired)
- Leverage SFP mechanical design
- Support multiple fiber and electrical media connectors
- Mechanical form factor to support high density, EMI considerations, and thermal dissipation







p/cjs/9/00





- Ad hoc status
- Current focus on IP and operating procedures
- Multi-phase product definition process
 - Electrical connector requirements and definition
 - Form factor definition and thermal provisions
 - Guide rail/cage system
 - Optical connector and PMD variants
- Process strategy
 - Achieve maximum consensus with minimum # of variants
 - Timely development process





- Preliminary technical requirements being developed
- Electrical connector design approach established
 - Current "place holder" is a 50 pin Z-axis hot pluggable
- Pin assignments under development





- IP, operating procedures, & membership guidelines resolution
- Baseline proposal presentations at next meeting
- Pinout definition & refinement
- Face-to-face meetings every 2 months, Bi-weekly conference calls

