

Help My Info Report a Bug Logout

MyBallot Control Panel >> Manage MyBallot Activity >> Ballot Comments >> Comment Detail

P802.3-REVam Information technology -- Telecommunications and information exchange between systems --Local and metropolitan area networks -- specific requirements Part 3: Carrier Sense Multiple Access with Collision Detection (CSMA/CD) Access Method and Physical Layer Specifications

#100 comment # 1734 Date: 01/12/2005

Must be No satisfied:

Category: Editorial

Comment: Seeing as how the ballot closing has been postponed, and I have been looking hard at open-drain circuits, I just did a survey on the spelling of those resistive elements used in that environment. The result: "pull-up", 8 occurrences, "pullup" 2 occurrences (but one is apparently hyphenated to "pull-up" across a line break), "pull up" 7 occurrences. I prefer the hyphenated form, which would also appear to have won a Florida-US-Supreme-Court type victory.

The statistics for "pull-down" (5 occurrences, including plurals) vs. "pulldown" (1 occurrence, in a PICS) vs. "pull down" (0 occurrence) are even more mandative.

Proposed Change all occurrences of "pullup" and "pull up" to "pull-up", and of "pulldown" to "pull-down". Change:

Resolution Principle

Status:

Resolution ACCEPT IN PRINCIPLE. Detail: See MyBallot comment #1900.

Return to the Ballot Comments

back to top

Copyright © 2004-2005 IEEE myballot@ieee.org