

30. Management

30.3 Layer management for DTEs

30.3.2.1.2 aPhyType

Insert entry in APPROPRIATE SYNTAX as follows:

APPROPRIATE SYNTAX:

...
1000BASE-T1 Clause 97 1000 Mb/s PAM3

30.3.2.1.3 aPhyTypeList

Insert entry in APPROPRIATE SYNTAX as follows:

APPROPRIATE SYNTAX:

...
1000BASE-T1 Clause 97 1000 Mb/s PAM3

30.5 Layer management for medium attachment units (MAUs)

30.5.1.1.2 aMAUType

Insert entry in APPROPRIATE SYNTAX as follows and insert entry below 1000BASE-T2:

APPROPRIATE SYNTAX:

...
1000BASE-T1 Single balanced twisted-pair copper cabling PHY as specified in Clause 97

30.5.1.1.4 aMediaAvailable

Insert into the third paragraph in BEHAVIOUR DEFINED AS section of 30.5.1.1.4 after the second sentence as follows:

BEHAVIOUR DEFINED AS:

...
For 1000BASE-T1, a link_status of OK maps to the enumeration “available”. All other states of link_status map to the enumeration “not available”.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54