

IEEE 802.3 Ethernet Working Group Liaison Communication

Source: IEEE 802.3 Working Group¹

To: Dr Albrecht Oehler Convenor, ISO/IEC JTC1/SC25 WG3
albrecht.oehler@fh-reutlingen.de

CC: Paul Nikolich Chair, IEEE 802 LMSC
p.nikolich@ieee.org

Adam Healey Vice-chair, IEEE 802.3 Ethernet Working Group
adam.healey@avagotech.com

Pete Anslow Secretary, IEEE 802.3 Ethernet Working Group
panslow@ciena.com

David Chalupsky Chair, IEEE P802.3bq Task Force
david.chalupsky@intel.com

Jürgen Tretter Secretary, ISO/IEC SC25
tretterconsult@gmail.com

Alan Flatman Liaison Officer, IEEE 802.3 & ISO/IEC JTC 1/SC 25/WG 3
a_flatman@tiscali.co.uk

From: David Law Chair, IEEE 802.3 Ethernet Working Group
dlaw@hpe.com

Subject: Reply to Incoming Liaison 25N2461 on 40GBASE-T Return Loss Requirements

Approval: Approved at IEEE 802.3 Meeting in Atlanta, GA on 21 January 2016

Dear Dr Oehler,

Thank you for your liaison on 40GBASE-T Return Loss Requirements. This was considered at the IEEE P802.3bq Task Force meeting in November 2015. Task Force members decided not to implement a length-dependent requirement to the IEEE P802.3bq Link Segment specification and, instead, adopted the Return Loss relaxation adopted for Class I & Class II cabling without any length dependence. The requirements in the latest draft of IEEE P802.3bq are as follows:

¹ This document solely represents the views of the IEEE 802.3 Working Group, and does not necessarily represent a position of the IEEE, the IEEE Standards Association, or IEEE 802.

113.7.2.3 Return loss

In order to limit the noise at the receiver due to impedance mismatches in the cabling system, each link segment duplex channel shall meet the values determined using Equation (113–14) at all frequencies from 1 MHz to $2000 \times S$ MHz. The reference impedance for the return loss specification is 100 Ω .

$$\text{Return Loss} \geq \begin{array}{ll} 19 & 1 \leq f < 10 \\ 24 - 5\log_{10} f & 10 \leq f < 40 \\ 16 & 40 \leq f < 130 \\ 35 - 9\log_{10} f & 130 \leq f < 1000 \\ 8 & 1000 \leq f < 1250 \\ 8 & 1250 \leq f < 1600 \text{ (for 40GBASE-T)} \\ 8 - 19\log_{10}\left(\frac{f}{1600}\right) & 1600 \leq f < 2000 \text{ (for 40GBASE-T)} \end{array} \quad \text{dB} \quad (113-14)$$

where

f is the frequency in MHz.

IEEE P802.3bq has now entered its final stage of review, Sponsor Ballot, and is planned to become an approved standard as early as June 2016, or likely no later than September 2016. A copy of the latest draft (D3.1) will be made available for your next meeting. IEEE P802.3bq makes formal reference to ISO/IEC 11801-1 which we hope will become technically stable in that timeframe (preferably FDIS status). We would be grateful if you could provide a status report on ISO/IEC 11801-1 and a copy of your latest draft.

Sincerely,

David Law

Chair, IEEE 802.3 Ethernet Working Group