

IEEE 802.3 NGOATH SG

Adopted Changes to 802.3bs Project Objectives

- **Support a MAC data rate of 200 Gb/s**
- Support a MAC data rate of 400 Gb/s
- Support a BER of better than or equal to 10^{-13} at the MAC/PLS service interface (or the frame loss ratio equivalent)
- Support full-duplex operation only
- Preserve the Ethernet frame format utilizing the Ethernet MAC
- Preserve minimum and maximum FrameSize of current Ethernet standard
- Provide appropriate support for OTN
- **Provide physical layer specifications which support 200 Gb/s operation over:**
 - **At least 500m of 4-lane parallel SMF**
 - **At least 2 km of SMF**
 - **At least 10 km of SMF**
- Provide physical layer specifications which support **400 Gb/s operation over:** ~~link distances of:~~
 - At least 100 m **of** ~~over~~ MMF
 - At least 500 m **of** ~~over~~ SMF
 - At least 2 km **of** ~~over~~ SMF
 - At least 10 km **of** ~~over~~ SMF
- Specify optional Energy Efficient Ethernet (EEE) capability ~~for 400 Gb/s PHYs~~
- Support optional ~~400 Gb/s~~ Attachment Unit Interfaces for chip-to-chip and chip-to-module applications

Adopted by IEEE 802.3 NGOATH Study Group ,Jan 22, 2016, IEEE 802 Jan 2016 Interim, Atlanta, GA, USA
Updated by IEEE 802.3 NGOATH Study Group, Mar 16, 2016, IEEE 802 Mar 2016 Plenary, Macau, China.