

IEEE 802.3 Ethernet Working Group Liaison Communication

Source: IEEE 802.3 Working Group¹

To:

Ray Emplit Chair, TIA TR-42 Telecommunications Cabling Systems Committee
remplit@harger.com

Greg Sandels Chair, TIA TR-42.13 Passive Optical Devices and Fiber Optic Metrology Subcommittee
gsandels@ofsoptics.com

Paul Nikolich Chair, IEEE 802 LMSC
p.nikolich@ieee.org

Adam Healey Vice-chair, IEEE 802.3 Ethernet Working Group
adam.healey@broadcom.com

Pete Anslow Secretary, IEEE 802.3 Ethernet Working Group
panslow@ciena.com

CC:

John D'Ambrosia Chair, IEEE P802.3bs Task Force
email@address.something

Valerie Maguire TIA Incoming Liaison to IEEE 802.3 Working Group
valerie_maguire@siemon.com

Chris DiMinico IEEE 802.3 Working Group Incoming Liaison to TIA
cdiminico@ieee.org

Germaine Palangdao Manager, TIA Emerging Technologies
gpalangdao@tiaonline.org

Teesha Jenkins Manager, TIA Standards Secretariat Services
tjenkins@tiaonline.org

From: David Law Chair, IEEE 802.3 Ethernet Working Group
dlaw@hpe.com

Subject: Liaison letter to TIA TR-42.13 informing of the need for minimum return loss performance for array plugs and corresponding active device receptacles for single-mode applications

Approval: Agreed to at IEEE 802.3 interim WG meeting, Whistler, B.C., Canada, May 26, 2016

Dear Mr. Emplit and Mr. Sandels,

As lane rates are increasing from approximately 25 Gb/s to 50 Gb/s and 100 Gb/s, the P802.3bs Task Force adopted the use of 4-level pulse amplitude modulation (PAM4) instead of non-return to zero (NRZ) modulation. The P802.3cd Task Force is also expected to employ PAM4 modulation. While PAM4 delivers twice the number of bits per symbol as

¹ This document solely represents the views of the IEEE 802.3 Working Group, and does not necessarily represent a position of the IEEE, the IEEE Standards Association, or IEEE 802.

NRZ, it also increases sensitivity to multipath interference (MPI) effects. Ensuring a minimum return loss of connection interfaces reduces MPI and its attendant power penalty.

We request TR-42 standardize array plugs and any associated device receptacles that can deliver minimum return loss of at least 45 dB at end of life in cable plant deployments. For example, the use of angled polish connectors (APC) has proven to be a robust way of delivering this return loss performance.

Thank you for your consideration.

Sincerely,

David Law

Chair, IEEE 802.3 Ethernet Working Group