

Note: PSE Vdiff and PD Vdiff was combined for simplicity i.e. PD Vdiff can be considered as PSE Vdiff+PD Vdiff. Results are depened only by Total Vdiff.

	PSE	PD	PD	Channel	Cable					Components									
Parameter	Vpse_diff	Vdiff_diode	Ppd	Length	PAIR Runb	P2PRunb	Cordage Resistivity	Cable Resistivity	# OF Connectors	Rt_max	Rt_min	Rconn max	Rcon nmin	Rsense_max	Rsense_min	Rdson_max	Rdson_min	Rd	
Value	0	0.1	51	100	0.02	0.05	0.125	0.125	4	0.13	0.12	0.05	0.03	0.1	0.098	0.1	0.05	0.25	
Units	V	V	W	m	-	-	ohm	ohm	-	ohm	ohm	ohm	ohm	ohm	ohm	ohm	ohm	ohm	

Forming 12.5 ohms at 100m

	Ipair[mA]	Idiff[mA]	Itotal	Iunb=Runb
A+	I(R41)	642.322	105.05	1179.594
B+	I(R42)	537.272		
A-	I(R20)	626.123	72.652	1179.594
B-	I(R19)	553.471		6.2%

At 100m we get 1179mA instead of 1200mA which is 21mA less.

This is due to how the PD Model calculate the average voltage at its input due to unbalance at high currents.

Current unbalance wil not be changed due to this error since diodes VF doesn't changed significantly for DI=20mA

At currents of 500mA range.

	PSE	PD	PD	Channel	Cable					Components									
Parameter	Vpse_diff	Vdiff_diode	Ppd	Length	PAIR Runb	P2PRunb	Cordage Resistivity	Cable Resistivity	# OF Connectors	Rt_max	Rt_min	Rconn max	Rcon nmin	Rsense_max	Rsense_min	Rdson_max	Rdson_min	Rd	
Value	0	0.1	51	100	0.02	0.05	0.0926	0.074	4	0.13	0.12	0.05	0.03	0.1	0.098	0.1	0.05	0.25	
Units	V	V	W	m	-	-	ohm	ohm	-	ohm	ohm	ohm	ohm	ohm	ohm	ohm	ohm	ohm	

	Ipair[mA]	Idiff[mA]	Itotal	Iunb=Runb
A+	I(R41)	604.271	105.499	1103.043
B+	I(R42)	498.772		
A-	I(R20)	589.564	76.085	1103.043
B-	I(R19)	513.479		6.9%

WHY I GET 1100mA AT 100M ? Answer: Channel at worst case unbalance calculations is much less that 12.5 ohms. See adhoc report.

	PSE	PD	PD	Channel	Cable					Components									
Parameter	Vpse_diff	Vdiff_diode	Ppd	Length	PAIR Runb	P2PRunb	Cordage Resistivity	Cable Resistivity	# OF Connectors	Rt_max	Rt_min	Rconn max	Rcon nmin	Rsense_max	Rsense_min	Rdson_max	Rdson_min	Rd	
Value	0	0.1	51	5	0.02	0.05	0.0926	0.074	4	0.13	0.12	0.05	0.03	0.1	0.098	0.1	0.05	0.25	
Units	V	V	W	m	-	-	ohm	ohm	-	ohm	ohm	ohm	ohm	ohm	ohm	ohm	ohm	ohm	

	Ipair[mA]	Idiff[mA]	Itotal	Iunb=Runb
A+	I(R41)	597.69	175.109	1020.271
B+	I(R42)	422.581		
A-	I(R20)	582.247	144.224	1020.27
B-	I(R19)	438.023		14.1%

	PSE	PD	PD	Channel	Cable					Components									
Parameter	Vpse_diff	Vdiff_diode	Ppd	Length	PAIR Runb	P2PRunb	Cordage Resistivity	Cable Resistivity	# OF Connectors	Rt_max	Rt_min	Rconn max	Rcon nmin	Rsense_max	Rsense_min	Rdson_max	Rdson_min	Rd	
Value	0	0.1	51	5	0.02	0.05	0.0926	0.074	1	0.13	0.12	0.05	0.03	0.1	0.098	0.1	0.05	0.25	
Units	V	V	W	m	-	-	ohm	ohm	-	ohm	ohm	ohm	ohm	ohm	ohm	ohm	ohm	ohm	

	Ipair[mA]	Idiff[mA]	Itotal	lunb=Runb
A+	I(R41)	593.815	168.563	1019.067
B+	I(R42)	425.252		
A-	I(R20)	578.061	137.056	1019.066
B-	I(R19)	441.005		13.4%

	PSE	PD	PD	Channel	Cable					Components									
Parameter	Vpse_diff	Vdiff_diode	Ppd	Length	PAIR Runb	P2PRunb	Cordage Resistivity	Cable Resistivity	# OF Connectors	Rt_max	Rt_min	Rconn max	Rcon nmin	Rsense_max	Rsense_min	Rdson_max	Rdson_min	Rd	
Value	0	0.1	51	5	0.02	0.05	0.0926	0.074	0	0.13	0.12	0.05	0.03	0.1	0.098	0.1	0.05	0.25	
Units	V	V	W	m	-	-	ohm	ohm	-	ohm	ohm	ohm	ohm	ohm	ohm	ohm	ohm	ohm	

	Ipair[mA]	Idiff[mA]	Itotal	lunb=Runb
A+	I(R41)	592.408	166.15	1018.666
B+	I(R42)	426.258		
A-	I(R20)	576.567	134.467	1018.667
B-	I(R19)	442.1		13.2%

	PSE	PD	PD	Channel	Cable				Components									
Parameter	Vpse_diff	Vdiff_diode	Ppd	Length	PAIR Runb	P2PRunb	Cordage Resistivity	Cable Resistivity	# OF Connectors	Rt_max	Rt_min	Rconn max	Rcon nmin	Rsense_max	Rsense_min	Rdson_max	Rdson_min	Rd
Value	0	0.1	51	0.5	0.02	0.05	0.0926	0.074	0	0.13	0.12	0.05	0.03	0.1	0.098	0.1	0.05	0.25
Units	V	V	W	m	-	-	ohm	ohm	-	ohm	ohm	ohm	ohm	ohm	ohm	ohm	ohm	ohm

	Ipair[mA]	Idiff[mA]	Itotal	lunb=Runb
A+ I(R41)	602.677	189.986	1015.368	18.7%
B+ I(R42)	412.691			
A- I(R20)	583.874	152.38	1015.368	15.0%
B- I(R19)	431.494			

	Ipair[mA]	Idiff[mA]	Itotal	lunb=Runb
A+ I(R41)	602.822	190.152	1015.492	18.7%
B+ I(R42)	412.67			
A- I(R20)	568.883	122.273	1015.493	12.0%
B- I(R19)	446.61			

	Ipair[mA]	Idiff[mA]	Itotal	lunb=Runb
A+ I(R41)	602.374	190.113	1014.635	18.7%
B+ I(R42)	412.261			
A- I(R20)	595.158	175.681	1014.635	17.3%
B- I(R19)	419.477			

424.212m If Vamx and Vmin of the diode in th emodels are reversed we will get the following:

591.249m The maximum current locations are changed and became a bit lower since

450.914m Now Vmax is in series to Rmax which helps to balance the current but still Vdiff is the dominate one

564.548m

602.822m If RDSON Rmax-Rmin is changed from 100% to 30% the negative pairs are improved as

412.670m Expected by 3%. No changes in th epositive pairs as expected.

568.883m

446.610m

For the same Rdson differencesof 30%

602.374m If RDSON is outside the unbalance circutry I.E. RDSON=0

412.261m The unbalance on th enegative pairs wereRDSON was removed will be increased as expected!

595.158m It means 1P Channel will have more unbalance at short channels.

419.477m

	PSE	PD	PD	Channel	Cable					Components									
Parameter	Vpse_diff	Vdiff_diode	Ppd	Length	PAIR Runb	P2PRunb	Cordage Resistivity	Cable Resistivity	# OF Connectors	Rt_max	Rt_min	Rconn max	Rcon nmin	Rsense_max	Rsense_min	Rdson_max	Rdson_min	Rd	
Value	0	0.1	51	0.15	0.02	0.05	0.0926	0.074	0	0.13	0.12	0.05	0.03	0.1	0.098	0.1	0.05	0.25	
Units	V	V	W	m	-	-	ohm	ohm	-	ohm	ohm	ohm	ohm	ohm	ohm	ohm	ohm	ohm	

	Ipair[mA]	Idiff[mA]	Itotal	lunb=Runb
A+ I(R41)	603.766	192.418	1015.114	19.0%
B+ I(R42)	411.348			
A- I(R20)	584.61	154.106	1015.114	15.2%
B- I(R19)	430.504			

	PSE	PD	PD	Channel	Cable					Components									
Parameter	Vpse_diff	Vdiff_diode	Ppd	Length	PAIR Runb	P2PRunb	Cordage Resistivity	Cable Resistivity	# OF Connectors	Rt_max	Rt_min	Rconn max	Rcon nmin	Rsense_max	Rsense_min	Rdson_max	Rdson_min	Rd	
Value	0	0.2	51	0.15	0.02	0.05	0.0926	0.074	0	0.13	0.12	0.05	0.03	0.1	0.098	0.1	0.05	0.25	
Units	V	V	W	m	-	-	ohm	ohm	-	ohm	ohm	ohm	ohm	ohm	ohm	ohm	ohm	ohm	

	Ipair[mA]	Idiff[mA]	Itotal	lunb=Runb
A+ I(R41)	690.851	366.381	1015.321	36.1%
B+ I(R42)	324.47			
A- I(R20)	650.056	284.79	1015.322	28.0%
B- I(R19)	365.266			

Unbalance was increased due to Vdiff increase

	Ipair[mA]	Idiff[mA]	Itotal	lunb=Runb
A+ I(R41)	690.927	366.394	1015.46	36.1%
B+ I(R42)	324.533			
A- I(R20)	633.424	251.388	1015.46	24.8%
B- I(R19)	382.036			

690.927m No changes on positive pairs as expected.

324.533m

633.424m 17mA reduction (3.9% less in Runbalance) if RDSON differences is 30% instead of 100%.

382.036m