

IEEE 802.3cg 10 Mb/s Single Twisted Pair Ethernet

ELEVATOR/ESCALATOR USE CASE

Introduction (elevators, global)

- Current network solutions:
 - Volume: mainly RS485-, CAN- and simple proprietary solution-based products
 - Sporadic: copper twisted pair point-to-point Ethernet ($\leq 100\text{m}$)
- On the worldwide market:
 - Currently: ≈ 850.000 new installations / year: each having avg. 20 serial port interfaces
 - 2020: $\approx 1.000.000$ new installations / year
- Requirements of near-future systems (functional safety, voice and video streaming) can not be met using these networks
- Product's life (market-dependent):
 - life-span is 15-20 years
 - life-time is 15-30 years, replaced/modernized afterwards
- We can estimate that half of the 20 million nodes per year market could be Ethernet-based in ten years' time

Example of current network (ISO OSI)

- L1: RS485, ≤ 250 kbps (slew-rate limited), ≤ 4000 f (≈ 1200 m), half duplex/multidrop (≤ 128 PHY)
- Single 18-23AWG stranded shielded twisted pair (copper), with termination
- L2: Manchester, CSMA/CA (p-persistent), 16-bit CRC
- L3-L7: proprietary protocol
- Several types of connectors (pitch in the range of 3-5.08mm)
- Separate wires in the same cable/connector for power and configuration/discovery
- Network may be branched: 1 backbone, single-level branches off of it (each branch with ≤ 128 PHY)

Why not standard (existing) Ethernet?

- Cabling
 - With parallel cabling: number of wires / m of distance covered
 - With serial cabling: single point (node) of failure
- Reach and speed: outside of the expected range

Planned network: L1 (PHY)

- Commercial solution preferred
- Till then solution should be possible to be implemented in $\leq 100\text{MHz}$ Cortex-M4/7 without FP, with ADC/DAC and native DSP (or similar)
- High level of flexibility with regards to hardware:
 - Cable
 - Connector (including IDC*)
 - Details: twist, stripping etc.

* Insulation Displacement Connector

Planned network: details

- Elevators: two models used as building blocks
 - Model A: branches (or very simple real systems)
 - Model B: trunk
 - Model A+B: real systems of wide range (distance and number of nodes)
- Self-synchronizing or support for a drift inherent to crystals (200ppm over whole temperature range)
- Framing should allow the following message classes to be supported (in decreasing order of importance):
 - Isochronous: safety monitoring (10/s, max jitter 1ms)
 - Immediate: safety events (≤ 20 /s, delivery within 1ms)
 - Ad-hoc (on-demand): events (≤ 200 /s, delivery within 10ms without safety)
 - Realtime: audio and video (properties are TBD)
 - None (idle): burn unused bandwidth for telemetry, file transfer (no guaranteed service)

Planned network: environment

- Systems:
 - Elevators: Two models
 - Model A: ≤ 16 nodes, $\leq 100\text{m}$
 - Model B: ≤ 16 nodes, $\leq 1000\text{m}$
 - Model A+B: 200(+) nodes, 1000(+)m
 - Escalators: Simple network with few (≤ 10) nodes and medium reach ($\leq 50\text{m}$), model A
 - Powerwalks: Simple network with few (≤ 10) nodes and medium reach ($\leq 100\text{m}$), model A
- Environmental conditions
 - Industrial conditions, with temperature range of -20°C – $+65^{\circ}\text{C}$
- Electrical requirements
 - Overvoltage and ground fault protection $\pm 40\text{V}$
 - Short- and open-circuit protection
 - Electrostatic discharge protection (EN 61000-4-2) 15kV
 - Fast transient protection (EN 61000-4-4) 2kV

Planned network: on noise


- Sources:
 - Mains: 50 or 60Hz, 1- or 3-phase
 - Motor drive and motor: (in shaft or machine room)
 - Ground loops, cross-coupling of switching transients
- Motors: hoisting (fixed) and doors (moving)
 - AC induction
 - Permanent Magnet AC
- Outside world:
 - Native: wireless devices, gadgets (working within specs)
 - Occasional: vandalism (malicious intent)
- Measurements and demonstration is possible
- Channel model: TBD

Planned network: model A (branches)

- Architecture: Single bus, 1 PHY/node (multidrop)
- Type: single shielded copper TP
 - As target is new device market (or when not, cables are replaced during modernization), there is high level of flexibility adopting external specs on cable and possibly on connectors
- Segment length: $\leq 100\text{m}$
- Nodes: ≤ 16 nodes
- PoDL: $\leq 50\text{W}$ (avg.), $\leq 100\text{W}$ (peak)
- Other factors:
 - Native topology discovery: desired (through software): installation-time automatic node self-configuration (based on node order and possibly approximate distance)

Planned network: model A, diagram

Model A




Planned network: model B (backbone)

- Same as model A, with exceptions:
 - Segment length: $\leq 1000\text{m}$
 - PoDL not needed
 - Cable may need to be weight-bearing (complete or part of own weight) with or without IDC

Planned network: model B, diagram

Model B




Planned network: hybrid (complete network)

- Single A:
 - Simplest elevators
 - Most of the escalators and power-walks (only power consumption may be an issue)
- A+B:
 - Anything that is beyond the above
 - Number of A segments is determined by system factors (total reach, power consumption)

Planned network: hybrid, diagram

Model B backbone with model A branches



Thank you for your kind attention

Ari Kattainen

Gergely Huszak