IEEE 802.3 Ethernet Working Group DRAFT Liaison Communication

Source: IEEE 802.3 Working Group¹

To:	Steve Trowbridge	Chairman, ITU-T SG15 <u>steve.trowbridge@nokia.com</u>
	Hiroshi OTA	ITU-T SG15 Advisor <u>tsbsg15@itu.int</u>
	Peter Stassar	Rapporteur, ITU-T Q6/15 <u>peter.stassar@huawei.com</u>
	Ed Frlan	OIF TC Chair <u>Efrlan@semtech.com</u>
	Kimberly Naughton	OIF liaison <u>liaisons@oiforum.org</u>
CC:	Konstantinos Karachalios	Secretary, IEEE-SA Standards Board Secretary, IEEE-SA Board of Governors <u>sasecretary@ieee.org</u>
	Paul Nikolich	Chair, IEEE 802 LMSC p.nikolich@ieee.org
	Adam Healey	Vice-chair, IEEE 802.3 Ethernet Working Group adam.healey@broadcom.com
	Jon Lewis	Secretary, IEEE 802.3 Ethernet Working Group jon.lewis@dell.com
	John D'Ambrosia	Chair, IEEE P802.3ct Task Force jdambrosia@ieee.org
From:	David Law	Chair, IEEE 802.3 Ethernet Working Group <u>dlaw@hpe.com</u>

Subject: Progress on P802.3ct (pending P802.3cw) Task Force

Approval: Agreed to at IEEE 802.3 interim meeting, Geneva, Switzerland, 23 January 2020

Dear Mr. Trowbridge and members of ITU-T Study Group 15,

Dear Mr. Frlan and members of OIF,

As a reminder, we have agreed to split the IEEE P802.3ct project, retaining 100 Gb/s Ethernet operation over a DWDM system in IEEE P802.3ct, while moving 400 Gb/s Ethernet operation over a DWDM system to a new project, IEEE P802.3cw. The P802.3cw PAR is still pending approval by NesCom/SASB, which is expected in early February.

¹ This document solely represents the views of the IEEE 802.3 Working Group, and does not necessarily represent a position of the IEEE, the IEEE Standards Association, or IEEE 802.

At our January interim meeting in Geneva Switzerland (meeting materials at: <u>http://ieee802.org/3/ct/public/20_01/index.html</u>), several decisions were made within the scope of the new IEEE P802.3cw project.

- It was agreed to change the grid spacing for 400GBASE-ZR from 100 GHz to 75 GHz.
- It was agreed to adopt 191.375 to 196.1 THz as the frequency range for 400GBASE-ZR, 64 channels.
- It was agreed to adopt the EVM measurement methodology defined by Slides 5-9 of <u>pittala 3ct 01a 0120.pdf</u> to enable correlation for the definition of a transmitter metric.

We look forward to continued collaboration with ITU-T SG15 and OIF on 400 Gb/s technologies.

Sincerely,

David Law

Chair, IEEE 802.3 Ethernet Working Group