

101.3.2.2 64B/66B Encode

The 64B/66B encoder shall perform the functions specified in {Figure 49–16}. The 64B/66B encoding process is as described in {49.2.4}, with the following exceptions:

- a) the 64B/66B encode process in the EPoC PCS operates on 72-bit vectors obtained from the output of the Idle control character deletion process (see 101.3.2.1), rather than directly from the XGMII; and
- b) the 64B/66B encode process in the EPoC PCS operates on bursty data stream produced by the Idle control character deletion process, unlike in 10GBASE-R PCS, where data stream to the input of the 64B/66B encoder is taken directly from the XGMII and hence continuous.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54

101.3.3.6 64B/66B Decode

The 64B/66B decoder shall perform the functions specified in {Figure 49–17}. The 64B/66B decoding process is as described in {49.2.11}, with the following exceptions:

- a) the 64B/66B decode process in the EPoC PCS produces 72-bit vectors fed into the Idle control character insertion process (see 101.3.3.7), rather than directly into the XGMII; and
- b) the 64B/66B decode process in the EPoC PCS operates on bursty data stream produced by the FEC decoder, unlike in 10GBASE-R PCS, where data stream to the input of the 64B/66B decoder is taken directly from the descrambler and hence continuous.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54