

# **BCN Calibration Simulation Results Pause Sample Window**


**Zhi-Hern Loh**  
zloh@fulcrummicro.com  
10/19/2006



# Workload

- **Traffic Type: 100% UDP (or raw Ethernet) Traffic**
- **Destination: EP0-EP3 sending to EP4**
- **Frame Size Distribution: 1500 byte fixed**
- **Arrival Distribution: Bernoulli temporal distribution**
- **Offered load at endpoint = 50%**

# Topology



- Link capacity 10Gbps
- Core switch egress port buffer size infinite
- Rate limiter queue buffer size 150KB
- Switch latency (1 us)
- Link length (not modelled, 0 latency)
- Endpoint response time (not modelled, 0 latency)

# BCN Parameters

- **Qeq 375 \* 64 byte pages**
- **Frame Sampling 150KB +- 5KB (random jitter)**
- **W = 2**
- **Gi = 5.3 x 10<sup>-1</sup>**
- **Gd = 2.6 x 10<sup>-4</sup>**
- **Ru = 1 Mbps**



# Simulations

- **Parameters**


- No limits on max queue length at congestion point
- Data sets
  - Pause only
  - Pause + BCN
  - Pause + BCN(0,0)
  - Sample Window Sweep for normal BCN

# Pause

- **Global pause**


- Pause all inputs if memory exceeds pause on watermarks
- Unpause all inputs if memory drops below pause off watermark
- Pause on 140 KB
- Pause off 130 KB

# Pause




# Pause Egress Throughput

Egress Throughput vs Time






# Pause Accepted Throughput




# Pause Edge Switch Occupancy



# Pause + BCN


- **Rmin 1 Gbps**
- **Drift disabled**
- **BCN CP detection not disabled for edge switches ES1-4**
  - Have some BCN messages from ES1-4 during onset of congestion.

# Pause + BCN



# Pause+BCN


## Egress Throughput vs Time






# Pause+BCN

## RLQ Rate vs Time




# Pause+BCN

## Accepted Throughput



# Pause+BCN



# Pause + BCN


- **Differences from Bergamasco's results**
  - Edge Switches have BCN turned on
    - Congestion spike in congestion point queue has shorter duration due to stronger feedback.
    - Duration of spike
      - Approx 0.003 with BCN on at edge switches
      - Approx 0.007 with BCN off at edge switches

# Pause + BCN(0,0)

- **Qsc = 112.5KB**




# Pause + BCN(0,0)




# Pause + BCN(0,0)

Egress Throughput vs Time




# Pause + BCN(0,0)

RLQ Rate vs Time




# Pause + BCN(0,0)

## Accepted Throughput



# Pause + BCN(0,0)






# Sweep Over Sample Window Length


- **What happens when sample window is decreased?**
- **Simulation datasets**
  - Window sizes = 10, 20, 40, 60, 80, 100 KB
  - Random jitter +/- 5KB for all window sizes
  - 25 runs per datapoint
- **Results**
  - Plot peak queue size vs sample window
  - Plot fairness index vs sample window
    - Fairness measured over  $t = 20 - 80$  ms

# Window size 10KB




# Window size 10KB

Egress Throughput vs Time




# Window size 10KB


## RLQ Rate vs Time




# Window size 10KB



# Averaged Peak Queue Size



# Fairness Index





# Standard Deviation in Fairness Index

