Provider Bridging -- Remote Customer Service Interface

PAR and 5c

Version 4

Ben Mack-Crane
Stephen Haddock
May 21, 2009
802.1 Interim, Pittsburgh

Title

- PAR for an amendment to an existing Standard 802.1Q
- IEEE Standard for Local and Metropolitan Area Networks---Virtual Bridged Local Area Networks - Amendment: Provider Bridging -- Remote Customer Service Interfaces

Scope

This standard allows an S-tagged service interface connecting two independently administered Provider Bridged Networks to be used to handle traffic (identified by a single S-VLAN identifier) for a given customer port attached to one PBN as if the customer were directly attached to the other PBN using a Portbased or C-tagged service interface.

Purpose

Metro Ethernet service providers need to provide service to customer locations not directly accessible to their network. Such "out-of-footprint" access may be obtained via other (access) service providers; however, the primary service provider has an interest in minimizing the amount of provisioning required of an access provider. This standard meets this need by specifying Provider Bridging technology that allows the primary service provider to treat customers connected via an access network as if they were directly connected to the primary service provider's network.

Need

 Metro Ethernet service providers need standardized Provider Bridge functionality that allows customers connected via an independently operated access network to be provided service as if they were directly connected to the service provider's network.

Stakeholders

 Vendors, users, administrators, designers, customers, and owners of Provider Bridged Networks.

Other standards with similar scope

 There are no IEEE standards specifying the functionality required for handling outof-footprint customer traffic at the interface between two Provider Bridged Networks.

Five Criteria

Broad Market Potential

A standards project authorized by IEEE 802 shall have a broad market potential. Specifically, it shall have the potential for:

- Broad sets of applicability.
 - The commercial provision of Metro Ethernet services is a large and growing business involving cooperative arrangements between service providers to offer end-to-end service.
- Multiple vendors and numerous users.
 - The same large body of vendors and users having a requirement for IEEE 802.1Q in service provider networks.
- Balanced costs (LAN versus attached stations).
 - This project does not materially alter the existing cost structure of bridged networks.

Compatibility

- IEEE 802 defines a family of standards. All standards shall be in conformance with the IEEE 802.1 Architecture, Management, and Interworking documents as follows: 802. Overview and Architecture, 802.1D, 802.1Q, and parts of 802.1f. If any variances in conformance emerge, they shall be thoroughly disclosed and reviewed with 802.
 - This PAR is for an enhancement to Provider Bridging that is intended to be fully compatible with the currently specified Provider Bridging functionality.
- Each standard in the IEEE 802 family of standards shall include a definition of managed objects that are compatible with systems management standards.
 - Such a definition will be included.

Distinct Identity

Each IEEE 802 standard shall have a distinct identity. To achieve this, each authorized project shall be:

- Substantially different from other IEEE 802 standards.
 - There are no IEEE standards specifying the functionality required for handling out-of-footprint customer traffic at the interface between two Provider Bridged Networks.
- One unique solution per problem (not two solutions to a problem).
 - There are no other standard solutions addressing Provider Bridging remote access.
- Easy for the document reader to select the relevant specification.
 - This project will amend the only IEEE 802 standard defining Provider Bridged Networking.

Technical Feasibility

For a project to be authorized, it shall be able to show its technical feasibility. At a minimum, the proposed project shall show:

- Demonstrated system feasibility.
 - The function is similar in complexity to existing functions in 802.1Q, which have been successfully implemented.
- Proven technology, reasonable testing.
 - The function can be implemented using existing frame formats. Compliance with the project can be tested using straightforward extensions of existing test tools for bridged networks.
- Confidence in reliability.
 - The reliability of the modified protocols will be not be measurably worse than that of the existing bridged networks.

Economic Feasibility

For a project to be authorized, it shall be able to show economic feasibility (so far as can reasonably be estimated) for its intended applications. At a minimum, the proposed project shall show:

- Known cost factors, reliable data.
 - This project introduces no significant frame processing beyond that currently specified for VLAN aware bridge components.
- Reasonable cost for performance.
 - Pre-standard deployments of similar functionality have been deployed at reasonable cost.
- Consideration of installation costs.
 - The cost of installing enhanced software and/or hardware, in exchange for improved network functionality, is familiar to vendors and users of bridged networks.