



P802.1Qbh Draft 0.2 Editors Report

Joe Pelissier

May, 2010

bh-pelissier-editors-report-0510-v02

Statistics

	Total	%
Approve	2	18
Disapprove	9	82
Abstain	19	63
Commenters	11	
Voters Responding	30	

	Required	Not Required	Total
Technical	47	3	50
Editorial	23	3	26
Total	70	6	76

Two topics for discussion at the joint session emerged during the ballot resolution process.

Discussion Topic #1

- EVB Controlling Bridge needs the following additions to a C-VLAN component:

Reflective relay (Qbg)

Ability to produce an M-Tag and perform additional filtering for multicast (Qbh)

- Are these optional capabilities for C-components or is this a new component?

Discussion Topic #2

- A C-VLAN bridge ignores S-Tags and Priority S-Tags
 - They pass through the bridge
 - A C-Tag may be pre-pended
 - Priority value in S-Tag is ignored
- It is desirable for an Extended Bridge (i.e. a bridge composed of Port Extenders and an EVB controlling bridge) to exhibit the same behavior
 - Would require a new behavior of S-Components (and M-Components) to accept and ignore an S-Tag
 - Seems like an odd thing to ask an S-Component to do
- Is it worth defining this new behavior for S-components, or should we just live with the fact that we get slightly different behaviors in this unusual case?