

Editor's Report 60802 Draft 1.2

**May 18, 2020
IEEE802 Virtual Interim Meeting**



Jordon Woods, Analog Devices

Progress to Date

- There were 2 major restructuring tasks:
 - Re-order the paragraphs – see comment 251
 - Modify conformance clause such that all cited 802.1 features reference the conformance clause of the specification in question – see comment 222
- These changes have been implemented.
- In addition, the missing contributions from what was clause 6, now clause 4, have been added
 - 4.1.2 Control Loop Applications
 - 4.1.3 Mechanisms that can be used to meet Control Loop Latency Requirements
- What remains is the task of going through each comment to ensure it is implemented. This task is 50% complete.

Revised Structure

CONTENTS

FOREWORD	5
INTRODUCTION	2
1 Scope	4
2 Normative references	4
3 Terms, definitions, symbols and abbreviated terms	4
3.1 List of terms and definitions given in IEC 61784-2, IEEE 802, IEEE 802.3-2018, IEEE 802.1Q-2018 and IEEE Std 802.1AS-2020	5
3.2 TSN-IA defined Terms	5
3.3 Abbreviated terms and acronyms	8
3.4 Conventions	8
3.4.1 Principles for (sub) clause selections of referenced documents	8
3.4.2 Convention for Capitalizations	8
3.4.3 Unit conventions	8
4 Overview of TSN in Industrial Automation	9
4.1.1 Control loop operation	9
4.1.2 Control Loop Applications	10
4.1.3 Mechanisms that can be used to meet Control Loop Latency Requirements	10
4.2 Industrial Traffic Types	11
5 Conformance	12
5.1 General	12
5.2 Requirements Terminology	12
5.3 Profile Conformance Statement (PCS)	12
5.4 Conformance Classes	12
5.5 Common requirements	13
5.5.1 Common PHY and MAC requirements	13
5.5.2 Common Network Discovery Requirements	13
5.5.3 Common requirements for synchronization	13
5.6 Common options	14
5.6.1 Common PHY and MAC options	14
5.6.2 Common Network Discovery Options	14
5.6.3 Common options for Synchronization	14
5.6.4 Common options for Security	15
5.7 Bridge requirements	15
5.7.1 Common Bridge requirements	15
5.7.2 ccA Bridge Requirements	16
5.7.3 ccB Bridge Requirements	16
5.8 Bridge Options	16
5.8.1 Common Bridge Options	16
5.8.2 ccA Bridge Options	17
5.8.3 ccB Bridge Options	17
5.9 End Station Requirements	17
5.9.1 Common End Station Requirements	17
5.9.2 ccA End Station Requirements	17
5.9.3 ccB End Station Requirements	17
5.10 End station Options	18

5.10.1 Common End Station Options	18
5.10.2 ccA End Station Options	18
5.10.3 ccB End Station Options	18
6 Required Functions for an Industrial Network	18
6.1 Synchronization	18
6.1.1 General	18
6.1.2 Grandmaster PTP Instance requirements	19
6.1.3 PTP End Instance requirements	19
6.1.4 Application Clock	19
6.1.5 Working Clock Domain	19
6.1.6 Global Time Domain	20
6.1.7 IA-device model for clocks	20
6.1.8 Error Model	20
6.1.9 gPTP Domains	22
6.1.10 Cold Standby Redundancy for Time Synchronization	23
6.1.11 Hot Standby Redundancy for Time Synchronization	23
6.2 Security Model	23
6.3 Bridge delay requirements	23
6.4 Network access	23
6.5 Bridge FDB requirements	23
6.6 Bridge resource requirements	23
6.7 Management	23
6.7.1 Engineering management model	24
6.7.2 Operation	25
6.7.3 Managed Objects	27
6.7.4 Protocols	27
Annex A PCS proforma – Time-sensitive networking profile for industrial automation	28
A.1 General	28
A.2 Abbreviations and special symbols	28
A.2.1 Status symbols	28
A.2.2 General abbreviations	28
A.3 Instructions for completing the PCS proforma	29
A.3.1 General structure of the PCS proforma	29
A.3.2 Additional information	29
A.3.3 Exception Information	29
A.3.4 Conditional status	29
A.4 Common requirements	30
A.4.1 Implementation identification	30
A.4.2 Profile summary, IEC/IEEE 60802	31
A.4.3 Implementation type	31
Annex B (informative) Representative TSN Domain	33
B.1 Case 1	33
Annex Z (informative) Gaps	34
Z.1 Hot standby redundancy for time synchronization	35
Z.1.1 Overview	35
Z.1.2 PTP Instance configuration	36
Z.1.3 60802_Instance state machine	36
Z.1.4 State machine global variables	36

Expected Contributions

- Committed for the next draft:
 - ✓ Traffic Types
 - ✓ features/options in conformance classes (quantities)
 - ✓ Management workflow
 - ✓ Clock State Definition
 - Qcc as it relates to management of stream translation
 - ccB timing model
 - Further explanation of TSN domains
- Committed on an unspecified timeline:
 - Managed Objects
 - Security Guidelines
 - Distribution configuration

Proposed Timeline

- May 18-29: Complete comment implementation.
- June 1-5: Add provided contributions.
- Monday, June 8:
 - Agree to proceed to TG Ballot (editor to provide an update on the call).
 - Provide draft to IEC editorial staff for review and conversion to pdf.
- Monday June 15: Open TG Ballot for d1.2.
- Monday July 6: Close TG Ballot for d1.2.
- Sunday July 12: Provide preliminary comment disposition
- Monday July 13: Begin comment resolution during the July IEEE802 Virtual Plenary.

Summary

- Progress on d1.2 is proceeding well but has slowed significantly since the last editor's report.
- The editor would like to make the next TG ballot a final precursor to WG ballot.
- It is the editor's desire to begin comment resolution during the July meeting.
- The proposed timeline is ambitious and requires timely submittal of contributions
- The editor will incorporate contributions directly into the draft to facilitate consensus building during the next ballot cycle.

Thank you