

```

+-----+
| IEEE 802.1 REVISION REQUEST 0155 |
+-----+

```

DATE: 11 January 2015  
NAME: Raphael Gartl  
COMPANY/AFFILIATION: RAD Data Communications Ltd.  
E-MAIL: raphael\_g@rad.com

REQUESTED REVISION:  
STANDARD: 802.1X-2010  
CLAUSE NUMBER: 13.5  
CLAUSE TITLE: Definitions for PAE MIB

RATIONALE FOR REVISION:

The description of ieee8021XAuthPaeReAuthEnabled says it should always return 'false'. This object is used to enable and disable periodic reauthentication, but if it is always 'false', how can a manager know if periodic reauthentication is enabled or disabled?

PROPOSED REVISION TEXT:

Omit the requirement to always return 'false':

```

ieee8021XAuthPaeReAuthEnabled OBJECT-TYPE
SYNTAX TruthValue
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"This object is set 'true' if PACP should initiate
reauthentication periodically, 'false' otherwise."
REFERENCE "IEEE 802.1X Clause 8.9, Figure 12-3"
 ::= { ieee8021XAuthenticatorEntry 4 }

```

IMPACT ON EXISTING NETWORKS:

```

+-----+
| Please attach supporting material, if any |
| Submit to:- Glenn Parsons, Chair IEEE 802.1 |
| and copy:- John Messenger, Vice-Chair IEEE 802.1 |
| E-Mail: stds-802-1-maint-req@ieee.org |
| |
| +----- For official 802.1 use -----+ |
| | REV REQ NUMBER: 0155 | |
| | DATE RECEIVED: 11 January 2015 | |
| | EDITORIAL/TECHNICAL | |
| | ACCEPTED/DENIED | |
| | BALLOT REQ'D YES/NO | |
| | Status: R | |
| +-----+ |
+-----+

```