

# Outline of the 802.16.1 Air Interface Standard

(Draft Date: 99/09/23)

(This draft was built by Roger Marks from outlines developed by the MAC and PHY Task Groups at 802.16 Session #3.)

## **1 Scope and Purpose**

### **1.1 Scope**

### **1.2 Requirements**

### **1.3 Background**

#### 1.3.1 Service Goals

#### 1.3.2 Reference Architecture

#### 1.3.3 Categories of Interface Specification

#### 1.3.4 Statement of compatibility

### **1.4 Definitions, Symbols & Abbreviation**

#### 1.1. Definitions

#### 1.2. Symbols & Abbreviations

## **2 Functional Assumptions**

### **2.1 Broadband Wireless Access (BWA) Network**

### **2.2 Equipment Assumptions**

#### 2.2.1 Frequency Plan

#### 2.2.2 Compatibility with Other Services

#### 2.2.3 Fault Isolation Impact on Other Users

#### 2.2.4 BWA System Terminal Devices

### **2.3 RF Channel Assumptions**

#### 2.3.1 Transmission Downstream

#### 2.3.2 Transmission Upstream

##### *2.3.2.1 Availability*

### **2.4 Transmission Levels**

### **2.5 Frequency Inversion**

## **3 Communication Protocols**

### **3.1 Protocol Stack**

### **3.2 The MAC Forwarder**

### **3.3 Network Layer**

### **3.4 Data Link Layer**

### **3.5 Physical Layer**

## **4 Physical Layer**

### **4.1 Scope**

### **4.2 Normative References**

### **4.3 PHY Overview**

#### 4.3.1 Introduction

#### 4.3.2 Reference Configuration

#### 4.3.3 Multiple Access

##### *4.3.3.1 Duplexing*

##### *4.3.3.2 Frames, Multiframe & Hyperframes*

##### *4.3.3.3 Time Slots & bursts*

- 4.3.3.4 *Logical Channels*
- 4.3.4 Coding, Interleaving & Scrambling
- 4.3.5 Modulation
- 4.3.6 RF Transmission & Reception
  - 4.3.6.1 *Band plan & Channelization*
- 4.3.7 Other PHY related functions
- 4.4 Multiple Access & Channel Multiplexing**
  - 4.4.1 Introduction
  - 4.4.2 Physical Resource
    - 4.4.2.1 *RF Channel*
    - 4.4.2.2 *Framing & Formatting*
  - 4.4.3 Logical Channels
    - 4.4.3.1 *Hierarchy*
    - 4.4.3.2 *Traffic Channels (TCHs)*
    - 4.4.3.3 *Control Channels (CCHs)*
  - 4.4.4 Types of Physical Channels
  - 4.4.5 Mapping of Logical Channels into Physical Channels
  - 4.4.6 PHY-MAC Interaction
    - 4.4.6.1 *Downstream*
    - 4.4.6.2 *Upstream*
- 4.5 Channel Coding**
  - 4.5.1 Introduction
  - 4.5.2 Downstream Coding Scheme
  - 4.5.3 Upstream Coding Scheme
- 4.6 Modulation**
  - 4.6.1 Introduction
  - 4.6.2 Downstream Modulation
    - 4.6.2.1 *Modulation Type(s)*
    - 4.6.2.2 *Modulation Rate(s)*
    - 4.6.2.3 *Modulation Symbol Definition & Mapping*
  - 4.6.3 Upstream Modulation
    - 4.6.3.1 *Modulation Type(s)*
    - 4.6.3.2 *Modulation Rate(s)*
    - 4.6.3.3 *Modulation Symbol Definition & Mapping*
- 4.7 RF Transmission & Reception**
  - 4.7.1 Frequency Bands & Channel Arrangement
    - 4.7.1.1 *LMDS Block A*
    - 4.7.1.2 *Others*
- 4.8 Radio Sub-system Control & Synchronization**
  - 4.8.1 Introduction

- 4.8.2 Timing & Synchronization
  - 4.8.2.1 *Base Station*
  - 4.8.2.2 *CPE*
- 4.8.3 Power Control
- 4.8.4 Radio Link Measurements
  - 4.8.4.1 *RSSI*
  - 4.8.4.2 *Signal Quality*
- 4.8.5 Additional PHY related Registration Functions
  - 4.8.5.1 *Ranging*
  - 4.8.5.2 *Power leveling*
- 4.8.6 PHY-MAC Service Access Points
  - 4.8.6.1 *Primitives*
  - 4.8.6.2 *Messages*
- 4.9 Minimum Performance**
  - 4.9.1 Reference Test Plans
  - 4.9.2 Propagation Models
  - 4.9.3 Transmitter Characteristics
    - 4.9.3.1 *FDD*
      - 4.9.3.1.1 *Downstream*
      - 4.9.3.1.2 *Upstream*
    - 4.9.3.2 *TDD*
      - 4.9.3.2.1 *Downstream*
      - 4.9.3.2.2 *Upstream*
  - 4.9.4 Receiver Characteristics
    - 4.9.4.1 *FDD*
      - 4.9.4.1.1 *Downstream*
      - 4.9.4.1.2 *Upstream*
    - 4.9.4.2 *TDD*
      - 4.9.4.2.1 *Downstream*
      - 4.9.4.2.2 *Upstream*
  - 4.9.5 Transmitter & Receiver Performance
    - 4.9.5.1 *Modulation Accuracy*
    - 4.9.5.2 *...*
- 5 Media Access Control Layer**
  - 5.1 MAC Reference Model**
  - 5.2 MAC Concept**
    - 5.2.1 Relationship Between Higher Layers and MAC Protocol
    - 5.2.2 Relationship Between Physical Layer and MAC Protocol
  - 5.3 Media Access Control Specification**
    - 5.3.1 Introduction
      - 5.3.1.1 *Overview*
      - 5.3.1.2 *Definitions*

- 5.3.1.3 *Future Use*
- 5.3.2 Access Modes
- 5.3.3 MAC Frame Format
- 5.3.4 MAC Messages
  - 5.3.4.1 *User*
  - 5.3.4.2 *Management*
- 5.3.5 MAC Error Handling Procedures
- 5.4 Network Entry**
  - 5.4.1 First Time Entry
    - 5.4.1.1 Scanning and Synchronization to Downstream
    - 5.4.1.2 Obtain Upstream Parameters
    - 5.4.1.3 Message Flows During Scanning and Upstream Parameter Acquisition
    - 5.4.1.4 Ranging and Automatic Adjustments
    - 5.4.1.5 *Initial Connection Establishment*
  - 5.4.2 Recurring Entry
    - 5.4.2.1 Scanning and Synchronization to Downstream
    - 5.4.2.2 Obtain Upstream Parameters
    - 5.4.2.3 Message Flows During Scanning and Upstream Parameter Acquisition
    - 5.4.2.4 Ranging and Automatic Adjustments
    - 5.4.2.5 *Initial Connection Establishment*
  - 5.4.3 Reinitialization
    - 5.4.3.1 Scanning and Synchronization to Downstream
    - 5.4.3.2 Obtain Upstream Parameters
    - 5.4.3.3 Message Flows During Scanning and Upstream Parameter Acquisition
    - 5.4.3.4 Ranging and Automatic Adjustments
    - 5.4.3.5 *Initial Connection Establishment*
- 5.5 Media Access Control Protocol Operation**
  - 5.5.1 Connection Establishment
  - 5.5.2 Connection Release
  - 5.5.3 MAC Link Management
    - 5.5.3.1 *Power and Timing Management*
    - 5.5.3.2 *Bandwidth Allocation Management*
    - 5.5.3.3 *Channel Error Management*
    - 5.5.3.4 *Link Management Messages*