1

Project	**IEEE 802.16 Broadband Wireless Access Working Group** <http://ieee802.org/16>
Title	802.16n Table of Contents for Amendment Working Draft
Date Submitted	2011-03-25
Source(s)	Tim Godfrey tim.godfrey@ieee.org Chair, GRIDMAN TG EPRI
Re:	
Abstract	This document captures functional requirements of the 802.16n amendment, including the System Architecture Reference Model
Purpose	To serve as a basis for further development by GRIDMAN SG
Notice	*This document does not represent the agreed views of the IEEE 802.16 Working Group or any of its subgroups*. It represents only the views of the participants listed in the "Source(s)" field above. It is offered as a basis for discussion. It is not binding on the contributor(s), who reserve(s) the right to add, amend or withdraw material contained herein.
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.
Patent Policy	The contributor is familiar with the IEEE-SA Patent Policy and Procedures: <http://standards.ieee.org/guides/bylaws/sect6-7.html#6> and <http://standards.ieee.org/guides/opman/sect6.html#6.3>. Further information is located at <http://standards.ieee.org/board/pat/pat-material.html> and <http://standards.ieee.org/board/pat>.

2
3
4
5
6
7
8
9
10

802.16n Table of Contents for Amendment Working Draft

1. Overview
1.1 Scope
1.2 Purpose
2. Normative references
3. Definitions
4. Abbreviations and acronyms
5. Service Specific CS
6. MAC common part sublayer
7. Security sublayer
8. Physical layer (PHY)
10. Parameters and constants
11. TLV encodings
16. WirelessMAN-Advanced Air Interface
16.1 Introduction
16.2 Medium access control
16.2.1 Addressing
16.2.1.3 Addressing to support machine to machine application
16.2.2 MAC PDU formats
16.2.3 MAC Control messages
16.2.4 Construction and Transmission of MAC PDUs
16.2.5 AAI Security
16.2.5.5 Security mechanisms for machine to machine application
16.2.6 MAC HO procedures
16.2.7 Persistent Scheduling in the Advanced Air Interface
16.2.8 Multicarrier operation
16.2.9 Group Resource Allocation
16.2.10 Connection Management
16.2.11 Bandwidth Request and Allocation Mechanism
16.2.12 Quality of Service (QoS)
16.2.13 ARQ mechanism
16.2.14 HARQ functions
16.2.15 Network entry and initialization
16.2.15.7 Network entry and initialization for machine to machine operation
16.2.16 Periodic ranging

16.2.17 Sleep mode
16.2.18 Idle mode
16.2.19 Deregistration with context retention (DCR) mode
16.2.20 Co-located coexistence (CLC)
16.2.21 Interference mitigation mechanism
16.2.22 MAC control reliability
16.2.23 Power management for active mode
16.2.24 Update of S-SFH IEs
16.2.25 Short Message Service
16.2.25.1 Small burst transmission for machine to machine application
16.2.26 Coverage Loss Detection and Recovery from Coverage Loss
16.2.27 AMS deregistration
16.2.28 Support for Multicast Service
16.2.28.4 Multicast operation for machine to machine application
16.2.29 MAC Support for M2M Application
16.2.29.1 Introduction
16.2.29.2 Addressing
16.2.29.3 Security
16.2.29.4 Network (Re-)entry
16.2.29.5 Idle Mode
16.2.29.6 Support of Multicast Service
16.2.29.7 Support of M2M short packet transmission
16.2.29.8 Group Resource Allocation
16.2.29.9 Device Collaboration
16.3 Physical layer
16.3.11 Global Values
16.4 Support for Femto ABS
16.4.1 General description
16.4.2 Femto base station subscription types
16.4.3 Femto ABS state diagram
16.4.4 PHY and MAC level identifier
16.4.4.1 PHY level cell identifier
16.4.4.2 CSG white list
16.4.5 Femto ABS initialization and de-attachment
16.4.6 Network synchronization
16.4.7 Network entry
16.4.8 Handover (HO)
16.4.9 Idle mode
16.4.10 Low-duty operation mode

16.4.11 Interference avoidance and interference mitigation
16.4.12 Power control
16.4.13 Femto ABS reliability
16.5 Multi-BS MIMO
16.6 Support for Relay
16.6.1 Relay Modes and General Description
16.6.2 Medium access control
16.6.2.1 Addressing
16.6.2.2 MAC PDU Formats
16.6.2.3 Construction and Transmission of MPDUs
16.6.2.4 Security
16.6.2.5 Handover
16.6.2.6 Scheduling and QoS
16.6.2.7 Bandwidth Request and Grant Management
16.6.2.8 ARQ
16.6.2.9 HARQ
16.6.2.10 Network Entry
16.6.2.11 Ranging
16.6.2.12 Sleep Mode
16.6.2.13 Idle Mode
16.6.2.14 ARS Configuration
16.6.2.15 ARS De-registration
16.6.2.16 Update of SFH
16.6.3 Physical Layer for TTR relay mode
16.6.3.1 Basic frame structure supporting ARS
16.6.3.2 Frame structure
16.6.3.3 Relay Downlink PHY Structure
16.6.3.4 Downlink Control Structure
16.6.3.5 Relay Uplink physical structure
16.6.3.6 Uplink Control Structure
16.6.4 Physical Layer for STR relay mode
16.7 Support for Self-organization
16.8 Support for Location Based Services (LBS)
16.9 Support for Enhanced Multicast Broadcast Service
16.10 Support for Advanced Air Interface in LZone
16.10.11 Global Values
17. WirelessMAN-High Reliability Network
17.1 Overview
17.1.1 Operating frequencies

17.1.2 Operating bandwidths
17.1.3 Duplex
17.1.4 Backward compatibility
17.2 WirelessMAN HR-OFDMA air interface
17.2.1 Multi-mode operation
17.2.2 Direct communication between HR-MSs
17.2.3 HR-MS Forwarding to network
17.2.4 Standalone network
17.2.5 Relaying operation
17.2.6 Local Forwarding
17.2.7 Path Discovery and Management
17.2.8 Priority Access Operation
17.2.9 Multicast support
17.2.10 Security
17.3 WirelessMAN HR Advanced air interface
17.3.1 Multi-mode operation
17.3.2 Direct communication between HR-MSs
17.3.3 HR-MS Forwarding to network
17.3.4 Standalone network
17.3.5 Relaying operation
17.3.6 Local Forwarding
17.3.7 Path Discovery and Management
17.3.8 Priority Access Operation
17.3.9 Multicast support
17.3.10 Security