

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >
Title	H-ARQ system parameters
Date Submitted	2004-08-19
Source(s)	Panyuh Joo, Seungjoo Maeng, Jaeho Jeon, Soonyoung Yoon, Jeong-Heon Kim, Jaehyok Lee, Myungkwang Byun, Inseok Hwang, Jaehee Cho, Jiho Jang, Sanghoon Sung, Hoon Huh, jaehee1.cho@samsung.com Samsung Electronics Co. Ltd.
Re:	IEEE P802.16-2004
Abstract	System parameters for H-ARQ is defined.
Purpose	Adopt changes
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < http://ieee802.org/16/ipr/patents/policy.html >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < mailto:chair@wirelessman.org > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < http://ieee802.org/16/ipr/patents/notices >.

H-ARQ system parameters

1. Motivation

For the H-ARQ operation, the number of maximum retransmission shall be defined for BS and MS. It shall be broadcast to MSs from BS. The DCD and UCD is good place for the parameters.

The number of usable ACID impacts on the memory size of decoders. MSs with limited capability shall negotiate the maximum number of usable ACIDs. Because it is MS specific, basic capability negotiation shall perform the function.

2. Details

3. Changes summary

[Add new UCD TLV of table 351 at line 52 page 659 in 11.3.1]

Name	Type(1 byte)	Length	Value
Maximum retransmission	173	1	Maximum number of retransmission in UL HARQ

[Add new DCD TLV of table 356 at line 20 page 665 in 11.4.1]

Name	Type(1 byte)	Length	Value
Maximum retransmission	173	1	Maximum number of retransmission in DL HARQ

[Add the following subclause at line 40 page 687 at the end of 11.8.3.7.5]

Type(1 byte)	Length	Value	Scope
155	1	Number of ACIDs that MSS can support.	SBC-REQ (see 6.3.2.3.23) SBC-RSP (see 6.3.2.3.24)