

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	Correction to PRBS	
Date Submitted	2005-04-21	
Source(s)	Eyal Bick Yuval Lomnitz Uri Perlmutter Dov Andelman Intel Corp.	Eyal.Bick@intel.com Yuval.Lomnitz@intel.com
Re:	IEEE P802.16-2004/Cor1- D1 D2	
Abstract	The PRBS is correlated over time between cells. We suggest to correct it.	
Purpose	Adopt changes	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < http://ieee802.org/16/ipr/patents/policy.html >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < mailto:chair@wirelessman.org > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < http://ieee802.org/16/ipr/patents/notices >.	

Correction to PRBS

*Eyal Bick, Yuval Lomnitz, Uri Perlmutter
Dov Andelman*

1. Motivation

The PRBS function should take care of sub-carriers randomization over frequency, time and between different cells. Good randomization of pilots is essential for good channel estimation in the presence of interference from other BS. With the current PRBS seed, the PRBS sequences of two BSs will be correlated over time and therefore although it is IDCELL dependant it doesn't supply separation between cells. We suggest a way to de-correlate the PRBS sequences of different cells.

[Differences from C80216maint-05/067 to 067r1:](#)

- [1. Text changes to reflect changes done in Cor1/D2](#)
- [2. Replace UL_permbase with IDCELL, since UL_permbase is not guaranteed to be different between cells.](#)

2. Details

There is a problem with the sub-carrier randomization (PRBS sequence) defined in 8.4.9.4.1.

2.1. Desired Situation

One of the important features of this sequence is to randomize the pilots in frequency and in time domain, and between cells.

When estimating the channel (in UL or in DL), in order to obtain reasonable channel estimation gain (=SNR of channel estimation / SNR of pilots), one may (or must) average on time domain, since there is not enough gain in frequency domain (depending on delay spread assumptions). This is especially important in scenario of interference, since the pilot boosting gain vanishes (pilots in other cell also boosted), and because of low SNR conditions at edge of cell, high channel estimation gain is needed, which necessitates de-spreading gain in both time and frequency.

We would expect that the PRBS will be uncorrelated between cells in frequency and in time. The important thing is how the (transmitted) PRBS sequence of cell x is seen after being de-rotated by the PRBS of cell y (in the receiver), i.e. the XOR between the two binary sequences.

2.2. Problem

The PRBS is a sequence generated by an LFSR whose seed is $\text{seed} = (\text{IDCELL} \mid \text{segment} \mid \text{symbol number})$. "|" indicates concatenation. An LFSR sequence is linear w.r.t. to its seed, which means that the XOR of two LFSR sequences is the LFSR sequence generated by the XOR of their seeds. So when xoring the PRBS-s of two cells, the symbol numbers in the seeds of cells x,y will cancel out, and what we'll end up is with a sequence which depends only on the XOR of the IDCELLs (and segment numbers).

As a results, the pilot on sub-carrier n from cell x and the same pilot n from cell y will have a constant relation (1 or -1), over all the OFDMA symbols (although each sub-carrier n will change from symbol to symbol).

The result of this is that there is no de-spreading gain in time domain. The major impact is on the pilots. The impact on the data is smaller (but there are some "bad" scenarios like repetition applied on a narrow allocation, in which all repetitions will have same phase across cells).

2.3. Solution

PRBS will be rotated $n=(\text{symbol offset})\%32$ times (i.e. the first N outputs will be thrown), and only the next output will be mapped to the first sub-carrier.

3. Changes summary

[Change lines ~~3-1035-42~~ at p.~~114-144~~ as follows]

~~b3..b0 = 1111 (all ones) In the downlink, Four least significant bits of symbol offset from the first data preamble~~

~~symbol in the frame (i.e., the symbol in the frame in which the DL-MAP starts first PUSC symbol after the preamble is indexed 1). In the uplink set to the result of XOR (bit wise) operation between the four LSBs of symbol offset from the first data preamble symbol in the frame (i.e. the symbol in the frame in which the DL-MAP starts first PUSC symbol after the preamble is indexed 1) and the four least significant bits of the Frame Number.~~

[Change lines 12-15 at p.~~114-144~~ 8.4.9.4.1]

Change the second sentence of the last paragraph as indicated:

~~The PRBS shall be initialized so that its first output bit coincides with the first usable subcarrier. The PRBS shall be initialized so that its first output bit coincides with the first usable subcarrier (as defined in Table 313) as defined for the zone in which the symbol resides.~~

The PRBS shall be rotated n times, $n=\text{Symbol_Offset}\%32$, before applying it to the subcarriers, where symbol offset is counted from the preamble in the downlink (i.e. the first symbol carrying the DL_MAP is indexed 1) and from Allocation start time in the uplink (i.e. the first symbol is indexed 0). As a result, the PRBS shall be used such that its n'th output bit will coincide with the first usable subcarrier (as defined for the zone in which the symbol resides). Subcarriers belonging to UL allocations with UIUC=12 or UIUC=13 shall not be randomized.

[Change text in line 29 at p.144 8.4.9.4.1]

~~From: as defined for the zone in which the symbol resides (E.g: if n=0 take the first output bit, if n=1 take the second bit, etc):~~

Five least significant bits of ~~UL_IDcell~~PermBase in the uplink

To: Five least significant bits of IDcell (as determined by the preamble) in the uplink