Project	IEEE 802.16 Broadband Wireless Access Working Group < <u>http://ieee802.org/16</u> >	
Title	Clarification of renumbering and permutation based on DL_PermBase parameter	
Date Submitted	2005-05-02	
Source(s)	Sean Cai Jason Hou Liujun Hu	scai@ztesandiego.com jhou@ztesandiego.com
	ZTE San Diego Inc. 10105 Pacific Heights Blvd. San Diego, CA 92121 USA	Voice: 858-554-0387 Fax: 858-554-0894
	Lei Wang Cygnus Multimedia Communications, Inc.	Voice (760)448-1984 Fax: (760)448-1989
Re:	Email: lwang@cygnuscom.com IEEE 802.16 WG Recirculation Ballot #17a on P802.16-2004/Cor1/D2	
Abstract	This contribution is for clarification of renumbering and permutation based on DL_PermBase parameter	
Purpose	To incorporate the text modification proposed in this contribution into P802.16-2004/Cor1/D3.	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures <http: 16="" ieee802.org="" ipr="" patents="" policy.html="">, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair <mailto:chair@wirelessman.org> as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site <http: 16="" ieee802.org="" ipr="" notices="" patents="">.</http:></mailto:chair@wirelessman.org></http:>	

Clarification of renumbering and permutation based on **DL** PermBase parameter

Sean Cai, Jason Hou, Liujun Hu ZTE San Diego Inc.

Lei Wang Cygnus Multimedia Communications, Inc.

Problem Statement 1.

In section 8.4.6.1.2.1.1 of P80216 Corl D2, the text of downlink subchannel subcarrier allocation in PUSC mentions that DL PermBase is used both for renumbering and permutation formulas. However, one of them states that DL PermBase = 0 in the first zone, the other says DL PermBase = IDcell in the first zone.

2. **Proposed solutions**

The forcing of DL PermBase = 0 ensures that the first zone of PUSC, all the different sectors from different cells are orthogonal. However, IDcell shall be used in the subcarrier permutation equation to have different permutations in the first zone for different cells, where the IDcell values can be chosen differently.

Specific text changes 3.

[Modify the following text to section 8.4.6.1.2.1.1 Downlink subchannels subcarrier allocation in PUSC]

=== Start text changes ====

1)

2) Renumbering the physical clusters into logical clusters using the following formula:

 $LogicalCluster = \begin{cases} RenumberingSequence(PhysicalCluster) & First DL Z \\ RenumberingSequence((PhysicalCluster + 13 * DL_PermBase) mod 120) & Otherwise \end{cases}$ First DL Zone

In the first PUSC zone of the downlink (first downlink zone), the default used IDcell is 0 renumbering sequence is used for logical cluster definition. For all other zones DL_PermBase parameter in the STC_DL_Zone_IE() shall be used.

3)

.... subcarriers in each symbol. Note that IDcell used for the first PUSC zone is 0.- is used for the first PUSC zone in 4) Equation (111). Otherwise the DL PermBase parameter in the STC DL Zone IE() shall be used in the equation.


[Modify the following text to section 8.4.6.1.2.2.2 Partitioning of data subcarriers into subchannels in downlink FUSC]

Replace Equation (111) with the following equation:

subcarrier(k, s) = $\begin{cases} N_{\text{subchannels}} n_k + \{p_s [n_k \mod N_{\text{subchannels}}] + IDcell\} \mod N_{\text{subchannels}} \\ N_{\text{subchannels}} n_k + \{p_s [n_k \mod N_{\text{subchannels}}] + DL_PermBase\} \mod N_{\text{subchannels}} \end{cases}$ First DL Zone Otherwise

Replace Figure 219 with the following figure:

[The DL PermBase = 0 in the first zone which includes FCH and DL MAP. It's better to indicate that IDcell = X in the figure after Preamble.]



=== End text changes ====

4. References

[1] [2] IEEE 802.16-2004

P80216_Cor1_D2