

| | | |
|------------------------------|---|--|
| Project | IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 > | |
| Title | Corrections about ARQ Block Size | |
| Date Submitted | 2006-09-26 | |
| Source(s) | Jaehong Chon Samsung Electronics | Voice: +82-31-279-3371 Fax: +82-31-279-2724 mailto: jhchon@samsung.com |
| Re: | IEEE802.16e-2005 | |
| Abstract | Corrections about ARQ Block Size | |
| Purpose | Adopt proposed changes | |
| Notice | This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein. | |
| Release | The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16. | |
| Patent Policy and Procedures | The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < http://ieee802.org/16/ipr/patents/policy.html >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < mailto:chair@wirelessman.org > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < http://ieee802.org/16/ipr/patents/notices >. | |

Corrections about ARQ Block Size

*Jaehong Chon**, *Geunhwi Lim**, *JaeJeong Shim**, *Joseph Schumacher***, *Tricci So****,
*Giovanni Maggi*****, *Erik Colban******, *Anuj Puri******, *Peretz Shekalim******, *Anders Lamm******
*Samsung Electronics**, *Motorola***, *Nortel****, *Siemens*****,
*NextWave******, *Beceem******, *Runcom******, *Ericsson******

Motivation

In IEEE Std 802.16-2004 and 802.16e-2005, we cannot use exact ARQ block size. In case higher throughput is needed, larger ARQ block size is necessary because the transmission may be limited by ARQ window size. So, the requester wants to use larger ARQ block size. For doing that, what the requester is only to do is to set the largest ARQ block size which the request can support in DSA-REQ message, but, the receiver may select smaller value than the desired size used by the requester. Therefore, current specification cannot guarantee to use proper ARQ block size.

Proposed Text Changes

[Change the text in 11.13.18.8 on page 739 of IEEE802.16e-2005]

11.13.18.8 ARQ_BLOCK_SIZE

This value of this parameter specifies the size of an ARQ block. This parameter shall be established by negotiation during the connection creation dialog.

~~The requester includes its desired setting in the REQ message. The receiver of the REQ message shall take the smaller of the value it prefers and value in the REQ message. This minimum value is included in the RSP message and becomes the agreed upon length value.~~
The requester includes its desired minimum and maximum setting in the DSA-REQ/REG-REQ message. The receiver of the DSA-REQ/REG-REQ message shall select the value it prefers within the range of the two values, inclusive, in the DSA-REQ/REG-REQ message. This selected value is included in selected block size of the DSA-RSP/REG-RSP message.

Absence of the parameter during a DSA dialog shall indicate the originator of the message desires the maximum value.

| Type | Length | Value | Scope |
|----------------------|--------|---|--|
| [145/146].26 1.26 | 2 | 0-15: Reserved 16, 32, 64, 128, 256, 512, or 1024: Desired/Agreed size in bytes 2041-65535: Reserved <u>For DSA-REQ and REG-REQ: Bit 0-3: encoding for proposed minimum block size (M) Bit 4-7: encoding for proposed maximum block size (N) where: The minimum block size is equal to $2^{(M+4)}$ and, the maximum block size is equal to $2^{(N+4)}$, $M \leq 6$, $N \leq 6$ and $M \leq N$</u> <u>For DSA-RSP and REG-RSP: Bit 0-3: encoding for selected block size (P) Bit 4-7: set to 0 where: The block size is equal to $2^{(P+4)}$, $P \leq 6$ and $M \leq P \leq N$</u> | DSA-REQ, DSA-RSP REG-REQ, REG-RSP |