

---

|                              |   |  |
|------------------------------|---|--|
| Project                      | <b>IEEE 802.16 Broadband Wireless Access Working Group</b> < <a href="http://ieee802.org/16">http://ieee802.org/16</a> >  |  |
| Title                        | <b>Proposal for adding Conditional Event Mask for wmanDevCmnEventLogTable</b>   |  |
| Date Submitted               | <b>2005-07-12</b>   |  |
| Source(s)                    | Zou Lan, Li Li<br>Huawei Technologies.<br>No.98,Lane91, Eshan Road, Pudong ,<br>Shanghai, China<br>Pudong Lujiazui Software Park  | Voice: +86-21-68644808-24657<br>Fax: +86-21-50898375<br>Mailto: <a href="mailto:zlan@huawei.com">zlan@huawei.com</a> |
| Re:                          | Contribution on IEEE 802.16f/D5   |  |
| Abstract                     | This contribution proposed a method to add conditional event mask feature in event reporting function. With this new feature, network manager can control on what kind of event will be reported from BS and SS. By decreasing useless event flood during special scenarios and make network manager draw their attention more on important events handling.  |  |
| Purpose                      | Adoption  |  |
| Notice                       | This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.  |  |
| Release                      | The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.  |  |
| Patent Policy and Procedures | The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < <a href="http://ieee802.org/16/ipr/patents/policy.html">http://ieee802.org/16/ipr/patents/policy.html</a> >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < <a href="mailto:chair@wirelessman.org">mailto:chair@wirelessman.org</a> > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < <a href="http://ieee802.org/16/ipr/patents/notices">http://ieee802.org/16/ipr/patents/notices</a> >. |  |

---

## Proposal for Adding Conditional Event Mask for wmanDevCmnEventLogTable

Zou Lan, Li Li  
HUAWEI

### Introduction

In IEEE802.16f, there are BS and SS trap control definitions which can enable/disable BS and SS event reporting. But current definition of BS and SS trap can be only controlled based on network element level and according to event identifier.

Usually operator may like to disable events notification according to specific object or disable events during some special time periods. It is useful when operators make some operations on specific objects like change spare parts etc. These kinds of operations will generate events but operator doesn't want to take care of them.

This contribution proposes to use conditional event mask to suppress the event reporting action during special scenarios. Several conditions are considered as conditional event mask, which includes object instance and time segment.

To fulfill this goal, object instance description field are required to be added in wmanDevCmnEventLogTable which can provide more accurate object instance information.

### Proposed Text Changes

1. [Change the text in section **13.2.3.1.3 wmanDevCmnEventLogTable** as the following]

1.1 Add object instance description in **13.2.3.1.3 wmanDevCmnEventLogTable**, keep the previous definition intact.

#### **13.2.3.1.3 wmanDevCmnEventLogTable**

wmanDevCmnEventLogTable is used to store local events, and should reside in the non-volatile memory.

The Event Log consists of the following features:

- Each event has its corresponding object instance description.

ASN.1 Definitions:

wmanDevCmnEventLogObjectInstance OBJECT-TYPE

SYNTAX SnmpAdminString

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This object describes the event related object instance information."

::= { wmanDevCmnEventLogEntry 6 }

1.2 Add Node wmanDevBsEventConditionMaskTable to wmanDevBsTrapControl , keep the previous structure

ASN.1 Definitions:

wmanDevBsEventConditionMaskTable OBJECT-TYPE  
SYNTAX SEQUENCE OF WmanDevBsEventConditionMaskEntry  
MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION  
"This table contains event conditions which are used to disable/enable Base Station event traps."  
 ::= { wmanDevBsTrapControl 2 }

wmanDevBsEventConditionMaskEntry OBJECT-TYPE  
SYNTAX WmanDevBsEventConditionMaskEntry  
MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION  
" wmanDevBsEventConditionMaskEntry is indexed by  
wmanDevBsEventConditionMaskIndex."  
 INDEX { wmanDevBsEventConditionMaskIndex }  
 ::= { wmanDevBsEventConditionMaskTable 1 }

wmanDevBsEventConditionMaskIndex OBJECT-TYPE  
SYNTAX Integer32  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
" An index identifies the BS event condition mask."  
 ::= { wmanDevBsEventConditionMaskEntry 1 }

wmanDevBsMaskStartTime OBJECT-TYPE  
SYNTAX TimeStamp  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
"Start time for event condition mask."  
 ::= { wmanDevBsEventConditionMaskEntry 2 }

wmanDevBsMaskEndTime OBJECT-TYPE  
SYNTAX TimeStamp  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
"End time for event condition mask."  
 ::= { wmanDevBsEventConditionMaskEntry 3 }

wmanDevBsMaskObjectDescription OBJECT-TYPE  
SYNTAX SnmpAdminString  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
"Object instance for event condition mask."  
 ::= { wmanDevBsEventConditionMaskEntry 4 }

1.3 Modify “wmanDevBsEventTrap” notification parameter, add “wmanDevCmnEventLogObjectInstance”.

ASN.1 Definition:

wmanDevBsEventTrap NOTIFICATION-TYPE

OBJECTS { wmanDevCmnEventId, wmanDevCmnEventLogIndex,  
wmanDevCmnEventLogObjectInstance, wmanDevCmnEventLoggedTime, wmanDevCmnEventDescription,  
wmanDevCmnEventSeverity }

STATUS current

DESCRIPTION

"This trap is sent when an event is logged into the table

wmanDevCmnEventLogTable."

::= { wmanDevBsTrapPrefix 1 }

1.4 Add Node wmanDevSsEventConditionMaskTable to wmanDevSsTrapControl , keep the previous structure intact.

ASN.1 Definitions:

wmanDevSsEventConditionMaskTable OBJECT-TYPE

SYNTAX SEQUENCE OF WmanDevSsEventConditionMaskEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table contains event conditions which are used to disable/enable Subscriber Station event traps."

::= { wmanDevSsTrapControl 2 }

wmanDevSsEventConditionMaskEntry OBJECT-TYPE

SYNTAX WmanDevSsEventConditionMaskEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"wmanDevSsEventConditionMaskEntry is indexed by wmanDevSsEventConditionMaskIndex."

INDEX { wmanDevSsEventConditionMaskIndex }

::= { wmanDevSsEventConditionMaskTable 1 }

wmanDevSsEventConditionMaskIndex OBJECT-TYPE

SYNTAX Integer32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"An index identifies the SS event condition mask."

::= { wmanDevSsEventConditionMaskEntry 1 }

wmanDevSsMaskStartTime OBJECT-TYPE

SYNTAX TimeStamp

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Start time for event condition mask."

::= { wmanDevSsEventConditionMaskEntry 2 }

wmanDevSsMaskEndTime OBJECT-TYPE

SYNTAX TimeStamp

2005-07-12  
05/007

IEEE C802.16f-

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"End time for event condition mask."

::= { wmanDevSsEventConditionMaskEntry 3 }

wmanDevSsMaskObjectDescription OBJECT-TYPE

SYNTAX SnmpAdminString

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Object instance for event condition mask."

::= { wmanDevSsEventConditionMaskEntry 4 }