
| | | |
|------------------------------|---|--|
| Project | IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 > | |
| Title | Management of Handover Context for Connections | |
| Date Submitted | 2005-07-11 | |
| Source(s) | Jaesun Cha and Chulsik Yoon | jscha@etri.re.kr |
| | ETRI | csyoon@etri.re.kr |
| | 161, Gajeong-dong, Yuseong-Gu, | |
| | Daejeon, 305-350, Korea | |
| Re: | Contribution on comments to IEEE 802.16g-04/03r3 | |
| Abstract | In this contribution, we propose to define and manage handover context for connections. | |
| Purpose | Adoption | |
| Notice | This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein. | |
| Release | The contributor grants a free, irrevocable license to the IEEE to incorporate text contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16. | |
| Patent Policy and Procedures | <p>The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures (Version 1.0) <http://ieee802.org/16/ipr/patents/policy.html>, including the statement "IEEE standards may include the known use of patent(s), including patent applications, if there is technical justification in the opinion of the standards-developing committee and provided the IEEE receives assurance from the patent holder that it will license applicants under reasonable terms and conditions for the purpose of implementing the standard."</p> <p>Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair <mailto:r.b.marks@ieee.org> as early as possible, in written or electronic form, of any patents (granted or under application) that may cover technology that is under consideration by or has been approved by IEEE 802.16. The Chair will disclose this notification via the IEEE 802.16 web site <http://ieee802.org/16/ipr/patents/notices>.</p> | |

Management of Handover Context for Connections

Jaesun Cha and Chulsik Yoon

ETRI

1. Introduction

During HO, serving BS shall inform some information of target BS to restore the connections at the target BS. Intuitively, only service flow information which are used to setup transport connections at the serving BS seems to be needed for re-establishment of transport connections at the target BS, but other information such as security information and MS capability information may be needed to continue the traffic service at the target BS because those information might be re-used at the target BS after HO. Therefore, the following information can be included in the HO context for connections.

- General MS Information: IP Address, MAC address, etc.
- MS Capability Information: ARQ support, Authorization Policy, etc.
- Security Information: AK, GKEK, TEK, etc.
- Service Flow Information: CID, SFID, Service Flow parameters, CS-specific parameters, etc.
- MAC State Information: ARQ timers, ARQ BSN counters, MAC SDU SN, etc.

Although the serving BS shall provide the mobility management entity in NCMS with all of the above information using HO primitives, the mobility management entity may provide the target BS with some of them according to the supported HO type and HO Optimization level. For example, if the target BS supports different authorization policy from the serving BS, then SBC-REQ/RSP and PKM procedure may not be omitted during network re-entry procedure. It means that MS capability information and security information don't need to be shared between the serving BS and the target BS during HO. Therefore, the mobility management entity in NCMS shall decide the sharing levels and inform the proper HO context of the target BS for re-establishment of the transport connections whenever HO occurs.

In the following table, we define 4 sharing levels according to HO type and HO optimization levels supported by MAC layer, and we also arrange the specific items of HO context which shall be shared according to the sharing levels.

| Sharing Level | General MS Information | MS Capability Information | Security Information | Service Flow Information | MAC State Information |
|-------------------------------|------------------------|---------------------------|----------------------|--------------------------|-----------------------|
| No Sharing | O | X | X | O | X |
| MS Capability Sharing | O | O | X | O | X |
| Security Optimization Sharing | O | O | O | O | X |
| Full Sharing | O | O | O | O | O |

**'O' means that the information item shall be shared and 'X' means that the information item doesn't need to be shared.*

2. Proposed Text Changes

[Modify section 14.5.9.1.1 as follow]

14.5.9.1.1 Handover Context for Connections

Handover context for connections is the set of information which is shared between the serving BS and the target BS for re-establishment of the transport connections during HO. HO context is consisted of the following information.

General MS Information

It is the information required to identify the MS. IP address and MAC address of the MS can be included in this information.

MS Capability Information

It is the information about MS capabilities which need to be negotiated with the serving BS through SBC-REQ/RSP handshake at the initial network entry.

Security Information

It is the information negotiated during PKM procedure. If the MS and the target BS can derive the AK for them without the help of the serving BS, AK key may be excluded from this information.

Service Flow Information

It is the information negotiated during DSx-related procedure.

MAC state Information

It is the information used to maintain MAC state machine and to manage MAC PDU transmission.

For the re-establishment of connections at target BS during HO, serving BS shall provide target BS with the HO context through the mobility management entity in NCMS using HO primitives. If the target BS can not re-use some information in the HO context for restoring the former MAC state or re-establishing connections, the mobility management entity in NCMS may exclude the information from the shared HO context.