

Project	<b>IEEE 802.16 Broadband Wireless Access Working Group</b> < <a href="http://ieee802.org/16">http://ieee802.org/16</a> >	
Title	<b>MAC PDU Concatenation in RS</b>	
Date Submitted	<b>2007-01-08</b>	
Source(s)	Yuefeng Zhou Mike Hart Sunil Vadgama  Fujitsu Laboratories of Europe Ltd  Hayes Park Central, Hayes End Road, Hayes, Middlesex, UB4 8FE, UK  Hongyun Qu  ZTE. Communications Shenzhen. Guangdong. China  Sean Cai ZTE San Diego Inc. 10105 Pacific Heights Blvd. San Diego, CA 92121. USA.  Jeffrey Z. Tao, Koon Hoo Teo, Jinyun Zhang Mitsubishi Electric Research Lab 201 Broadway Cambridge, MA 02139 USA  Toshiyuki Kuze Mitsubishi Electric Corp 5-1-1 Ofuna Kamakura, Kanagawa 2478501, Japan  Yong Sun, Dharma Bageet, Zhong Fan, Paul Strauch Toshiba Research Europe Ltd., Telecommunications Research Laboratory 32 Queen Square, Bristol BS1 4ND, UK	Voice: +44 (0) 20 8573 4444 FAX: +44 (0) 20 8606 4539  yuefeng.zhou@uk.fujitsu.com mike.hart@uk.fujitsu.com sunil.vadgama@uk.fujitsu.com  Voice : +86-755-26776604 <a href="mailto:qu.hongyun@zte.com.cn">qu.hongyun@zte.com.cn</a>  Voice: 858-554-0387 Fax: 858-554-0894 <a href="mailto:scai@ztesandiego.com">scai@ztesandiego.com</a>  Voice: 617-621-{7557,7527} Fax: 617-621-7550 {tao, teo, jzhang}@merl.com  Voice: +81-467-41-2885 Fax: +81-467-41-2486 <a href="mailto:Kuze.Toshiyuki@ah.MitsubishiElectric.co.jp">Kuze.Toshiyuki@ah.MitsubishiElectric.co.jp</a>  Sun@toshiba-trel.com Dharma.Bageet@toshiba-trel.com Zhong.fan@toshiba-trel.com Paul.Strauch@toshiba-trel.com
Re:	IEEE 802.16j-06/034: "Call for Technical Proposals regarding IEEE Project P802.16j"	

---

Abstract	In MR networks, By classifying and combining the MAC PDUs in RS, the PHY and MAC overhead can be decreased.
Purpose	Discuss and adopt proposed text and message format.
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < <a href="http://ieee802.org/16/ipr/patents/policy.html">http://ieee802.org/16/ipr/patents/policy.html</a> >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < <a href="mailto:chair@wirelessman.org">mailto:chair@wirelessman.org</a> > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < <a href="http://ieee802.org/16/ipr/patents/notices">http://ieee802.org/16/ipr/patents/notices</a> >.

---

## MAC PDU Concatenation in RS

*[This contribution propose a harmonization text proposal on MAC PDU Concatenation.]*

### 1. Problem Statement

The MAC PDU concatenation method in 16e (6.3.3.2) can still be used for MR systems. However, some clarifications are needed for MR network.

In MR networks, downlink MAC PDUs for transmission to an RS, including MAC PDUs for transmission to an SS via an RS, and downlink MAC PDUs for transmission to an SS shall not be concatenated into the same burst.

### 3. Specific Text Change

*[Insert a new paragraph after the first paragraph of the subclause 6.3.3.2 as indicated:]*

#### 6.3.2.2 Concatenation

Multiple MAC PDUs may be concatenated into a single transmission in either the uplink or downlink directions. Figure 25 illustrates this concept for an uplink burst transmission. Since each MAC PDU is identified by a unique CID, the receiving MAC entity is able to present the MAC SDU (after reassembling the MAC SDU from one or more received MAC PDUs) to the correct instance of the MAC SAP. MAC Management message, user data, and bandwidth request MAC PDUs may be concatenated into the same transmission.

In MR networks, downlink MAC PDUs on relay links and downlink MAC PDUs on access links shall not be concatenated into the same burst. RS may concatenate uplink MAC PDUs into a single transmission burst on the relay link.

*[Insert the following text into subclause 3:]*

access link: An 802.16 radio link that originates or terminates at an MS. The access link is either an uplink or downlink as defined in IEEE Std. 802.16-2004 and IEEE Std. 802.16e-2005.

relay link (R-Link): An IEEE Std. 802.16j radio link between an MR-BS and a RS or between a pair of RSs.

This can be a relay uplink or downlink.

### References

[1] IEEE C802.16j-06/178, "Enhanced Concatenation and MPDU Construction"

[2] IEEE C802.16j-06/237, "A Proposal for Construction and Transmission of MAC PDU in 802.16j"