

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	GNSS-equipped RS CDMA-based Ranging	
Date	2006-01-08	
Submitted		
Source(s)	<p>Kanchei (Ken) Loa, Yi-Hsueh Tsai, Voice: +886-2-2739-9616 Chih-Chiang Hsieh, Yung-Ting Lee, loa@iii.org.tw Hua-Chiang Yin, Shiann-Tsong Sheu, Frank C.D. Tsai, Youn-Tai Lee, Heng-Iang Hsu Institute for Information Industry 8F., No. 218, Sec. 2, Dunhua S. Rd., Taipei City, Taiwan.</p> <p>[add co-authors here]</p>	
Re:	IEEE 802.16j-06/034: "Call for Technical Proposals regarding IEEE Project P802.16j"	
Abstract	This contribution proposes procedures for GNSS-equipped RS CDMA-based ranging	
Purpose	Text proposal for 802.16j Baseline Document	
Notice	<p>This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.</p>	
Release	<p>The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.</p>	
Patent Policy and Procedures	<p>The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures <http://ieee802.org/16/ipr/patents/policy.html>, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair <mailto:chair@wirelessman.org> as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site <http://ieee802.org/16/ipr/patents/notices>.</p>	

GNSS-equipped RS CDMA-based Ranging

Global navigation satellite system (GNSS) is the generic name given to the satellite-based navigation systems including GPS (global positioning system), GLONASS (global navigation satellite system), and Galileo. GPS is the first passive one-way ranging satellite system to become operational. While GPS was under development by United States (US), the Soviet Union undertook to develop a similar system, called GLONASS. Like GPS, GLONASS was designed primarily for the military, and was also offered for civil use. In a later time, the European Union decided to develop a similar system planned to be under civil control. This system is called Galileo, which is now developed by European Space Agency (ESA).

This contribution describes CDMA-based ranging for GNSS-equipped RS with access station. In order to facilitate the incorporation of this proposal into IEEE 802.16j standard, specific changes to the baseline working document IEEE 802.16j-06/026r1 are listed below.

Text Proposal

6.3.10 Ranging

6.3.10.3 OFDMA based ranging

6.3.10.3.4 Relaying support for OFDMA based ranging

6.3.10.3.4.8 Support for GNSS-equipped RS OFDMA based ranging

6.3.10.3.4.8.1 GNSS-equipped RS contention-based initial/handover ranging

An GNSS-equipped RS that support initial/handover ranging process shall take a process similar to that defined in section 6.3.10.3.4.5 and 6.3.10.3.4.5 with the following modifications.

After GNSS-equipped RS is time synchronized, the RS can perform initial/handover ranging procedure during network entry. The RS initial/handover ranging process begin by sending a randomly selected RS CDMA initial/handover ranging code in a randomly selected ranging slot from available periodic ranging region, instead of sending it in the one from initial ranging region.

6.3.10.3.4.8.2 GNSS-equipped RS periodic ranging

After GNSS-equipped RS is time synchronized, the periodic ranging process should be omitted.