

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	Frame number synchronization between MR-BS and RS	
Date Submitted	2007-03-06	
Source(s)	Jung Je Son Hyoung Kyu Lim Panyuh Joo Samsung electronics Suwon, Korea Republic of	Voice: +82-31-279-5098 Fax: +82-31-279-5130 [mailto:jungje.son@samsung.com]
Re:	This is the response to a Call for Contributions, from IEEE802.16 Relay TG.	
Abstract	This contribution does propose the way to synchronize the offset of frame numbers between MR-BS and RS. And it proposes the mechanism for RS to know the frame number at which RS shall transmit PAG-ADV.	
Purpose	Discussion and Adoption of proposed text into baseline document by Relay TG.	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < http://ieee802.org/16/ipr/patents/policy.html >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < mailto:chair@wirelessman.org > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < http://ieee802.org/16/ipr/patents/notices >.	

Frame number Synchronization between MR-BS and RS

Jung Je Son, Hyoung Kyu Lim and Panyuh Joo
Samsung Electronics

Introduction

In IEEE802.16 TGe standard, BS's shall be synchronized at TDD. But, the transmitted frame numbers among neighbor BS's should be not synchronized. It is because the derivable number of uplink PUSC with different frame numbers is much more than the number with same frame numbers(refer to section 8.4.9.4.1). In system perspective, larger number of derivable subchannelizations is preferred for less probability of inter-cell interference.

The same theory will apply to the relay extension, i.e. the frame number among BS and RSs should be unsynchronized. As the BS controls the belonging RSs, the difference between the frame numbers of BS and RS shall be shared between BS and RS.

Furthermore, some MAC management message such as PAG-ADV, TRF-IND message shall be transmitted at a specific frame number per Paging Group or MS. Therefore, BS shall refer to the frame number offset of each RS in addition to processing delay when scheduling and forwarding MAC message to RSs. And the scheme that notifies the specific frame number to the RSs shall be provided.

In this contribution, the scheme enabling to share the frame number offset between BS and RS is proposed and the scheme that notifies the frame number to transmit MAC management message such as PAG-ADV and TRF-IND to RS is proposed.

Proposed Text Changes

Insert following text at the end of 6.3.2.3.7

When a RS enter network, the REG-REQ shall contain the following TLVs :

RS frame offset(11.7.27)

Insert following text at the end of 6.3.2.3.8

In response to REG-REQ from a RS, the REG-RSP shall contain the following TLVs :

RS frame offset(11.7.27)

Insert following text at the end of 6.39.16.2.

When a RS enters network, the RS shall negotiate the difference between frame numbers used by the MR-BS and the RS by transmitting REG-REQ including RS frame offset TLV. The MR-BS shall respond to the RS by including RS frame offset TLV in REG-RSP.

When a RS start and transmit its frame, the RS shall keep the difference to the frame number used by MR-BS as indicated RS frame offset TLV in REG-RSP.

Insert following text at the end of 6.3.21.7 Relay support for MS sleep mode.

When MR-BS transmit TRF-IND to a RS to forward to MSs under the RS. The MR-BS shall schedule and transmit TRF-IND in consideration of RS's processing delay, D_R , and RS frame offset so that the RS has enough time to decode and transmit TRF-IND and the delay is minimized until RS forward.

Insert new subclause at the end of 6.3.24.6

6.3.24.6.1 RS Broadcast Paging message.

When a paging is need to some MS's in a Paging Group, RSs belonging to the Paging Group shall be involved to transmit PAG-ADV to the MSs. The paging information shall be transmitted by MR-BS to RSs in a relay link. When MR-BS need to transmit paging information to RSs, MR-BS shall calculate the time to transmit in consideration of RS's processing delay, D_R , and RS frame offset so that RSs have enough time to decode and transmit PAG-ADV and paging delay will be minimized. When MR-BS transmits a paging information to RSs, it transmit PAG-ADV including RS tx frame number TLV to RSs. When a RS receive PAG-ADV including RS tx frame number TLV in a relay link, the RS shall restructure and transmit PAG-ADV by extracting the TLV and updating the length field at the frame number as specified by the TLV.

Insert new subclause at the end of 11.7.26

11.7.27 RS frame offset

RS frame offset indicates the offset value between frame number used by MR-BS and frame number used by the RS transmitting (receiving) REG-REQ(REG-RSP) with RS frame offset.

When the RS broadcast frame number in its frame, RS shall keep the offset to the frame number used by BS as indicated by this TLV.

<u>Name</u>	<u>Length</u>	<u>Value</u>	<u>Scope</u>
<u>RS frame offset</u>	<u>1 byte</u>	<u>Unsigned integer for frame offset of LSB 8 bit between Relay Station and Base Station.</u>	<u>REG-REQ , REG-RSP</u>

Insert new subclause at the end of 11.17.3

11.17.4 RS tx frame number

RS tx frame number indicates the frame number at which RS shall transmit the message including this TLV to MS's. When RS receive PAG-ADV including this TLV, RS shall restructure and transmit PAG-ADV by extracting this TLV and updating the length field at the frame number as specified by this TLV.

<u>Name</u>	<u>Length</u>	<u>Value</u>	<u>Scope</u>
<u>RS tx frame number</u>	<u>1 byte</u>	<u>Unsigned integer for LSB 8 bit of frame number at which RS shall transmit.</u>	<u>PAG-ADV</u>