

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	RS Periodic Ranging with Dedicated Ranging Code	
Date	2007-04-25	
Submitted		
Source(s)	<p>Kanchei (Ken) Loa, Yi-Hsueh Tsai, Voice: +886-2-2739-9616 Chih-Chiang Hsieh, Yung-Ting Lee, loa@iii.org.tw Hua-Chiang Yin, Shiann-Tsong Sheu, Frank C.D. Tsai, Youn-Tai Lee, Heng-Iang Hsu Institute for Information Industry 8F., No. 218, Sec. 2, Dunhua S. Rd., Taipei City, Taiwan. [add co-authors here]</p>	
Re:	IEEE 802.16j-07/013: "Call for Technical Comments Regarding IEEE Project 802.16j"	
Abstract	This contribution proposes RS Periodic Ranging with Dedicated Ranging Code	
Purpose	Text proposal for 802.16j Baseline Document	
Notice	<p>This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.</p>	
Release	<p>The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.</p>	
Patent Policy and Procedures	<p>The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures <http://ieee802.org/16/ipr/patents/policy.html>, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair <mailto:chair@wirelessman.org> as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site <http://ieee802.org/16/ipr/patents/notices>.</p>	

RS Periodic Ranging with Dedicated Ranging Code

Introduction

In 802.16e-2005, an MS transmits randomly selected periodic ranging code in a randomly selected ranging slot from available ranging region. In an MR system with transparent RSs, if a RS uses randomly selected periodic ranging code as an MS, the RS stays anonymously during periodic ranging process. Therefore, MR-BS cannot keep a stable relay path to the RS.

This contribution proposes assigning a dedicated periodic ranging for each RS such that a MR-BS can identify the RS and the associated relay path during periodic ranging process. In order to facilitate the incorporation of this proposal into IEEE 802.16j standard, specific changes to the baseline working document IEEE 802.16j-06/026r3 are listed below.

Text Proposal

6.3.10 Ranging

6.3.10.3 OFDMA based ranging

6.3.10.3.4 Relaying support for OFDMA based ranging

[\[Insert the following subclause 6.3.10.3.4.6 in page 77\]](#)

[6.3.10.3.4.6 RS periodic ranging and automatic adjustments with the access station](#)

[An RS that wishes to perform periodic ranging shall take the same steps described in 6.3.10.3.2, 6.3.10.3.4.1 and 6.3.10.3.4.2.](#)

[In an MR system with transparent RSs, the MR-BS may assign a dedicated periodic ranging code to a RS during network entry. In the CDMA periodic ranging process, the dedicated periodic ranging code is used instead of the \(MS\) periodic ranging code.](#)

[When the RS receives an unsolicited RNG-RSP message during network \(re-\)entry or handover procedure, it shall take the same steps described in 6.3.10.3.2, 6.3.10.3.4.3 and 6.3.10.3.4.4.](#)

11.19.1 CDMA Codes TLV

[\[Insert the following TLV in the table of 11.19.1 in page 118:\]](#)

Name	Type (1 byte)	Length	Value
<u>Transparent MR system CDMA Code</u>	<u>TBD</u>	<u>1</u>	<u>The TLV carries 1 byte ranging code in the following order - Dedicated periodic ranging code</u>