

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >		
Title	RS scheduling offset		
Date Submitted	2008-05-13		
Source(s)	David Comstock Huawei Technologies Co., Ltd.	E-mail:	dcomstock@huawei.com * http://standards.ieee.org/faqs/affiliationFAQ.html
Re:	IEEE 80216-08/020; IEEE 802.16 Letter Ballot Recirc #28c, on P802.16j/D4		
Abstract	Proposal for RS scheduling offset		
Purpose	Accept into P802.16j specification		
Notice	<i>This document does not represent the agreed views of the IEEE 802.16 Working Group or any of its subgroups. It represents only the views of the participants listed in the "Source(s)" field above. It is offered as a basis for discussion. It is not binding on the contributor(s), who reserve(s) the right to add, amend or withdraw material contained herein.</i>		
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.		
Patent Policy	The contributor is familiar with the IEEE-SA Patent Policy and Procedures: < http://standards.ieee.org/guides/bylaws/sect6-7.html#6 > and < http://standards.ieee.org/guides/opman/sect6.html#6.3 >. Further information is located at < http://standards.ieee.org/board/pat/pat-material.html > and < http://standards.ieee.org/board/pat >.		

RS scheduling offset

David Comstock

Huawei Technologies Co., Ltd.

Summary

- Provide the capability for the RS and its superordinate station to coordinate the size of transmit/receive windows within relay zones.
- In 802.16e, the BS is able to do this with the SS/MS since it has control over DL and UL scheduling for all zones.
- With an RS, scheduling is done by the superordinate zone and the RS.
- It is proposed to introduce a Scheduling Offset that is provided to the RS from its superordinate station.
- Please see S802.16j-08/113.ppt for supporting discussion.

Proposed text changes:

[Modify Section 6.3.2.3.5 as follows:](#)

6.3.2.3.5 RNG-REQ (ranging request) message

An RNG-REQ shall be transmitted by the SS at initialization and periodically to determine network delay and to request power and/or DL burst profile change. The format of the RNG-REQ message is shown in Table 42. The RNG-REQ message may be sent in initial ranging and data grant intervals.

[...]

The following TLV parameter shall be included in RNG-REQ message in order for an RS to request from its superordinate station the offset from the start of a relay zone that indicates the first possible RS resource allocation for that relay zone

Scheduling Offset

This TLV is provided by an RS to a superordinate station to request the Offset from the start of a relay zone that indicates the first possible RS resource allocation for that relay zone

[...]

[Modify Section 6.3.2.3.6 as follows:](#)

6.3.2.3.6 RNG-RSP (ranging response) message

An RNG-RSP shall be transmitted by the BS in response to a received RNG-REQ. In addition, it may also be transmitted asynchronously to send corrections based on measurements that have been made on other received data or MAC messages. As a result, the SS shall be prepared to receive a RNG-RSP at any time, not just following a RNG-REQ transmission. The format of the RNG-REQ message is shown in Table 43.

[...]

The following TLV parameter shall be included in RNG-RSP message in order for a superordinate station to provide the offset from the start of a relay zone that indicates the first possible RS resource allocation for that relay zone

Scheduling_Offset

This TLV is provided by a superordinate station to an RS and provides the Offset from the start of a relay zone that indicates the first possible RS resource allocation for that relay zone

[...]

Modify Section 11.5 as follows:

11.5 RNG-REQ management message encodings

The encodings in Table 569 are specific to the RNG-REQ message (6.3.2.3.5).

[...]

Name	Type(1 byte)	Length	Value(variable length)	PHY scope
[...]				
<u>Scheduling_Offset</u>	<u>1</u>		<u>Offset from the start of a relay zone that indicates the first possible RS resource allocation for that relay zone</u>	=

Modify Section 11.6 as follows:

11.6 RNG-RSP management message encodings

CID update encodings (11.7.10) and SAID update encodings (11.7.18) may be used in RNG-RSP for reestablishing connections. When CID update encodings or SAID update encodings are used in RNG-RSP, those will be included in the compound REG-RSP encodings TLV. When the compound SBC-RSP encodings and REG-RSP encodings are included in RNG-RSP for HO optimization, the target BS shall only include TLV fields which values are different from what are used in the serving BS. For the TLV fields that are not included in the compound SBC-RSP and REG-RSP encodings, the MS shall set the values according to what are used in the serving BS. The encodings in Table 572 are specific to the RNG-RSP message (6.3.2.3.6).

[...]

Name	Type (1 byte)	Length	Value(variable length)	PHY scope
Timing Adjust	1	4	Tx timing offset adjustment (signed 32-bit). The amount of time required to adjust SS transmission so the bursts will arrive at the expected time instance at the BS. Units are PHY-specific (see 10.3). The SS shall advance its burst transmission time if the value is negative and delay its burst transmission if the value is positive.	-

[...]

<u>Scheduling_Offset</u>	<u>1</u>		<u>Offset from the start of a relay zone that indicates the first possible RS resource allocation for that relay zone</u>	=
--------------------------	----------	--	---	---