

DL HARQ with Relays

IEEE 802.16 Presentation Submission Template (Rev. 8.3)

Document Number:

IEEE S802.16j-07/002

Date Submitted:

2007-01-15

Source:

Junichi Suga, Michiharu Nakamura
Fujitsu Laboratories Ltd.
Kamikodanaka 4-1-1,
Kawasaki, 211-8588, Japan

Voice: +81 44 754 2811
Fax: +81 44 754 2786
E-mail: suga.junichi@jp.fujitsu.com
michi@labs.fujitsu.com

Haihong Zheng, Yousuf Saifullah, Shashikant Maheshwari
Nokia
6000 Connection Drive, Irving, TX

Voice: 972 894 5000
E-mail: haihong.1.zheng@nokia.com
shashikant.maheshwari@nokia.com,
Yousuf.saifullah@nokia.com

Aik Chindapol, Yishen Sun, Jimmy Chui
Siemens Corporate Research
Princeton, NJ, USA

Voice: +1 609 734 3364
Fax: +1 609 734 6565
E-mail: aik.chindapol@siemens.com

Kyu Ha Lee
Samsung Thales
San 14, Nongseo-Dong, Giheung-Gu,
Yongin, Gyeonggi-Do, Korea 449-712

Voice: +82-31-280-9917
Fax: +82-31-280-1562
E-mail: kyuha.lee@samsung.com

Young-il Kim
ETRI
161, Gajeong-Dong, Yuseong-Gu, Daejeon, Korea 305-350

Voice: +82-42-860-5399
Fax: +82-42-861-1966
E-mail: yikim@etri.re.kr

Venue:

Session #47, London

Base Document:

IEEE C802.16j-07/002r1.pdf

Purpose:

This contribution proposes downlink HARQ procedure for relay.

Notice:

This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.

Release:

The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.

IEEE 802.16 Patent Policy:

The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures <<http://ieee802.org/16/ipr/patents/policy.html>>, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair <<mailto:chair@wirelessman.org>> as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site <<http://ieee802.org/16/ipr/patents/notices>>.

Introduction


- This contribution proposes downlink HARQ for non-transparent/two-hop transparent RS in centralized scheduling
- The concept is that RS retransmits HARQ data instead of MR-BS to reduce bandwidth and latency for retransmission

DL HARQ Problem in centralized scheduling

- In centralized scheduling, MR-BS does all the MAP allocation and scheduling
- In order to retransmit HARQ data from RS, MR-BS must know where the error is occurred in previous transmission


Solution for non-transparent RS

- DL transmission failure is indicated by the new orthogonal code on the UL ACK Channel
- The RS sends Code C_{k+1} to next RS, when the RS receives Code C_k from previous RS ($k \neq 0$)
- MR-BS knows where HARQ packet is lost from receipt Code




Solution for two-hop transparent RS

- In two-hop transparent RS, MS-BS sends preamble and DL/UL MAP to MS directly, and MR-BS receives ACK/NAK from MS directly
- RS also sends ACK/NAK to MR-BS when RS receives HARQ data



Alternative proposal for transparent RS

- In first transmission, MR-BS transmits HARQ data to MS directly and informs RS to monitor the transmission
- RS retransmits the HARQ data that RS captures in first transmission



Conclusion

- Described a problem for retransmission scheduling from a RS in the case of centralized scheduling
- Proposed a solution by sending new orthogonal code sequence in the UL ACK Channel for non-transparent case
- Proposed a solution by receiving ACK/NAK from MS and RS separately for two-hop transparent case
- Proposed a solution by RS monitoring HARQ data to support retransmission for two-hop transparent case
- Doesn't modify MS behavior
- Provides corresponding spec changes in C80216j-07_002r1.pdf