

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	Proposed Technical Requirements Guideline for IEEE 802.16 Relay TG	
Date Submitted	2006-10-11	
Source(s)	<p>Hyunjeong Kang, hyunjeong.kang@samsung.com Jaeweon Cho, Hyoung Kyu Lim, Changyoon Oh, Panyuh Joo Samsung Electronics</p> <p>Rakesh Taori, rakesh.taori@samsung.com Samsung Advanced Institute of Technology</p> <p>Peter Wang, peter.wang@nokia.com Yousuf Saifullah, Shashikant Maheshwari, Adian Boariu, Haihong Zheng Nokia Inc.</p> <p>Hyunjeong Lee, hyunjeong.hannah.lee@intel.com Wendy C. Wong, Sydir Jerry, Kerstin Johnsson, Frank R. Favichia Intel Corporation</p> <p>Aimin Zhang, zam@huawei.com Huawei Technologies</p> <p>Fang-Ching Ren, frank_ren@itri.org.tw Tzu-Ming Lin, Chie-Ming Chou, Ching-Tang Hsieh, I-Kang Fu, Jen-Shun Yang, Yu-Ching Hsu, Shiao-Li Tsao Industrial Technology Research Institute</p> <p>Koon Hoo Teo, teo@merl.com Toshiyuki Kuze, Yukimasa Nagai Mitsubishi Electric Corp. & MERL</p> <p>Peiyong Zhu, pyzhu@nortel.com Hang Zhang, Mark Naden, David Steer, Guo-Qiang Wang, Gamini Senarath, Dean Kitchener, Derek Yu, Wen Tong Nortel</p> <p>Edited by: Mike Hart & Jung Je Son, Relay TG Editors</p>	<p>Yong Sun, sun@toshiba-trel.com Dharma Basgeet Toshiba Research Europe Limited</p> <p>Youn-Tai Lee, lyt@nmi.iii.org.tw Shiann-Tsong Sheu, Kanchei (Ken) Loa, Heng-Iang Hsu, Yung-Ting Lee Institute for Information Industry (III)</p> <p>Aik Chindapol, Aik.chindapol@siemens.com Siemens Corporate Research, Inc.</p> <p>Yukihiro Takatani, takatani@sdl.hitachi.co.jp Seishi Hanaoka Hitachi, Ltd.</p> <p>Kaibin Zhang, kaibin.zhang@alcatel-sbell.com.cn, Gang Shen, JiminLiu, Wei Zou, Shan Alcatel Shanghai Bell Co.</p> <p>Kenji Saito, saito@kddilabs.jp Takashi Inoue, Mitsuo Nohara KDDI Masahito Asa, asa@motorola.com , Shyamal Ramachandran, Ariel Sharon, Nat Natarajan, Roger Peterson Motorola</p> <p>Byung-Jae Kwak, bjkwak@etri.re.kr Dong-Seung Kwon, Sung-Cheol Chang, Dong-Hyun Ahn ETRI</p>

Re:	
Abstract	<p>This document contains general high level and requirements for Relay TG specification.</p> <p>This document is a Task Group document to which the harmonized contribution document C802.16j-06/050r4 has been converted as one of the baseline documents defined during the 2nd Relay TG in Session #44.</p>
Purpose	<p>This document is a proposal for requirements to be considered while submitting technical proposals to Relay TG.</p>
Notice	<p>This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.</p>
Release	<p>The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.</p>
Patent Policy and Procedures	<p>The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures <http://ieee802.org/16/ipr/patents/policy.html>, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair <mailto:chair@wirelessman.org> as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site <http://ieee802.org/16/ipr/patents/notices>.</p>

Proposed Technical Requirements Guideline for IEEE 802.16j (Mobile Multihop Relay)

1. Introductory remarks

This document is submitted in response to the call for contributions on system requirements that was issued by the IEEE 802.16 Relay Task Group [1].

In this document, we provide

- general high level requirements
- a table for the mandatory requirements and
- a table for the optional requirements

In the mandatory requirements table, we further specify whether the function is mandatory for the MMR base station (MMR-BS) only, or whether it is mandatory for both MMR-BS and the relay station (RS). The term mandatory, in this document, refers to those requirements which should be fulfilled by RS and MMR-BS, as opposed to the optional requirements which may be specified by the amendment but implementations are not required to fulfil them. It is not necessarily the intention of this document to mandate the specification of all of the mandatory and optional requirements listed here in order to declare the amendment complete.

It is noted that the purpose of this requirements document, as well as the document that will eventually be adopted by the TG, will be to provide additional *guideline* for submitting proposals to Relay TG and will supplement the 802.16j PAR and 5 Criteria [2] documents, which provide the overriding requirements for Relay TG. The split into mandatory and optional parts, as well as the split of the function between MMR-BS and RS is intended to serve as an initial guideline and does not force the proponents to adhere to the split strictly.

2. General high level requirements

As a general requirement, which follows directly from the PAR and 5 criteria document, proposals to Relay TG shall not require modifications to the mobile stations (including subscriber stations). Proposals shall ensure backward compatibility with the mobile stations as specified in the legacy standard (i.e., IEEE Std 802.16-2004 and IEEE Std 802.16e-2005) to the extent that the relay operation is transparent to the mobile stations.

It is also hereby proposed that the submissions should minimize the modifications related to the MAC and OFDMA PHY as specified in the legacy standard. Proponents of contributions are encouraged to maximize the re-use of the procedures defined in the legacy standard.

As another general requirement, submitted proposals should support LOS as well as non-LOS operation for the deployment of the RS.

MMR-BS will distinguish itself from a BS, as defined in the legacy standard, in that it shall support the operations of RS, while at the same time maintaining full compliance with the legacy standard.

Hop count greater than or equal to 2 shall be supported. The specification shall consider 2-hop support mandatory while considering general multi-hop (>2) support optional.

RS shall not have mandatory requirement to support optional features as specified in the legacy standard. It is assumed that the RS will not generate user traffic of its own, but it is expected that the RS shall support the generation of control and management messages that are necessary for proper relay operation.

3. Functional requirements

The following table describes the mandatory and optional functional requirements.

* legacy: IEEE Std 802.16-2004 + IEEE Std 802.16e-2005

3.1 Mandatory functional requirements

Number	Name	Requirements	Subject (MMR-BS/RS)	Notes
M1	Capability management	Capabilities of RS shall be managed by MMR-BS.	MMR-BS (M) RS (M)	
M2	RS control	The specification shall define a mechanism for MMR-BS to control and manage RSs in the MMR cell.	MMR-BS (M)	
M3	PHY frame structure for backward compatibility with legacy 16 mobile station	The specification shall define a backward compatible frame structure that supports relay links while accommodating the legacy access links.	MMR-BS (M) RS (M)	
M4	RF part	The specification shall define OFDMA RF parameters necessary for the correct operation of the BS-RS link. RF parameters such as frequency band and channel bandwidth, as well as transmitter/receiver requirements including RS-emission and RS-susceptibility, shall be defined/specified for the BS-RS and RS-RS link.	MMR-BS (M) RS (M)	
M5	Baseband part	The specification shall define/specify baseband parameters/operation necessary for the correct operation of the BS-RS link. Baseband parameters such as FFT size, symbol CP, and baseband operations such as preamble transmission, synchronization, channel quality measurement shall be defined/specified for BS-RS link and RS-RS link.	MMR-BS (M) RS (M)	Preamble aspect TBD
M6	Duplexing Mode	The specification shall support either TDD or FDD for relay link	MMR-BS (M) RS (M)	
M7	RS network entry	The specification shall define network entry process for RS.	MMR-BS (M) RS (M)	

M8	MS network entry support	RS shall support network entry process for MS.	MMR-BS (M) RS (M)	
M9	Scheduling	The specification shall provide signaling to support MAC scheduling of data and control message transmission on relay and access links.	MMR-BS (M) RS (M)	Scheduling may be centralized, distributed, or a hybrid thereof.
M10	QoS support	The specification shall support QoS as defined in the legacy 16 system for multi-hop.	MMR-BS (M) RS (TBD)	
M11	Unicast data delivery	The specification shall support unicast data delivery via RS.	MMR-BS (M) RS (M)	
M12	Connection management	The specification shall support MS connections (i.e., CIDs) for multi-hop.	MMR-BS (M) RS (O)	
M13	MS handover support	RS shall support MS handover.	MMR-BS (M) RS (M)	
M14	Relay security	The specification shall define security mechanisms to ensure security between MMR-BS and RS, and between RSs and between RS and MS.	MMR-BS (M) RS (M)	

3.2 Optional functional requirements

Number	Name	Requirements	Subject (MMR-BS/RS)	Notes
O1	Multi-hop path selection	The specification shall define a mechanism to select, set up and maintain one or more multi-hop paths between an MMR-BS and MS.	MMR-BS (O) RS (O)	There can be centralized and distributed approaches to determine a relay path.
O2	Multicast/broadcast data delivery	The specification shall support multicast and broadcast data delivery via RS.	MMR-BS (O) RS (O)	

O3	ARQ support	The specification shall support ARQ of MS via RS.	MMR-BS (O) RS (O)	
O4	HARQ support	The specification shall support HARQ of MS via RS.	MMR-BS (O) RS (O)	
O5	Mobile RS handover support	The specification shall support RS with mobility and its subordinate MSs.	MMR-BS (O) RS (O)	
O6	Handover decision for subordinates stations	The specification shall allow the handover decision originated by a serving RS or MMR-BS on behalf of moving stations.	MMR-BS (O) RS (O)	
O7	MMR-BS authentication	The specification shall permit RS to authenticate MMR-BS when it joins an MMR network.	MMR-BS (O) RS (O)	
O8	PHY parameters	The specification shall allow an RS to use different PHY parameters on the relay and access links when they operate on the different RF frequency channels..	MMR-BS (O) RS (O)	
O9	Multiple antenna support	The specification shall allow the use of multiple antennae to enhance spectral efficiency of the system or extend the coverage.	MMR-BS (O) RS (O)	This includes MIMO, beamforming, transmit diversity, etc.
O10	Feedback mechanism support	The specification shall enable RS to support feedback mechanisms.	MMR-BS (O) RS (O)	
O11	Cooperative relay	The specification shall enable RS to participate in cooperative relay.	MMR-BS (O) RS (O)	
O12	Location information	The specification shall support RS to perform location update.	MMR-BS (O) RS (O)	
O13	Power saving	The specification shall support sleep/idle mode.	MMR-BS (O) RS (O)	
O14	Neighbor Detection	The specification shall enable the RS to detect its neighbor stations including the status and quality of radio link to each neighbor.	RS (O)	A neighbour station could be RS or MMR-BS.
O15	Flexible radio resource assignment	The specification shall provide a mechanism to support various forms of radio resource assignment.	MMR-BS (O) RS (O)	Sharing channels between access links and relay links, sharing channels between multiple relay links, using different channels for

				different links, frequency reuse between access links and relay links, etc.
O16	Control information processing	The specification may enable the RS to process and forward the DL and UL control information.	RS (O)	DL and UL control information includes DL/UL-MAP, DCD/UCD, MOB_NBR-ADV.
O17	Bandwidth request and allocation for the relay link	MMR-BS shall support the bandwidth request and allocation mechanism for RS.	MMR-BS (O) RS (O)	
O18	RS control	The specification may define mechanisms for both MMR-BS and RSs to learn the topology of the MMR-cell in which they operate.	MMR-BS (O) RS (O)	
O19	MAC PDU processing	RS may support MAC PDU processing.	MMR-BS (O) RS (O)	

4. References

- [1] Call for Comments and Contributions IEEE 802.16 Relay Task Group, IEEE 802.16j-06/006.
[2] Draft P802.16j PAR and Five Criteria, IEEE 802.16mmr-06/002r1.

Appendix A. Abbreviations and acronyms

ARQ:	Automatic Repeat Request
BS:	Base station
CID:	Connection Identifier
CP:	Cyclic Prefix
CQICH:	Channel Quality Information Channel
DL:	Downlink
FDD:	Frequency Division Duplex
FFT:	Fast Fourier Transform
HARQ:	Hybrid Automatic Repeat Request
LOS:	Line of Sight
MIMO:	Multiple Input Multiple Output
MMR-BS:	Mobile Multi-hop Relay Base Station
MS:	Mobile station
OFDMA:	Orthogonal Frequency Division Multiple Access
PDU:	Protocol Data Unit
QoS:	Quality of Service
RF:	Radio frequency

2006-10-11

IEEE 802.16j-06/016r1

RS: Relay Station
TDD: Time Division Duplex
UL: Uplink.