

Project	IEEE 802.16 Mobile Multihop Relay Study Group	
Title	Definition of terminology used in Mobile Multihop Relay	
Date Submitted	2006-01-06	
Source(s)	<p>Roger Peterson Kevin Baum Eugene Visotsky Motorola Labs, 1301 E. Algonquin Road, Room 2256A, Schaumburg, IL 60196 USA</p> <p>Masahito Asa Motorola Japan Ltd., 3-20-1 Minami- azabu, Minato ku, Tokyo, 106-8573, Japan</p> <p>Ariel Sharon Motorola Inc., 1301 E. Algonquin Road, Room 1232, Schaumburg, IL 60196 USA</p> <p>Shyamal Ramachandran Motorola Inc, 485 N. Keller Road, Suite 250, Maitland, FL 32751 USA</p> <p>David T. Chen Nat Natarajan Motorola Inc. 1501 W. Shure Drive, Arlington Heights, IL 60004 USA</p>	<p>r.peterson@motorola.com kevin.baum@motorola.com eugene.visotsky@motorola.com voice: +1 847-576-3892 voice: +1 847-576-1619 voice: +1 847-538-9458</p> <p>asa@motorola.com, voice: +81-3-5424-3156</p> <p>ariel.sharon@motorola.com voice: +1 847-576-3403</p> <p>shyamal.ramachandran@motorola.com voice: +1 407-659-5354</p> <p>david.t.chen@motorola.com nat.natarajan@motorola.com voice: +1 847-632-2664 voice: +1 847 632-6303</p>
Re:	IEEE P802.16 MMR SG	
Abstract	This contribution proposes definitions of terminologies to be used in the Mobile Multi-hop Relay project.	
Purpose	Discussion	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < http://ieee802.org/16/ipr/patents/policy.html >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < mailto:chair@wirelessman.org > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web	

site <<http://ieee802.org/16/ipr/patents/notices>>.

Definition of terminology used in Mobile Multihop Relay

1 Introduction

This contribution proposes definitions that could be used to clarify discussions within the IEEE 802.16mmr Task Group. These definitions were originally proposed in [1] which was presented at IEEE 802.16 Session 40 in November 2005. The following definitions are modified slightly from those presented in [1].

2 Proposed Definitions

The following definitions are recommended for use in all Mobile Multi-hop Relay discussions and documents:

Station: Any transceiver and associated control hardware and software designed as a component of an IEEE 802.16 WirelessMAN system.

Fixed Relay Station (FRS): A permanently installed station whose function is to relay information between a Subscriber or Mobile station and a Base Station or between other Relay Stations or between a Relay Station and a Base Station. An FRS is usually owned and maintained by a service provider and is most often installed by that service provider. An FRS may, however, be installed by a subscriber within that subscriber's place of business with the approval of a service provider. A connection to a power source is assumed. A backup power source may be provided. An FRS and all other relay stations are controlled by a centralized MMR controller. An FRS does not generate information of its own except for control information associated with the relay function.

Nomadic Relay Station (NRS): A relay station that is not permanently installed whose function is to relay information between a Subscriber or Mobile station and a Base Station or between other Relay Stations or between a Relay Station and a Base Station. Since the NRS is not permanently installed, it may be relocated from time to time. An NRS is assumed to be at a single location for periods of time at least as long as a typical subscriber session. An NRS may be owned and maintained by a service provider or by a subscriber. An NRS is typically installed by a subscriber in the subscriber's place of business or home with approval of a service provider. NRS antennas are mounted with the NRS itself (i.e. not on a separate structure). An NRS does not generate information of its own except for control information associated with the relay function. An NRS is controlled by a centralized MMR controller.

Mobile Relay Station (MRS): A fully Mobile Station whose function is to relay information between a Subscriber or Mobile station and a Base Station or between other Relay Stations or between a Relay Station and a Base Station. An MRS is typically owned and maintained by a service provider. An MRS may be installed, for example, in a bus or train for use by subscribers in these vehicles. An MRS does not generate information of its own except for control information associated with the relay function. An MRS is controlled by a centralized MMR controller. An MRS is powered by the vehicle in which it is installed.

Relay Station (RS): An FRS or NRS or MRS.

MMR-Subscriber Station (MMR-SS): A Subscriber Station that has been enhanced to enable it to function as a relay. The MMR-SS may be one element in a relay path between another Station and a Base Station. The entire relay path may include other MMR-SS, MMR-MS, and/or RS. The MMR-SS is owned by a subscriber and is controlled cooperatively by the subscriber and the service provider. The MMR-SS is a source and sink of information in addition to functioning as a relay for other subscriber's information.

MMR-Mobile Station (MMR-MS): A Mobile Station that has been enhanced to enable it to function as a relay. The MMR-MS may be one element in a relay path between another Station and a Base Station. The entire relay path may include other MMR-MS, MMR-SS, and/or RS. The MMR-SS is owned by a subscriber and is controlled cooperatively by the subscriber and the service provider. The MMR-MS is a source and sink of information in addition to functioning as a relay for other subscriber's information.

MMR-Base Station (MMR-BS): An IEEE 802.16e-2005 Base Station that has been enhanced to support Mobile Multihop Relay. An MMR-Base Station shall be fully compliant with IEEE 802.16e-2005. The MMR-BS, in addition to having all legacy IEEE 802.16e-2005 functionality, controls all relay functions in RS, MMR-SS, and MMR-MS.

Coverage Reliability: Coverage reliability for a system is the probability that a randomly located SS, MS, MMR-SS, or MMR-MS is able to achieve a specified level of service (QoS and data rate) when the system load is at a specified level. Coverage Reliability may be used as a metric for the comparison of different relay strategies.

Throughput: The rate at which user application information is transferred from source to destination. For the purpose of the MMR Task Group, throughput is the ratio of the total number of information bits in the payload portions of a sequence of Medium Access Control Packet Data Units (MAC-PDU) to the total average time required to transfer these bits. Throughput accounts for the resources required to transmit all control, preamble, and other overhead data but does not count this information in the number of subscriber information bits transferred. Throughput may be calculated for a single link (i.e. one hop) or may be calculated for a relayed path between a SS, MS, MMR-SS, or MMR-MS and a Base Station. Throughput is measured or calculated with adaptive modulation and coding functions operational. Throughput does not account for time in transmission queues; however throughput does account for resources used for ARQ and HARQ retransmissions. Therefore, throughput should be measured or calculated for a lightly loaded system. [Note that alternate definitions of throughput are possible that could take queuing delays and total latency into account.] The measure of throughput is bits per second per unit bandwidth.

System Data Capacity: The system data capacity is the maximum total average system information transfer rate that a Base Station can support while providing a specified Quality of Service to specified fraction of randomly placed users. Counted information includes only the payload portions of MAC-PDUs. Capacity accounts for the resources required to transmit all control, preamble, and other overhead data but does not count this information in the number of subscriber information bits transferred. Capacity is measured or calculated with adaptive modulation and coding functions operational. Transmissions from (or to) all user Stations directly or indirectly via RS are counted. Capacity is dependent upon the specific physical environment (e.g. buildings, foliage, terrain, and so on). The measure of capacity is bits per second per unit bandwidth per Base Station.

MMR Delay: Delay is the average time between the events of receiving one MAC-SDU at layer 2 of the transmitter and successfully receiving that MAC-SDU at the receiver. The time required to communicate ARQ acknowledgments to the transmitter is not counted. This definition includes the waiting times in the per-flow queues encountered by data prior to MAC-SDU transmission and takes into account delays associated with the ARQ process and scheduling.

Relay Enhanced SS/MS: An IEEE 802.16-2004 Subscriber Station or IEEE 802.16e-2005 Mobile Station that has been modified to function within a MMR enhanced IEEE 802.16 system. A Relay Enhanced SS/MS differs from a MMR-SS/MS in that it does not have the capability of functioning as a relay for data from other users.

Multihop Backhaul: A system architecture that is composed of one Base Station connected to wired infrastructure and multiple Base Stations without connections to the wired infrastructure. The Base Stations without wired infrastructure connections have wireless relay functionality to communicate with the Base Station that is connected to wired infrastructure. The wireless backhaul may use any viable spectrum possibly including the same spectrum used for BS to RS/MS communications.

3 References

- [1] M. Asa, R. Peterson, S. Ramachandran, D. T. Chen, N. Natarajan, "Recommendations for the Scope and Purpose of the Mobile Multihop Relay Study Group", document IEEE C802.16mmr-05/032, 11 November 2005.Revision History

4 Revision History

Version No.	Date	Remarks		Author
1.0	2006.01.06	Initial submission for MMR Study Group in Session 41 of IEEE 802.16		all authors